Feasibility of Repairing Mr. Brett Corsentino's Holita Dam, DAMID: 160214

Water Division 2, Water District 16

As Required by

State of Colorado, Department of Natural Resources, Division of Water Resources, Office of the State Engineer,

Dick Wolfe, P.E., DWR Director/State Engineer

Certified Mail: 7004 0550 0001 0704 4803

SUBJECT: Reservoir Storage Restriction

Dated: October 2, 2014

Prepared by:

Walter G. Bland, Engineering Technician and

Nicholas F. Koch, P.E. Agricultural Engineer 217 East Grand Avenue

La Junta, CO 81050 31 May 2017 FEASIBILITY STUDY



Water Project Loan Program

Department of Natural Resources

Application Type								
Prequalification (Attach 3 years of financial statements)	Loan Approval (Attach Loan Feasibility Study)							
Agency/Company Information								
Company / Borrower Name: Brett Corsentino								
Authorized Agent & Title: Corsentino Dairy FARM The								
Address: 2689 STATE Huy10;	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \							
Phone: (919) 568 0429 Email: beorsenting Hotmail, Com								
	cipality Incorporated?							
Vother: Dair Fary	FARMIS CCORD NO							
County: Hughan	Number of Shares/Taps:							
Water District: Upper Huerton District	Avg. Water Diverted/YrSupplemental Supplemental Suppl							
Number of Shareholders/Customers Served:	Current Assessment per Share \$ 940,00 (Ditch Co)							
Federal ID Number: 8407 309 34	Average monthly water bill \$ (Municipality)							
Contact Information								
Project Representative: Walt Bland								
Phone: (7/9) 940-2960 Email: N/A								
Engineer: Nick Koch								
Phone: (719) 469-6530 Email: Kock	DEER @ Yahoo. com							
Attorney:								
Phone: () Email:								
Project Information								
Project Name: Holita Reservior								
Brief Description of Project: (Attach separate sheets	if needed)							
See attacked 9 page report tit	led:							
Feasibility of Repairing Mr. Brett Corsentino's, Holita Dam								
DAMID: 160214 Water Division 2. Water District 16								
dated 31 May 2017								
General Location: (Attach Map of Area)	•							
1 See 9 page attachment 2	,							
Estimated Engineering Costs: See affactment	Estimated Construction Costs: See attachment							
Other Costs (Describe Above): 500 attachment	Estimated Total Project Costs: 500 attachment							
Requested Loan Amount:	Requested Loan Term (10, 20, or 30 years):							
#93,600	1017 10) Son Ophons							
Project Start Date(s) Design: Now Completed Signature	Construction: Oct 2017							
O . A	Return to: Finance Section Attn: Anna Mauss							
Brett Corsenbio	1313 Sherman St #718							
	Denver, CO 80203 Ph. 303/866.3449							
President/sec 5-31-17 Signature / Title Date	e-mail: anna.mauss@state.co.us							

Feasibility of Repairing Mr. Brett Corsentino's

Holita Dam, DAMID: 160214

Water Division 2, Water District 16

As Required by

State of Colorado, Department of Natural Resources,

Division of Water Resources, Office of the State Engineer,

Dick Wolfe, P.E., DWR Director/State Engineer

Certified Mail: 7004 0550 0001 0704 4803

SUBJECT: Reservoir Storage Restriction

Dated: October 2, 2014

Prepared by:

Walter G. Bland, Engineering Technician and
Nicholas F. Koch, P.E.
Agricultural Engineer
217 East Grand Avenue
La Junta, CO 81050

31 May 2017

Table of Contents

Overview	3
Project Map Location	. 5
Dam Water Storage Volume	. 6
Holita Ditch Water Rights	. 7
Project Description	. 8
Cost Estimate	. 9
Implementation Schedule	. 9
Conclusion	9


Overview

Mr. Brett Corsentino received a State of Colorado Dam Safety Branch Engineer's Inspection Report letter dated September 2, 2014 which assigned an UNSATISFACTORY Overall Condition to his Holita dam. The subject letter titled Reservoir Storage Restriction is detailed in the following information below:

- 1. In accordance with Colorado's Revised Statute 37-87-107, the Holita dam reservoir storage level is hereby restricted to elevation 6,117.5 feet, which is approximately 5 feet below the low point of the west dam crest noted from the reservoir capacity survey dated May 10, 2013 by Wachob & Wachob Inc., P.L.S. This storage restriction will result in a loss of approximately 224 acre-feet of water from the current 498 acre-feet of dam storage at the current spillway elevation which is 1.6 feet below the current dam crest. The existing spillway is currently not safe and part of the State of Colorado's restriction is the spillway shall be permanently lowered to a storage level which would then contain 274 acre-feet of water (498 224 = 274). This newly constructed spillway would need to have a minimum width of 16 feet.
- 2. The intent of the State of Colorado's storage restriction is to eliminate uncontrolled seepage from exiting on the dam's downstream slope which could lead to a dam failure if not corrected.
- 3. There apparently has been a history of non-compliance with the Colorado State Engineer's Orders concerning this dam. In 1972 the State Engineer required the dam spillway to be lowered and issued a storage restriction order in 1977. Then in 2007 the State Engineer's Dam Safety Branch recommended a 5 foot restriction. The dam spillway was not lowered, as required, in 1972 and it appears the owner has stored in excess of restrictions when water has been available.
- 4. The Division 2 Engineer is directed to enforce this Reservoir Storage Restriction and the owner, Mr. Brett Corsentino, is the responsible person to ensure compliance occurs. Failure to comply with this order will result in the State Engineer's Office initiating legal action in accordance with Colorado Revised Statute (C.R.S.) 37-87-114. This court action could result in the imposition of a fine of not less than \$500 per day and a District Court Order requiring the breach of the Holita Dam.
- 5. The required Reservoir Storage Restriction is the minimum action required to improve the safety of the Holita Dam. The owner, Mr. Brett Corsentino, is reminded he is liable for the safety of this structure (dam) in accordance with C.R.S. 37-87-104 and this Reservoir Storage Restriction does not relieve him of that liability. Also, be aware that this Reservoir Storage Restriction is not a permanent solution to the condition of the dam and action by the owner, Mr. Brett Corsentino, to repair or breach the structure (dam) is required. The letter from

The State Engineer's Office titled "Transmittal of Dam Safety Inspection Report, for Required Actions to improve the condition of the dam dated September 26, 2014" discusses more dam repair details.

6. Mr. Mark Perry, P.E., Dam Safety Engineer, is the primary contact for questions and issues concerning this Reservoir Storage Restriction. He can be reached by calling 719-542-3368, extension 2109.



HOLITA RESERVOIR

HUERFANO COUNTY, COLORADO



DEAD POOL



HORIZONTAL AND VERTICAL DATUM SHOWN HEREON OBTAINED BY GPS
OBSERVATION ON May 6, 2013
Coordnate Units
US survey feet
US survey feet
Vertical Datum-NAVD 29 Bench Mark A-22 = 6128.46

Horizontal Datum-WGS84

Pm Red Cap N 37" 39" 38.94" W 104" 44" 15.89" Elev=6131.25

ELEV.	SURFACE AREA (sq-ft)	VOLUME (cu-ft)	CUMM. VOLUME (cu-ft)	CUMM. VOLUME (ac-ft)
6109	0.00			
6110	347,885.81	173,942.91	173,942.91	3.99
6111	763,419.32	555,652.57	729,595.47	16.75
6112	1,200,770,81	982,095.07	1,711,690.54	39.30
6113	1,498,192.55	1,349,481.68	3,061,172.22	70.27
6114	1,704,401.83	1,601,297,19	4,662,469,41	107.04
6115	1,893,332.38	1,798,867.11	6,461,336.51	148.33
6116	2,102,815.54	1,998,073.96	8,459,410.47	194.20
6117	2,349,987.96	2,226,401.75	10,685,812.22	245.31
5118	2,601,120.98	2,475,554,47	13,161,366.69	302.14
6119	2,789,837.43	2,695,479.21	15,856,845.90	364.02
6120	2,920,892.09	2,855,364.76	18,712,210.66	429.57
6121	3,008,041,23	2,964,466.66	21,676,677.32	497.53

Lowest elevation=6107.10 feet. 12" Outlet Pipe = 6109 feet. 2.20 acre feet of non-usable storage.

Pm/Red Cap N 37"39"31.10 W 104"44'15.69" Elev=6122.04"

Wachob and Wachob, Inc.

Professional Land Surveyors, Colorado City, Colorado P.O. Box 19376, Zip 81019 Phone (719)-676-3665

Job Name: 2013-044.TRV

Scale: 1" = 100" Date: = 5-10-2013 Drawn By:WSB Job No. 2013-044

Corsentino Dairy Farm, Inc.

There are 3 center pivot sprinklers located on the property. The oldest sprinkler is a 1985 Valley which irrigates 60 acres; the next is a 1993 Lockwood which irrigates 62 acres; and finally is a 1995 T & L which irigates 103 acres. Both the Lockwood and the T & L were purchased new and are in excellent condition. The Valley was purchased used and is in good condition for its age.

Holita Ditch WATER RIGHTS:

1. Holita Ditch Reservoir
Priority #22, Atwood Decree
Appropriation Date: 3/20/1901
Adjudication Date: 2/23/1898 and 10/15/1901
Type: Storage
Total Right: 540 Acre Feet
% Owned: 23,280 Shares of 25,000 Shares
93.12% = 502.85 Acre Feet
Incorporated: April 18, 1940

2. Holita Ditch Enlargement Priority #417 and 417C, Killian Decree Appropriation Date: 5/23/1910 Adjudication Date: 10/10/1901 and 10/3/1921 Type: Stoage Total right: 130 Acre Feet % Owned: 93.12% = 121.06 Acre Feet Junior right, not used at this time.

38

30/

From: Brett Corsentio
When we met Wednesday
afternoon, 31 May 2017,
Walt Bland & Nick KOCH

Project Description

The purpose of this project is to make the necessary repairs to meet or exceed the minimum State of Colorado dam safety requirements for a low hazard earthen dam.

The main problem identified is the dam seepage along and several feet above the downstream embankment toe. The existing dam is probably 100 years old and it most likely did not have a core trench installed.

The Holita Dam Repair/Upgrade Planned Sequence of Events are as follows:

1st: Drain the reservoir and let the existing embankment dewater itself for a week or longer depending on site and weather conditions.

2nd: Strip the top and downstream side of the existing embankment to remove all woody vegetation and other undesirable materials.

3rd: Excavate a trench with 1.5 to 1 side slopes, an 8 ft. bottom width, and at least a 6 ft. depth below the original ground level (in the deep section of the dam), as directed, which is basically located in the middle of the downstream embankment slope. This includes approximately 25% wet excavation.

4th: An existing steel pipeline runs through the embankment and needs to be cut through and plugged with a plug/concrete slurry or equivalent to remove seepage issues/problems as identified/required by the Colorado State Engineer. This task would probably be best accomplished when the excavated trench cuts through this pipeline.

5th: Use nearby approved soil/earthen fill to backfill the excavated core trench in 6 inch lifts and compacted with the hauling and spreading scrapers splitting there tracks when placing the earthen fill lifts, as directed.

6th: Complete the compacted earthen fill to the line and grades on the approved plans.

7th: Excavate the new emergency spillway to the line and grades on the approved plans.

Cost Estimate


Items of Work	Quantity	Units	Un	it Cost	1	Amount
Site Survey	1	Job	\$	1,000	\$	1,000
Drain the Reservoir, Open the Headgate	1	Job	\$	100	\$	100
Site Stripping & Removal of Undesirables	1	Job	\$	2,000	\$	2,000
Trench Excavation, with 25% Wet Excavation	n 4,800	CY	\$	5.00	\$	24,000
Plug Existing Pipeline thru Dam	1	Job	\$	1,000	\$	1,000
Embankment Compacted Fill Placement	19,200	CY	\$	2.50	\$	48,000
Excavate the Emergency Spillway	1	Job	\$	500	\$	500
Engineering Design	1	Job	\$	4,000	\$	4,000
Stakeout and Construction Checks	1	Job	\$	4,000	\$	4,000
Contingencies	10%	Job	\$	9,000	\$	9,000
				Total is	\$	93,600

Implementation Schedule

The final design has just been completed and Mr. Corsentino's Loan may be approved before the reservoir is drained after the last irrigation run this fall. Depending on the availability of a contractor and the weather conditions, construction should begin this fall and be completed before a hard freeze.

Conclusion

This much needed low hazard dam upgrade is technically feasible and restores 224 acre feet of water back to Mr. Corsentino.



Job.

Job

Job.

Job.

Job

Cubic Yards

Cubic Yards

4,800

19,200

Drain the Reservoir, Open the Headgate.

Site Stripping & Removal of Undesirables

Plug Existing Pipeline thru Dam Dam Compected Earth Fit Placement

Excavate the Emergency Spilway

On Site Construction Checks

Trench Excevation, with 25% Wet Excevation

Dam Repair
for
Holita Reservoir
on
Corsentino Dairy Farm Inc. Lans
2689 State Highway 10
Walsanburg, Colorado
Dam Classification
Designed by & date: 11 15 Change 15
Approved by & date: 11 15 Change 15

20 mm | 10