



STATE OF
COLORADO

Musick - DNR, Jason <jason.musick@state.co.us>

Bowie No. 2 2nd Quarter Gob & Pond Reports

1 message

Tamme Bishop <tamme.jestover@bresnan.net>

Thu, Jul 14, 2016 at 9:58 AM

To: "Musick - DNR, Jason" <jason.musick@state.co.us>, Bill Bear <BBear@bowieresources.com>

Please see the attached 2nd quarter report. Let me know if you have any questions. <<...>>

Tamme Bishop, P.E.

JE Stover & Associates, Inc.

2352 N. 7th Street, Unit B

Grand Junction, CO 81501

970-245-4101



2nd Quarter 2016 Gob_Pond Inspections.pdf

2271K

J. E. STOVER & ASSOCIATES, INC.

2352 NORTH 7TH STREET, UNIT B
GRAND JUNCTION, COLORADO 81501
PHONE: (970) 245-4101, FAX: (970) 242-7908

MINE ENGINEERING
MINE RECLAMATION

CIVIL ENGINEERING
CONST. MANAGEMENT

Via Electronic Transmittal

July 14, 2016

Jason Musick
Division of Reclamation, Mining & Safety
1313 Sherman St., Room 215
Denver, CO 80203


Re: Bowie Resources, LLC, Bowie No. 2 Mine
Coal Mine Waste Banks & Instrumentation Monitoring
Pond Quarterly Inspections
Permit C-1996-083

Dear Mr. Musick:

Enclosed please find the referenced reports for the 2nd quarter of 2016.

Please call if you have any questions.

Sincerely,



Tamme Bishop, P.E.
Project Engineer

cc: Alysha Hernandez (DRMS)
Wm. A. Bear, Jr.

BOWIE RESOURCES, LLC

Bowie No. 2 Mine

Coal Mine Waste Bank Nos. 1, 2, & 3 Inspections - 2nd Quarter 2016

On June 30, 2016 a visual inspection of the Bowie No. 2 Mine coal mine waste banks was performed by the undersigned in accordance with Rule 4.10.2. This inspection includes Gob Pile Nos. 1, 2, and 3. Pile No. 1 is considered inactive. Pile no. 2 is located north of Bowie Road. Pile no. 3 is located south of Bowie Road.

I, Tamme Bishop, P.E., have a wide variety of experience in the design and construction of earth fill embankments. Nothing was observed during the inspection that would indicate the piles have a potential for failure. A small area of seepage was seen at the toe of gob pile #2, west of the haul road. On the far east side of gob pile #2, there were windrows of stacked gob. All organic material and topsoil has been removed ahead of the waste bank founding. The diversion ditches at gob pile #2 were inspected, both lower and upper, and found to be in good condition. The upper and lower diversion ditches at gob pile #3 were inspected, and were in good condition. The underdrain was flowing, and the water was clear. A new seep has been discovered at gob pile #3, north of the east drying area. At this time, the seep will not impact the long term stability of the gob pile. However, before final placement and compaction of gob in the footprint of the east drying area, an underdrain will be installed. Approval of the underdrain design was incorporated into the permit under Technical Revision No. 105.

At gob pile #2, the first bench east of the haul road is covered with soil. The second bench east of the haul road is mostly covered with a subsoil pile. Most of the third and forth benches east of the road are covered with soil. Soil has been placed on most of the second and third benches west of the haul road.

Most of the coal mine waste was generated from the preparation plant. Approximately 29,742 tons of gob were hauled during the quarter with an estimated 90% of the gob going to gob pile #3. Coal mine waste is to be placed in the piles in approximately horizontal lifts no more than 24-inches thick. The coal mine waste is dried and then spread and compacted by self propelled sheepsfoot compactors. Thirty-three compaction tests were taken at gob pile #2 during the quarter. No compaction tests were performed at gob pile #3 during the quarter.

The top of gob pile #2 serves as a drying area for end dumped gob. Gob is to be stacked to a maximum height of 20 feet, with a slope angle up to 1.5h:1v. A 25 foot buffer zone on the face of the gob pile will be maintained at all times. Gob will be spread and compacted to the currently approved slope configuration as soon as gob and weather conditions allow.

The westernmost and easternmost sections of gob pile #3 serve as drying areas for end dumped material. The purpose of the gob drying area is to provide an area for temporary storage of gob for drying purposes. End-dumped gob in the gob drying

areas is worked with dozers and track hoes to assist in the drying process.

At gob pile #3 it is necessary to stockpile gob material during the winter months then place and compact the stockpiled gob when weather allows. Stockpiling of gob can commence November 15 and end April 15. Winter stockpiled material will be re-handled and compacted by September 30. Beginning on October 1, the Operator should be compacting all material concurrently, until conditions again require stockpiling. The stockpiling dates listed above should be considered flexible and may change slightly from year to year based on weather conditions. The gob material will be stockpiled in rows generally running from northwest to southeast. The rows of gob will be placed in a controlled manner and overlap will be minimized so there is space between rows to allow for drainage to the southeast. There were no rows of stockpiled gob at gob pile #3 during the inspection.

The available volume of coverfill material is sufficient to meet the requirements of Rule 4.10.4(5). No coverfill was used for blending or other uses during the quarter.

A failure of the gob pile no. 1 would probably not be a hazard to human life. The pile is located above a large flat bench. The bench is approximately 80 to 150-feet wide directly below the pile. Additionally, the gob pile sediment pond is located below the pile. If the coal mine waste bank failed, the material would very likely be contained on the bench below the pile and or within the gob pile sediment pond.

A failure of gob pile no. 2 would probably not be a hazard to human life. A residential dwelling is located over 300-feet below pile no. 2. The piles are located above Bowie Road. A failure of the piles might damage Bowie Road and the Fire Mountain Canal but would not likely impact the residential dwelling.

A failure of gob pile no. 3 would not be a hazard to human life. A failure of the pile might damage the rail track below the pile.

I certify that to the best of my knowledge and belief, that the fill and other aspects of the coal mine waste banks have been constructed as permitted in the design approved by the DRMS.



Tammie Bishop
Colorado Professional Engineer
Registration No. 43402

Date

7-14-16

QUARTERLY POND INSPECTION REPORT

Operator:

Bowie Resources LLC

Quarter:

Second 2016

Mine:

Bowie No. 2 Mine - C-1996-083

Inspection Date:

30-Jun-16

Pond Identification

Type of Pond

B	C	D - Gob Pile	F - New Gob	J UTL East	K UTL West
Sediment	Sediment	Sediment	Sediment	Sediment	Sediment

Status During Inspection:

Approximate Water Level

Sediment (% remaining)

Outflow (cfs)

5944	5991	5971	5948	5848	Dry
75%	100%	90%	60%	40%	80%
0	0	0	0	0	0

Features

Problem

Problem

Problem

Problem

Problem

Problem

Yes/No

Yes/No

Yes/No

Yes/No

Yes/No

Yes/No

Erosional

Rills & Gulleys

Inadequate Vegetation

Outlet Channel Erosion

Burrows

Other

No	No	No	No	No	No
No	No	No	No	No	No
No	No	No	No	No	No
No	No	No	No	No	No
No	No	No	No	No	No

Structural

Differential Settling

Cracks or Slides

Seepage

Other

No	No	No	No	No	No
No	No	No	No	No	No
No	No	No	No	No	No
No	No	No	No	No	No

Appurtenant Structures

Defective Spillways

Dewatering Devices Clogged

Faulty Gates, Etc.

Other

No	No	No	No	No	No
No	No	No	No	No	No
No	No	No	No	No	No
No	No	No	No	No	No

Additional Comments

Design depth measured from pond bottom to invert of emergency spillway:

Pond B=10, C=10, D=10, J=10, K=3, F=10' TD

Pond Bottom Elevations B=5942, C=5990, D=5970, J=5846, F=5944, K=5819

Pond B held about 6 feet of water

Pond C had a water pool at the bottom of the pond.

Pond D contained a pool of water below the primary spillway.

Pond J held about 4 feet of water & sediment

Pond K was damp.

Pond F held about 5 feet of water and sediment

There were no mud pits open at the end of the quarter.



Maintenance Required: Ponds F, B and J will need to be cleaned of sediment this summer/fall

Name of Inspector: Jim Stover

Tamme Bishop

Colorado P. E. 43402 Date



Huddleston-Berry
Engineering & Testing, LLC

640 White Avenue, Unit B
Grand Junction, Colorado 81501
Phone: 970-255-8005
Fax: 970-255-6818
HuddlestonBerry@Bresnan.net

July 12, 2016
Project#01349-0001

Bowie Resources, LLC
43659 Bowie Road
Paonia, Colorado 81428

Attention: Mr. Bill Bear

Subject: Construction Materials Testing
2nd Quarter 2016
Bowie Mine No. 2
Paonia, Colorado

Dear Mr. Bear,

At your request, a representative of Huddleston-Berry Engineering and Testing, LLC (HBET) conducted field moisture and compaction testing, and laboratory moisture testing of coal mine waste materials placed at Bowie Mine No. 2 near Paonia, Colorado. Field testing was conducted on May 4th and June 29th, 2016. Soil compaction test reports, test location data, and laboratory optimum moisture and density (Proctor) data are attached.

We are pleased to be of service to your project. Please contact us if you have any questions or comments regarding the contents of this report.

Respectfully Submitted:
Huddleston-Berry Engineering and Testing, LLC

A handwritten signature in blue ink that reads "Michael A. Berry". The signature is fluid and cursive, with a long horizontal stroke at the end.

Michael A. Berry, P.E.
Vice President of Engineering

SOIL COMPACTION TEST REPORT

Task: Gob Pile Densities

Field vs. Lab Densities

Project No.: 01349 - 0001

Tested By: MS **Date:** 5/4/16

Project Name: Bowie Mine

Work Order No: 40624

Client Name: Bowie Resources

Authorized By: Client **Date:** 5/4/16

Placement Contractor: Bowie Resources


Reviewed By: MAB **Date:** 7/12/16

Contractor Representative: Ron

No.	Point No.	Elevation	Max. Dry Density (pcf)	Optimum Moisture (%)	Wet Density (pcf)	Speedy Moisture (%)	Field Dry Density (pcf)	Relative Field Comp.(%)	Tare Weight (g)	Wet Weight (g)	Dry Weight (g)	Lab Dry Density (pcf)	Lab Moisture (%)	Relative Lab Comp.(%)	
1	5444	6190.6	83.5	16.0	89.0	14.0	78	93	391.6	1300.3	1185.6	77.8	14.4%	93%	
2	5445	6192.5	83.5	16.0	89.7	-	-	-	180.6	1293.3	1151.2	78.2	14.6%	94%	
3	5446	VOID													
4	5447	6194.6	83.5	16.0	90.7	14.4	79	95	189.7	1613.8	1430.6	79.0	14.8%	95%	
5	5448	6194.3	83.5	16.0	90.3	-	-	-	192.1	1246.0	1107.9	78.5	15.1%	94%	
6	5449	6195.4	92.0	13.5	102.4	-	-	-	236.4	1680.8	1514.1	90.3	13.4%	98%	
7	5450	6193.5	92.0	13.5	93.0	-	-	-	191.7	1057.4	986.7	83.3	11.6%	91%	
8	5451	6193	92.0	13.5	98.7	-	-	-	312.5	1580.7	1443.6	87.7	12.6%	95%	
9	5452	6195.7	92.0	13.5	99.8	-	-	-	318.7	1245.8	1149.7	88.5	12.8%	96%	
10	5453	6191.2	92.0	13.5	94.9	-	-	-	237.1	1258.7	1155.6	85.1	11.5%	93%	
11	5454	6188.8	92.0	13.5	93.0	-	-	-	313.2	2063.5	1894.2	83.0	12.0%	90%	

Remarks: _____

Gob Pile Disturbed Area Outline



GOB PILE #2 COMPACTION TEST LOCATIONS

PREPARED FOR:



BOWTIE RESOURCES, LLC
BOWTIE NO. 2 MINE
P.O. BOX 483
PAONIA, COLORADO 81428

J. E. STOVER & ASSOCIATES, INC.
2355 N 7th St. Unit B
Grand Jct., CO 81501

GOB PILE #2
05/04/16

DESIGN BY:	DATE:	1/9/14
DRAWN BY:	J.E.S.	CHK'D BY:
SCALE:	NONE	
DIRECTORY:	D:\BOWTIE	DWG. NAME:

SOIL COMPACTION TEST REPORT

Task: Gob Pile Densities

Field vs. Lab Densities

Project No.: 01349 - 0001

Tested By: DM **Date:** 6/29/16

Project Name: Bowie Mine

Work Order No: 41596

Client Name: Bowie Resources

Authorized By: Client **Date:** 6/29/16

Placement Contractor: Bowie Resources

Reviewed By: MAB **Date:** 7/12/16

Contractor Representative: Ron

No.	Point No.	Elevation	Max. Dry Density (pcf)	Optimum Moisture (%)	Wet Density (pcf)	Speedy Moisture (%)	Field Dry Density (pcf)	Relative Field Comp.(%)	Tare Weight (g)	Wet Weight (g)	Dry Weight (g)	Lab Dry Density (pcf)	Lab Moisture (%)	Relative Lab Comp.(%)	
1	5455	6198.3	83.5	16.0	89.5	-	-	-	394.2	1423.3	1289.6	77.9	14.9%	93%	
2	5456	6197.5	83.5	16.0	89.0	-	-	-	393.5	1512.9	1367.3	77.4	15.0%	93%	
3	5457	6195.6	83.5	16.0	88.3	-	-	-	202.0	1338.6	1195.1	77.2	14.4%	92%	
4	5458	6193.9	83.5	16.0	86.9	-	-	-	388.3	1493.1	1351.6	75.8	14.7%	91%	
5	5459	6195.3	92.0	13.5	98.5	-	-	-	237.6	1382.5	1259.2	87.9	12.1%	96%	
6	5460	6197.9	83.5	16.0	86.1	-	-	-	387.3	1767.7	1597.3	75.5	14.1%	90%	
7	5461	6199.3	83.5	16.0	85.6	-	-	-	189.4	1408.3	1258.6	75.1	14.0%	90%	
8	5462	6201.1	83.5	16.0	85.7	-	-	-	193.9	1299.3	1161.6	75.0	14.2%	90%	
9	5463	6202.2	92.0	13.5	98.2	-	-	-	200.7	1232.5	1116.1	87.1	12.7%	95%	
10	5464	6202.8	92.0	13.5	98.3	-	-	-	238.5	1182.4	1085.2	88.2	11.5%	96%	
11	5465	6202	92.0	13.5	94.6	-	-	-	274.0	1508.5	1366.9	83.7	13.0%	91%	
12	5466	6200.6	92.0	13.5	93.2	-	-	-	193.3	1095.0	995.3	82.9	12.4%	90%	
13	5467	6196.7	83.5	16.0	86.9	-	-	-	189.8	1464.7	1305.2	76.0	14.3%	91%	
14	5468	6195.6	83.5	16.0	85.5	-	-	-	312.9	1523.3	1373.2	74.9	14.2%	90%	
15	5469	6198	83.5	16.0	92.9	-	-	-	316.6	1605.8	1440.9	81.0	14.7%	97%	

Remarks: _____

Gauge Number: 12122

Density Counts: 1561

Moisture Counts: 563

Record No. 18 S



SOIL COMPACTION TEST REPORT

Task: Gob Pile Densities

Field vs. Lab Densities

Project No.: 01349 - 0001

Tested By: Dm Date: 6/29/16

Project Name: Bowie Mine

Work Order No: 41596

Client Name: Bowie Resources

Authorized By: Client Date: 6/29/16

Placement Contractor: Bowie Resources

Reviewed By: MAB Date: 7/12/16

Contractor Representative: Ron

No.	Point No.	Elevation	Max. Dry Density (pcf)	Optimum Moisture (%)	Wet Density (pcf)	Speedy Moisture (%)	Field Dry Density (pcf)	Relative Field Comp.(%)	Tare Weight (g)	Wet Weight (g)	Dry Weight (g)	Lab Dry Density (pcf)	Lab Moisture (%)	Relative Lab Comp.(%)	
16	5470	6199.4	83.5	16.0	86.3	-	-	-	286.5	1586.3	1425.2	75.6	14.1%	91%	
17	5471	6200.7	92.0	13.5	94.2	-	-	-	238.4	1441.9	1317.6	84.5	11.5%	92%	
18	5472	6199.6	92.0	13.5	97.7	-	-	-	309.7	1620.9	1482.7	87.4	11.8%	95%	
19	5473	6197.2	92.0	13.5	94.3	-	-	-	392.5	1572.7	1449.6	84.5	11.6%	92%	
20	5474	6198	92.0	13.5	97.1	-	-	-	313.3	1371.2	1238.1	84.9	14.4%	92%	
21	5475	6201.6	92.0	13.5	100.1	-	-	-	236.8	1254.8	1148.1	89.6	11.7%	97%	
22	5476	6203.3	92.0	13.5	94.5	-	-	-	237.9	1419.3	1295.9	84.6	11.7%	92%	

Remarks: _____

Gauge Number: 12122




Density Counts: 1561

Moisture Counts: 563

Record No. 19 S

Gob Pile Disturbed Area Outline

Gob Pile Disturbed Area Outline



GOB PILE #2 COMPACTION TEST LOCATIONS

PREPARED FOR:



BOWTIE RESOURCES, LLC
BOWTIE NO. 2 MINE
P.O. BOX 483
PAONIA, COLORADO 81428

J. E. STOVER & ASSOCIATES, INC.
2355 N 7th St. Unit B
Grand Jct., CO 81501

GOB PILE #2 06/29/16

DESIGN BY:	DATE:	1/9/14
DRAWN BY:	J.E.S.	CHK'D BY:
SCALE:	NONE	
DIRECTORY:	D:\BOWIE	DWG. NAME:

Bowie Resources Gob Disposal Location of Compaction Tests				
Gob Pile #2				
	North	East	Elevation	Date
Point #				
5444	19440.95	36552.08	6190.59	5/4/2016
5445	19470.78	36631.78	6192.50	5/4/2016
5446	Void			5/4/2016
5447	19522.70	36718.92	6194.55	5/4/2016
5448	19536.87	36807.42	6194.26	5/4/2016
5449	19595.94	36824.39	6195.44	5/4/2016
5450	19572.17	36914.38	6193.47	5/4/2016
5451	19668.93	36911.58	6192.95	5/4/2016
5452	19732.59	37022.08	6195.67	5/4/2016
5453	19676.14	37062.32	6191.22	5/4/2016
5454	19615.99	37075.62	6188.80	5/4/2016
5455	19580.58	36928.23	6198.33	6/29/2016
5456	19532.56	36827.24	6197.49	6/29/2016
5457	19488.39	36731.65	6195.64	6/29/2016
5458	19440.34	36611.34	6193.88	6/29/2016
5459	19452.63	36553.63	6195.33	6/29/2016
5460	19499.69	36660.13	6197.85	6/29/2016
5461	19534.51	36740.71	6199.30	6/29/2016
5462	19579.52	36819.71	6201.11	6/29/2016
5463	19635.33	36878.99	6202.24	6/29/2016
5464	19707.24	36931.39	6202.80	6/29/2016
5465	19759.15	36990.46	6202.03	6/29/2016
5466	19688.31	37011.40	6200.58	6/29/2016
5467	19626.41	37034.24	6196.73	6/29/2016
5468	19633.18	37139.32	6195.62	6/29/2016
5469	19718.12	37142.35	6197.98	6/29/2016
5470	19815.83	37134.45	6199.42	6/29/2016
5471	19812.15	37231.16	6200.70	6/29/2016
5472	19733.39	37246.08	6199.57	6/29/2016
5473	19667.36	37249.42	6197.16	6/29/2016
5474	19684.00	37338.59	6197.96	6/29/2016
5475	19752.02	37346.15	6201.60	6/29/2016
5476	19817.07	37352.39	6203.33	6/29/2016

Total 33 Tests



Huddlestone-Berry Engineering & Testing, LLC
640 White Avenue, Unit B
Grand Junction, CO 81501
970-255-8005
970-255-6818

MOISTURE-DENSITY RELATIONSHIP

CLIENT Bowie Resources, LLC

PROJECT NAME Bowie Mine #2

PROJECT NUMBER 00489-0003

PROJECT LOCATION Paonia, CO

Sample Date: _____

Sample No.: _____

Source of Material: _____

Description of Material: _____

Test Method: _____

14-0680

Top of Gob #2

ASTM D698A

TEST RESULTS

Maximum Dry Density 92.0 PCF

Optimum Water Content 13.5 %

GRADATION RESULTS (% PASSING)

#200

#4

3/4"

ATTERBERG LIMITS

LL

PL


PI

Curves of 100% Saturation
for Specific Gravity Equal to:

2.80

2.70

2.60





Huddlestone-Berry Engineering & Testing, LLC
640 White Avenue, Unit B
Grand Junction, CO 81501
970-255-8005
970-255-6818

MOISTURE-DENSITY RELATIONSHIP

CLIENT Bowie Resources, LLC

PROJECT NAME Bowie Mine #2

PROJECT NUMBER 00489-0003

PROJECT LOCATION Paonia, CO

Sample Date: 10/29/2014
Sample No.: 14-0695
Source of Material: Gob #2 10-29-14
Description of Material: _____
Test Method: ASTM D698A

TEST RESULTS

Maximum Dry Density 83.5 PCF
Optimum Water Content 16.0 %

GRADATION RESULTS (% PASSING)

#200 #4 3/4"

ATTERBERG LIMITS


LL PL PI

Curves of 100% Saturation
for Specific Gravity Equal to:

2.80

2.70

2.60





Huddlestone-Berry
Engineering & Testing, LLC

640 White Avenue, Unit B
Grand Junction, Colorado 81501
Phone: 970-255-8005
Fax: 970-255-6818
Info@huddlestoneberry.com

July 12, 2016
Project#01349-0001

Bowie Resources, LLC
43659 Bowie Road
Paonia, Colorado 81428

Attention: Mr. Bill Bear

Subject: Summary of Instrumentation Monitoring
2nd Quarter 2016
Bowie Coal Waste Disposal Area No. 2
Paonia, Colorado

Reference: *Summary of Instrumentation Monitoring, 1st Quarter 2016, Bowie Coal Waste Disposal Area No. 2, Paonia, Colorado* by Huddlestone-Berry Engineering & Testing, LLC for Bowie Resources, LLC, April 13, 2016.

Stability Evaluation, Technical Revision #85, Gob Pile #2 Drying Area, Bowie No. 2 Mine by Huddlestone-Berry Engineering & Testing, LLC for Bowie Resources, LLC, June 3, 2014.

Dear Mr. Bear,

At the request of the Colorado Division of Reclamation, Mining and Safety (DRMS), Huddlestone-Berry Engineering & Testing, LLC (HBET) prepared this letter regarding quarterly monitoring of vibrating wire piezometers and inclinometers at Coal Waste Disposal Area No. 2 (CWDA No. 2) at the Bowie mine near Paonia, Colorado. The intent of the monitoring was to detect significant changes in the pore water pressures or significant displacements within the coal waste which may impact the stability of the waste pile.

Inclinometers

In 2005, three inclinometers, designated BG05-04, BG05-05, and BG05-07, were installed at CWDA No. 2 through the coal refuse and into the native foundation soils. The inclinometers have been monitored quarterly since August 2005. The 2nd Quarter 2016 monitoring was completed by DOWL on June 25th, 2016. The monitoring report prepared by DOWL includes a site plan showing the locations of the inclinometers and cumulative displacement curves relative to the baseline readings in 2005. Axis "A" reflects deformation with depth in the direction of anticipated movement perpendicular to the face of the gob. Axis "B" reflects deformation with depth parallel to the face of the gob.

Discussion of Inclinometer Monitoring

The latest inclinometer readings indicate no major movements since the last quarterly reading. As indicated in the DOWL report, some deflection was observed at BG05-05. However, the movement in the A-axis is zero at the top and bottom with a fairly uniform shift of the data along the length of the instrument. In general, it is unusual to see a fairly uniform shift along the 'middle' of the instrument with no movement at the top along the same axis. In addition, the movement along the B-axis is only in the upper portion of the instrument. Overall, HBET does not believe that the data represents instability in the gob. However, the 3rd Quarter 2016 monitoring data may provide additional information regarding the observed deflection.

Vibrating Wire Piezometers

Between 2005 and 2012, a total of ten vibrating wire piezometers were installed in CWDA No. 2. However, several of the piezometers have been damaged or have otherwise ceased to function. Currently, five of the piezometers are functional.

Monitoring of the functioning piezometers was completed by DOWL on June 25th, 2016. The attached monitoring report prepared by DOWL includes the piezometer monitoring data and the data is summarized in the following table.

VWP ID	Initial Pore Pressure (psi)	3/21/16 Pore Pressure (psi)	6/25/16 Pore Pressure (psi)	Difference Since Installation (psi)	Difference Since Last Reading (psi)
VWP-05	6.8	1.7	1.8	-5.0	+0.1
VWP-06	11.3	16.1	14.3	+3.0	-1.8
VWP-08	8.2	10.0	10.0	+1.8	0.0
VWP-09	2.8	2.8	2.9	+0.1	0.0
VWP-10	-1.9	-1.8	-1.8	+0.1	0.0

Discussion of Vibrating Wire Piezometers

VWP-05

VWP-05 was installed on August 3, 2005 near the toe of CWDA No. 2 adjacent to the access road/bench. The pore pressures recorded at VWP-05 have shown some seasonal fluctuations; however, the range of pore pressure changes is fairly small. In general, HBET does not believe that the pore pressures in VWP-05 are cause for concern regarding stability of the gob pile.

VWP-06

VWP-06 was installed on June 5, 2009 near the existing top of CWDA No. 2. The pore pressures recorded at VWP-06 have fluctuated since installation. In general, the fluctuations have been seasonal and reflect the level of coal mine waste placement activity on top of CWDA No. 2. Although an increase was recorded in the 1st Quarter 2016, the pore pressures recorded in VWP-06 decreased during the 2nd Quarter. In general, HBET does not believe that the measured pore pressures are an indication of any instability in CWDA No. 2.

VWP-08

VWP-08 was installed on June 5, 2009 at a slightly lower elevation than VWP-06. The pore pressures recorded at VWP-08 have fluctuated since installation. However, the fluctuations have generally been within a narrow range of values. The measured pore pressures are generally consistent with the level of coal mine waste placement activity at CWDA No. 2.

As indicated in the referenced *Stability Evaluation* report, the stability of CWDA No. 2 is sensitive to increases in pore pressures in VWP-08. An increase in the pore pressure of 7 psi in VWP-08 would result in a reduction of the Factor of Safety to below 1.5.

The current pore pressure reflects a piezometric surface elevation of approximately 6098 feet which is much less than the critical elevation of 6113 feet. As a result, HBET does not believe that the measured pore pressures in VWP-08 are any indication of instability in CWDA No. 2.

VWP-09

VWP-09 was installed on May 18, 2012 near the toe of CWDA No. 2. The pore pressures recorded at VWP-09 have been fairly steady since installation. This suggests that dewatering of the gob in this area is likely nearly complete. It is anticipated that the pore pressures at VWP-09 will remain fairly steady over time.

VWP-10

VWP-10 was installed on May 18, 2014 near the toe of CWDA No. 2. The pore pressures recorded at VWP-10 have been fairly steady since installation. This suggests that dewatering of the gob in this area is likely nearly complete. It is anticipated that the pore pressures at VWP-10 will remain fairly steady over time.

Site Visit Observations

HBET visited the site on July 1st, 2016. At the time of our visit, no coal mine waste was being actively placed. However, it appeared that some material had been moved around CWDA No. 2 during the last quarter. HBET did not observe any material from the wash plant being moved to CWDA No. 2. In general, CWDA No. 2 appeared to be in good condition and no evidence of instability or other adverse conditions were observed.

General

In general, based upon the results of the recent VWP and inclinometer monitoring data, and upon our observations at the site, HBET does not believe that there is any reduction in the stability of CWDA No. 2. Continued quarterly monitoring of piezometers and inclinometers is recommended.

We are pleased to be of service to your project. Please contact us if you have any questions or comments regarding the contents of this report.

Respectfully Submitted:

Huddlestone-Berry Engineering and Testing, LLC



Michael A. Berry, P.E.
Vice President of Engineering

ATTACHMENTS



July 7, 2016

Huddleston-Berry Engineering and Testing, LLC
640 White Avenue
Grand Junction, CO 81501
Attention: Mike Berry, PE

SUBJECT: Summary Report, Second Quarter 2016, Inclinator and Active Vibrating Wire Piezometer Data through June 2016, Bowie Mine No. 2, Coal Waste Disposal Area No. 2

Dear Mr. Berry,

DOWL conducted quarterly monitoring of inclinometers and vibrating wire piezometers at Coal Waste Disposal Area No. 2 (CWDA No. 2), Bowie Resources, LLC. This report is intended to cover the time period of April through June 2016. VWP and inclinometer data was obtained on 6-25-16 and 6-26-16, respectively. Per DRMS and your instructions, vibrating wire piezometer readings for all active piezometers are taken quarterly along with inclinometers.

Vibrating Wire Piezometers

Table 1. Summary of VWP Pore Pressure Readings

VWP ID #	Initial Pore Pressure (psi)	3/21/16 Pore Pressure (psi)	6/25/16 Pore Pressure (psi)	Difference Since Installation (psi)	Difference Since Last Reading (psi)
VWP-05	6.8	1.7	1.8	-5.0	+0.1
VWP-06	11.3	16.1	14.3	+3.0	-1.8
VWP-08	8.2	10.0	10.0	+1.8	0
VWP-09	2.8	2.8	2.9	+0.1	+0.1
VWP-10	-1.9	-1.8	-1.8	+0.1	0

The physical locations of the piezometers are shown on the attached Instrumentation Site Plan, Drawing 1. The graph of historical data through 5-21-14 is presented for reference as Figure 1. A graph of active piezometers only is presented as Figure 2.

Inclinometers

Three inclinometers, designated BG05-04, BG05-05, and BG05-07, were installed at CWDA No. 2 in August 2005. The inclinometers were installed through the coal refuse and approximately 20 feet into the native foundation soils. The physical locations of the inclinometers are shown on the attached Instrumentation Site Plan, Drawing 1. Baseline readings were taken on 8/10/05 and subsequent readings have generally been taken quarterly since that time. Displacement curves for the prior three readings are presented as attachments to this letter for each inclinometer. Axis "A" reflects deformation with depth in the direction of anticipated movement (downslope), while Axis "B" is orthogonal to Axis A. Based on our most recent site visit, there appears to be slight movement within inclinometer BGO5-05 which could be within

the accuracy tolerance of the equipment or which may require some scrutiny in the future. As described in previous reports, we are of the opinion that historic displacements indicated on the plots for the approximate upper ten feet of the inclinometers are likely due to placement of cover soil on the face of the waste bank during normal operations.


If you have any questions regarding this letter or the instrumentation monitoring at CWDA No. 2, please don't hesitate to contact me at (970) 497-8827 or wpandorf@dowl.com.

Respectfully Submitted,
DOWL

Wayne Pandorf, P.E.
Sr. Geotechnical Engineer

Enclosures: Instrumentation Location Plan, Drawing 1
Figure 1 – Active and Damaged Piezometer Data Graph through 5-21-14
Figure 2 – Active Vibrating Wire Piezometer Data Graph
Inclinometer Graphs BG05-04, BG05-05, and BG05-07

INSTRUMENTATION SITE PLAN



DRAWING
NUMBER

1

OF 1

DATE

2014

JOB NO.

13-231-001

Huddleston-Berry

BOWIE #2 GOB PILE

DELTA COUNTY, COLORADO

BUCKHORNGEOTECH

Civil, Structural, and Geotechnical Engineers, Inc.
222 South Park Avenue
Montrose, Colorado 81401
Phone (970) 249-6828 Fax (970) 249-0945

Bowie Mine No. 2 - CWDA No. 2 **Active and Damaged Vibrating Wire Piezometer Data**

Inception through 5-21-14




FIGURE 1

Bowie Mine No. 2 - CDWA No.2
Active Vibrating Wire Piezometer Data





FIGURE 2


BOWIE BG05_4 A

■ 8/10/2005 ● 6/27/2015 ▲ 9/27/2015
◆ 12/19/2015 ▼ 3/21/2016 ✦ 6/28/2016




BOWIE BG05_4 B

■ 8/10/2005 ● 6/27/2015 ▲ 9/27/2015
◆ 12/19/2015 ▼ 3/21/2016 ✦ 6/28/2016




BOWIE BG05_5 A

■ 8/10/2005 ● 6/27/2015 ▲ 10/3/2015
◆ 12/19/2015 ▼ 6/28/2016




BOWIE BG05_5 B

■ 8/10/2005 ● 6/27/2015 ▲ 10/3/2015
◆ 12/19/2015 ▼ 6/28/2016




BOWIE BG05_7 A

■ 8/10/2005 ● 10/3/2015 ▲ 12/19/2015
◆ 3/21/2016 ▼ 6/28/2016



BOWIE BG05_7 B

■ 8/10/2005 ● 10/3/2015 ▲ 12/19/2015
◆ 3/21/2016 ▼ 6/28/2016





Huddleston-Berry
Engineering & Testing, LLC

640 White Avenue, Unit B
Grand Junction, Colorado 81501
Phone: 970-255-8005
Fax: 970-255-6818
Info@huddlestonberry.com

July 12, 2016
Project#01349-0001

Bowie Resources, LLC
43659 Bowie Road
Paonia, Colorado 81428

Attention: Mr. Bill Bear

Subject: Summary of Instrumentation Monitoring
2nd Quarter 2016
Bowie Coal Waste Disposal Area No. 3
Paonia, Colorado

Reference: *Summary of Instrumentation Monitoring, 1st Quarter 2016, Bowie Coal Waste Disposal Area No. 3, Paonia, Colorado* by Huddleston-Berry Engineering & Testing, LLC for Bowie Resources, LLC, April 13, 2016.

Stability Evaluation, Gob Pile #3, Bowie No. 2 Mine by Huddleston-Berry Engineering & Testing, LLC for Bowie Resources, LLC, July 15, 2014.

Dear Mr. Bear,

At the request of the Colorado Division of Reclamation, Mining and Safety (DRMS), Huddleston-Berry Engineering & Testing, LLC (HBET) prepared this letter regarding quarterly monitoring of vibrating wire piezometers at Coal Waste Disposal Area No. 3 (CWDA No. 3) at the Bowie mine near Paonia, Colorado. The intent of the monitoring was to detect significant changes in the pore water pressures within the coal waste which may impact the stability of the waste pile.

Vibrating Wire Piezometers

Five vibrating wire piezometers were installed in CWDA No. 3 in October 2014. The piezometers were installed at three locations within the footprint of the gob pile. Monitoring of the functioning piezometers was completed by DOWL on June 25th, 2016. The attached monitoring report prepared by DOWL includes the piezometer monitoring data and the data is summarized in the following table.

VWP ID	Initial Pore Pressure 10/31/14 (psi)	03/21/16 Pore Pressure (psi)	06/25/16 Pore Pressure (psi)	Difference Since Installation (psi)	Difference Since Last Reading (psi)
VWP-A Deep	10.4	4.4	4.8	-5.6	+0.4
VWP-A Shallow	4.7	4.5	4.4	-0.3	-0.1
VWP-B Deep	0.2	-0.1	1.6	+1.4	+1.7
VWP-B Shallow	13.9	13.7	13.0	-0.9	-0.7
VWP-D	7.1	6.3	6.1	-1.0	-0.2

Discussion of Vibrating Wire Piezometers

VWP-A Deep

VWP-A Deep was installed on October 6, 2014 near the northern edge of CWDA No. 3. VWP-A Deep was installed in the foundation soil approximately eight feet below the bottom of the gob. The pore pressures recorded at VWP-A Deep generally decreased since installation until September 2015. Between September and December 2015, the pore pressures increased slightly. However, the pore pressures dropped significantly between December 2015 and March 2016. A slight increase was recorded since March; however, HBET does not believe that the pore pressure changes in VWP-A Deep are cause for concern regarding stability of the gob pile.

VWP-A Shallow

VWP-A Shallow was installed on October 6, 2014 near the northern edge of CWDA No. 3. VWP-A Shallow was installed approximately ten feet above the base of the gob. After installation, the pore pressures dropped until November 2014. Between November 2014 and September 2015, increases in the pore pressures were recorded at VWP-A Shallow. However, between September 2015 and June 2016, the pore pressures decreased. The increases through September 2015 likely reflect the active gob placement at CWDA No. 3 which slowed down and then stopped during the winter months and has not substantially resumed in 2016. In general, HBET does not believe that the pore pressure changes in VWP-A Shallow are an indication of instability in CWDA No. 3.

VWP-B Deep

VWP-B Deep was installed on October 6, 2014 in the west-central portion of CWDA No. 3. VWP-B Deep was installed in the foundation soil approximately ten feet below the bottom of the gob. Since installation, the pore pressures recorded at VWP-B Deep were fairly constant through March 2016. However a slight increase was recorded between March and June 2016. It is unclear why the pore pressures increased during the last quarter; however, the increase was not significant and HBET does not believe that the pore pressure changes in VWP-B Deep are an indication of instability in CWDA No. 3.

VWP-B Shallow

VWP-B Shallow was installed on October 6, 2014 in the west-central portion of CWDA No. 3. VWP-B Shallow was installed approximately ten feet above the base of the gob. Since installation, the pore pressures recorded at VWP-B Shallow have fluctuated with periods of slight increase and slight decrease. Between March and September 2015, the pore pressures at VWP-B Shallow increased. However, since September 2015, the pore pressures have decreased. The increases through September 2015 likely reflect the active gob placement at CWDA No. 3 which slowed down and then stopped during the winter months and has not substantially resumed in 2016. In general, HBET does not believe that the pore pressure changes in VWP-B Shallow are an indication of instability in CWDA No. 3.

VWP-D

VWP-D was installed on October 7, 2014 in the east-central portion of CWDA No. 3. VWP-D was installed approximately ten feet above the base of the gob. Since installation, the pore pressures recorded at VWP-D have fluctuated. There was a slight increase in pore pressures between June and September 2015 with a decrease since. This likely reflects active gob placement at CWDA No. 3 during the summer and early fall 2015 and then cessation of placement during the winter months. In general, HBET does not believe that the pore pressure changes in VWP-D are an indication of instability in CWDA No. 3.

Site Visit Observations

HBET visited the site on July 1, 2016. At the time of our visit, coal mine waste was not being placed at CWDA No. 3. Several small piles of wet gob were present on top of the pile; however, no equipment was actively operating. .

At the time of our site visit, a small quantity of water was emanating from the underdrain at CWDA No. 3. Due to the recent rains, HBET was unable to observe evidence of seepage along the south edge of the pile. In general, no evidence of instability of other adverse conditions were observed at CWDA No. 3

General

Based upon the results of the most recent VWP monitoring data and upon our observations at the site, HBET does not believe that there is any reduction in the stability of CWDA No. 3. Continued quarterly monitoring of piezometers and inclinometers is recommended.

We are pleased to be of service to your project. Please contact us if you have any questions or comments regarding the contents of this report.

Respectfully Submitted:

Huddlestone-Berry Engineering and Testing, LLC



Michael A. Berry, P.E.
Vice President of Engineering

ATTACHMENTS



July 7, 2016

Huddleston-Berry Engineering and Testing, LLC
640 White Avenue
Grand Junction, CO 81501
Attention: Mike Berry, PE

SUBJECT: Summary Report, Second Quarter 2016, Vibrating Wire Piezometers through June 2016, Bowie Mine No. 2, Coal Waste Disposal Area No. 3

Dear Mr. Berry,

DOWL conducted quarterly monitoring of installed vibrating wire piezometers at Coal Waste Disposal Area No. 3 (CWDA No. 3), Bowie Resources, LLC. This report is intended to cover the time period of April through June 2016. VWP data was obtained on 6-25-16. A graphic plot of measured pore pressures over time is presented on the attached Figure 1, and numerically in Table 1 below. Table 1 summarizes the initial, prior and current readings and the difference in individual pore pressures since installation and prior readings.

Table 1. Summary of Pore Pressure Readings

VWP ID #	Initial Pore Pressure 10/31/14 (psi)	3/21/16 Pore Pressure (psi)	6/25/16 Pore Pressure (psi)	Difference Since Installation (psi)	Difference Since Last Reading (psi)
VWP-A Deep	10.4	4.4	4.8	-5.6	+0.4
VWP-A Shallow	4.7	4.5	4.4	-0.3	-0.1
VWP-B Deep	0.2	-0.1	1.6	+1.4	+1.7
VWP-B Shallow	13.9	13.7	13.0	-0.9	-0.7
VWP-D	7.1	6.3	6.1	-1.0	-0.2

If you have any questions regarding this letter or the instrumentation monitoring at CWDA No. 3, please don't hesitate to contact me at (970) 497-8827 or wpandorf@dowl.com.

Respectfully Submitted,
DOWL

Wayne Pandorf, P.E.
Sr. Geotechnical Engineer
Enclosure: Figure 1 – Vibrating Wire Piezometer Data Graph

Bowie Mine No. 2 - CDWA No.3 **Vibrating Wire Piezometer Data**




FIGURE 1