

Eschberger - DNR, Amy <amy.eschberger@state.co.us>

Approval of SWSP Renewal Request for Lamb Lake (Plan ID 6135)

Vargas-Johnson - DNR, Javier <javier.vargasjohnson@state.co.us> To: Richard Raines <rraines@scwtp.org>, jennifer.petrzelka@greeleygov.com Tue, Dec 14, 2021 at 9:05 AM

Cc: Michael Hein - DNR <michael.hein@state.co.us>, Louis Flink - DNR <louis.flink@state.co.us>, Mark Simpson - DNR <mark.simpson@state.co.us>, Jared Ebert - DNR <jared.ebert@state.co.us>, Amy Eschberger - DNR <amy.eschberger@state.co.us>

Dear Mr. Raines and Ms. Petrzelka.

The Colorado Division of Water Resources has reviewed the application for the SWSP Request for Lamb Lakes (Plan ID 6135). Please see the attached letter for the conditions of approval.

Please let me know if you have any questions or concerns.

Sincerely,

Javier Vargas-Johnson Water Resources Engineer



COLORADO

Division of Water Resources Department of Natural Resources

P 303.866.3581x8227 1313 Sherman St., Suite 821 Denver CO 80203 javier.vargasjohnson@state.co.us | www.colorado.gov/water

Lamb Lakes Approval 2022.pdf 5775K



December 13, 2021

Richard T. Raines, P.H. Water Resource Manager Tri-Districts 4424 LaPorte Avenue Fort Collins, CO 80521 Ms. Jen Petrzelka Water Resource Operations Manager City of Greeley 1100 10th Street, Suite 300 Greeley, CO 80631

Re: Lamb Lakes Substitute Water Supply Plan (WDID 0302556) Lamb Lakes, DRMS Permit No. M-2018-039 (WDID 0303005, Plan ID 6135) Section 3, T7N, R69W, 6th P.M. Water Division 1, Water District 3, Larimer County

Approval Period: January 1, 2022 through December 31, 2023 Contact Information for Mr. Raines: 970-218-2738; <u>rraines@scwtp.org</u> Contact Information for Ms. Petrzelka: 970-350-9859; <u>jennifer.petrzelka@greelevgov.com</u>

Dear Mr. Raines & Ms. Petrzelka:

We have received your letter dated November 1, 2021 requesting renewal of a substitute water supply plan ("SWSP") in accordance with section 37-90-137(11), C.R.S., to cover depletions caused by gravel mining operations at a mine owned by the Tri-Districts and the City of Greeley ("Partners" or "Applicant") along the Cache la Poudre River known as Lamb Lakes (DRMS permit no. M-2018-039). This SWSP was previously known as the Partners Combined Substitute Water Supply Plan. The Treiber Lakes (DRMS permit no. M-2011-049) were previously included in the Partners Combined SWSP along with the Lamb Lakes. Liners for the Treiber Lakes were previously approved by the State Engineer's Office and there are no historical lagged depletions remaining from the site, therefore the site is no longer required to be included in a SWSP. The required fee of \$257 has been submitted (receipt no. 10016580).

SWSP Operations

The two Treiber Lakes and three Lamb Lakes were constructed under Colorado Division of Reclamation, Mining, and Safety ("DRMS") permit no. M-1977-439 (Home Office Pit). The Home Office Pit is operated by Martin Marietta Materials ("MMM") and is included in their Home Office Pit SWSP (WDID 0302517, Plan ID 2998), most recently approved in a letter dated April 1, 2021. The Treiber Lakes and the Lamb Lakes have officially been separated from the Home Office Pit mining permit boundaries and are now covered under DRMS Permit Nos. M-2011-049 and M-2018-039, respectively.

The Partners completed construction of a slurry wall around Treiber Lake A on August 7, 2013. The liner was approved on January 27, 2014 and re-approved (after intentional breaching) on August 19, 2015 as meeting the design standard. A slurry wall was completed around Treiber Lake B



in May, 2016. The liner for Treiber Lake B was approved on September 16, 2016 as meeting the design standard. Treiber Lakes A and B are both now classified as lined reservoirs in accordance with the 1999 SEO Guidelines. All lagged depletions associated with the Treiber Lakes have been replaced under previous SWSPs; therefore, the Treiber Lakes are no longer included in this SWSP.

The Lamb Lakes are located just northwest of the City of Fort Collins in Section 3, Township 7 North, Range 69 West of the 6th P.M. The only depletions required to be replaced during this SWSP period will be evaporative depletions from Lamb Lake B and Lamb Lake C. Replacement sources under this SWSP include releases of reusable water from mountain reservoirs, direct replacement from transmountain sources, reusable municipal return flows from East Larimer County District pursuant to case no. 2009CW282, water stored in the Overland Trail Reservoirs pursuant to case no. 2000CW251, water stored during free river conditions in the River Bluffs Reservoir, and reusable municipal return flows from the Fort Collins-Loveland Water District.

Depletions

Pursuant to section 37-90-137(11)(b), C.R.S., and 2009CW049, a gravel pit operator or property owner does not need to replace depletions that occur due to evaporation from groundwater exposed prior to January 1, 1981 as a result of open mining of sand and gravel ("pre-81 areas"), regardless of whether mining continued after December 31, 1980. Per the State Engineer's *General Guidelines for Substitute Supply Plans for Sand and Gravel Pits* updated April 1, 2011, pre-81 areas are tied to the physical location at which the groundwater was exposed prior to January 1, 1981 with the exception for areas whose reallocation was approved by the State Engineer prior to January 1, 2011. Previous SWSPs (prior to January 1, 2011) approved the pre-81 area without specific mention of its location. Therefore, the State Engineer's Office allowed the pre-81 area to be reallocated and memorialized under the May 11, 2011 SWSP approval. The applicant provided a map (*Figure 1 - Home Office Pit*) showing the specific location of the pre-81 area, which includes the 22.1 acres of groundwater exposed in Lamb Lake A. The credits for the pre-81 area are tied to the location identified on *Figure 1 - Home Office Pit* and may not be reallocated to other areas of groundwater exposure within the gravel pit boundary.

Evaporative depletions for the remaining lakes were calculated using a gross annual evaporation of 38 inches, with a credit of 10.58 inches for effective precipitation (based on an average annual precipitation of 15.12 inches for the Fort Collins weather station). You have estimated the surface area of groundwater exposed in the Lamb Lakes after December 31, 1980 as 61.8 acres which results in a net evaporative depletion of 141.19 acre-feet per year.

The monthly evaporative depletions to the Cache la Poudre River were lagged using the AWAS program developed by the IDS Group at Colorado State University. The parameters used in the model were an average distance from the centroid of each lake to the river (X) of 744 feet, an estimated distance from the site to the no flow aquifer boundary (W, measured perpendicular to the point of impact) of 6,500 feet, an aquifer transmissivity (T) of 160,000 gallons per day per foot, and a specific yield (S) of 0.2.

Lagged depletions due to past and projected operations at the site will total 141.19 acre-feet for 2022 and 141.19 acre-feet for 2023.

Replacements

The first source of replacement water to be utilized under this SWSP is reusable municipal return flows from the East Larimer County Water District ("ELCO"). ELCO is one of the Tri-Districts.

ELCO decreed its reusable municipal return flows in case no. 2009CW282 on June 29, 2012. Their accounting was approved by the Division Office on August 23, 2012. The reusable municipal return flows accrue to the Poudre River primarily at either the Fort Collins Waste Water Treatment Plants Nos. 1 & 2 (WDIDs 0302313 and 0302301, respectively) or the Boxelder Sanitation District Waste Water Treatment Plant (WDID 0302322).

All three waste water treatment plants ("WWTPs") are located downstream of the point of depletion and thus no transit loss will be applied to any releases made for this SWSP. However, there are water rights between the point of depletion and the WWTPs that have the potential to be injured should they place a call. Therefore, the ELCO municipal return credits are not a valid replacement source when an intervening water right places a call. Depending on which WWTP is supplying the municipal reuse credits, the intervening water rights may include the Fort Collins Irrigation Canal, Larimer and Weld Irrigation Canal, Lake Canal, Coy Ditch, Timnath Reservoir Inlet, Box Elder Ditch, and the Fossil Creek Reservoir Inlet. Because of this limitation, the applicant does not rely on ELCO municipal return credits in their projections, however they reserve the right to use this source when available and at their discretion.

The second source of replacement water consists of various supplies owned by the City of Greeley or the Tri-Districts identified as follows:

	1	
Owner	Decree	Description
City of Greeley	87CW042	Milton Seaman Reservoir Water stored under 87CW042.
City of Greeley		Windy Gap Units - Wholly consumable transbasin water pursuant to 61 units owned by Greeley in the Windy Gap Project.
City of Greeley	06CW258	Water pursuant to Greeley's 75 shares of stock in the Windsor Reservoir and Canal Company that entitle Greeley to water from the Laramie River System. A decree was entered in this case on January 4, 2012.
Tri-Districts	03CW421	Reusable supplies stored in an account in Chambers Reservoir for water decreed in case no. 03CW421.
Tri-Districts	89CW071	Transmountain water available from the Divide Canal and Reservoir Company in case no. 89CW071.
Bi-Districts	06CW259	Water pursuant to Bi-Districts's 75 shares of stock in the Windsor Reservoir and Canal Company that entitle Bi-Districts to water from the Laramie River System. A decree was entered in this case on January 22, 2013.
Tri-Districts	03CW422	Transmountain water available from ownership in Water Supply and Storage Company and released from Chambers Reservoir decreed in case no. 03CW422.

Water will primarily be released from Greeley's mountain reservoirs although the Tri-Districts may supplement the Greeley releases. The applicant has included a 5% transit loss through the Poudre Canyon and a 0.25% per mile transit loss from the mouth of the Poudre Canyon to the Lamb Lakes for a total transit loss of 7.8%. This loss will be applied to Greeley's and the Tri-Districts' replacement supplies unless the Partners receive prior approval from the District 3 Water Commissioner to make replacements downstream of the Lamb Lakes. Appropriate transit losses are subject to the Water Commissioner's approval for any replacements made upstream of the Lamb Lakes.

The third source of replacement water is water stored pursuant to the Overland Trail Reservoirs conditional water storage right decreed in case no. 2000CW251. The Overland Trail Reservoir system (WDID 0303312) consists of a series of existing off-channel lined gravel pits, located in portions of Sections 32 & 33, Township 8 North, and Section 3, Township 7 North, all in Range 69 West of the 6th P.M. (*see Figure 1: Overland Trail Reservoir Project*). The liners for Overland Ponds 1-5 and Treiber Lakes A and B have been approved by this office. The Overland Trail Reservoirs are filled with water diverted from the Cache la Poudre River via the New Mercer Ditch, Larimer County Canal No. 2, the Overland Trail Diversion Structure, Munroe Gravity Canal (a/k/a North Poudre Supply Canal), and/or the Pleasant Valley Pipeline. The total decreed capacity of the Overland Trail Reservoirs is 10,962 acre-feet, conditional. Replacement water from the Overland Trail Reservoirs is proposed to be pumped into the Cache la Poudre River at approximately the same location as the Lamb Lakes.

The fourth source of replacement water is water stored in priority in the River Bluffs Lake (WDID 0303324) located at the Three Bells Veldman Property. The River Bluffs Lake is primarily located in the W½ of the NE¼ and the E½ of the NW¼ of Section 13, Township 6 North, Range 68 West of the 6th P.M., and was mined under the Three Bells gravel pit (DRMS Permit No. M-1979-191). The reservoir was lined with a compacted clay liner and the liner was approved by the State Engineer's Office on March 6, 2015 as meeting the design standard referenced in the August 1999 State Engineer Guidelines for Lining Criteria for Gravel Pits (1999 SEO Guidelines). The reservoir capacity is approximately 1,038 acre-feet.

On March 23, 2018, ELCO and the North Weld County Water District ("NWCWD") purchased River Bluffs Lake. ELCO and NWCWD are two entities of the Tri-Districts. As part of the purchase ELCO and NWCWD obtained the right to use up to 500 acre-feet of the water stored in River Bluffs Lake. In addition, ELCO and North Weld obtained a water storage right in case no. 2019CW3059 for a volume of 964 acre-feet of water that may be used for augmentation purposes. To date, no water has been stored under this right. The Partners are proposing to use water released from storage in River Bluffs Lake for replacement of evaporative depletions at the Lamb Lakes if the calling right is located downstream of the River Bluffs Lake. Releases of replacement water will be made at or above the point of the downstream calling right. Releases from River Bluffs Lake will be delivered into the Cache la Poudre River in the SW¼ of the SW¼ of Section 13, Township 6 North, Range 68 West of the 6th P.M. No transit losses associated with the releases from River Bluffs Lake will be assessed under this SWSP since the releases will be made downstream of the point of depletion (i.e., downstream of the Lamb Lakes).

Water has been stored in River Bluffs Lake during free river periods since 2015 through the present. Water stored in the reservoir is also being used for replacements of depletions at the Three Bells site. The temporary pump must be equipped with a totalizing flow meter to record daily discharge volumes to the river. The applicant shall obtain <u>prior</u> permission from the District 3 Water Commissioner when making releases from the River Bluffs Lake. Credit will not be given to any releases not measured and recorded to the satisfaction of the District 3 Water Commissioner or Division Engineer.

The fifth source of replacement water is reusable municipal return flows derived from Fort Collins-Loveland Water District's customers' indoor water use discharged from the South Fort Collins

Sanitation District wastewater treatment plant ("SFCWD WWTP"), as quantified and authorized for replacement purposes in Fort Collins-Loveland Water District's Substitute Water Supply Plan (WDID 0302566, Plan ID 6222). The SFCWD WWTP (aka "Tridistricts WWTP 1", WDID 0302323), is located in the NW¼ of the SE¼ of Section 17, Township 6 North, Range 68 West of 6th P.M. Treated effluent from the SFCWD WWTP is discharged directly into Fossil Creek Reservoir and is passed through the Reservoir to the Fossil Creek Reservoir Outlet where it is discharged to Cache la Poudre River in the NE¼ of the SW¼ of Section 11, Township 6 North, Range 68 West of 6th P.M. This source may only be used when the calling right is located at or below the Fossil Creek Reservoir Outlet, and no transit loss will be assessed as the replacement water will be delivered downstream of the point of depletion.

A total of 152.20 acre-feet of replacement water is proposed to be released in both 2022 and 2023, which includes 11.01 acre-feet of transit losses each year, conservatively assuming that all replacements will be released from Greeley's mountain reservoirs. A monthly breakdown of depletions, transit loss, and replacement releases is shown on the attached Table 4.

Long Term Augmentation

All sand and gravel mining operators must comply with the requirements of the Colorado Reclamation Act and the Mineral Rules and Regulations for the protection of water resources. To prevent long term injurious stream depletions that result from mining related exposure of groundwater, future operations will include constructing slurry walls around each of the three ponds to construct water storage reservoirs. The Partners obtained a conditional water right for these future reservoirs (collectively known as the Overland Trail Reservoirs) in water court case no. 2000CW251. The owners and operators of the mining site are municipal entities and thus a bond to cover the cost of lining or backfilling the pits is not required.

Conditions of Approval

I hereby approve this substitute water supply plan, in accordance with section 37-90-137(11), C.R.S., subject to the following conditions:

- 1. This plan shall be valid for the period of January 1, 2022 through December 31, 2023, unless otherwise revoked or modified. If either lagged or projected depletions will extend beyond the plan's expiration date, a renewal request must be submitted to this office with the statutory fee (currently \$257) no later than November 1, 2023. If a renewal request is received after the expiration date of this plan, it may be considered a request for a new SWSP, in which case a \$1,593 filing fee will apply.
- 2. Well permit no. 75423-F was obtained for the Home Office Pit by Lafarge to cover their use and exposed pond surface area of the gravel pit in accordance with sections 37-90-137(2) and (11), C.R.S. This permit is now held by Martin Marietta Materials and currently covers evaporation from the three Lamb Lakes that are the subject of this SWSP.
- 3. The total surface area of the groundwater exposed in the Lamb Lakes after December 31, 1980 must not exceed 61.8 acres, which results in an evaporative loss of 141.19 acre-feet per year. Should the total surface area exposed after December 31, 1980 exceed this amount, an amendment will need to be filed with this office.

- 4. Approval of this plan is limited to covering evaporative losses from exposed groundwater surface areas and lagged depletions. Any additional uses must first be approved by this office.
- 5. All releases of replacement water must be sufficient to cover all out-of-priority depletions in time, place, and amount and must be made under the direction and/or the approval of the water commissioner. Notice must be provided and approval made by the water commissioner at least 48 hours prior to the release of replacement water, or as required by the water commissioner. The release of replacement water may be aggregated to maximize beneficial use. The water commissioner and/or the division engineer shall determine the rate and timing of an aggregated release.
- 6. The replacement water that is the subject of this SWSP cannot be sold or leased to any other entity. As a condition of subsequent renewals of this SWSP, the replacement water must be appurtenant to this site until a plan for augmentation is obtained. All replacement water must be concurrent with depletions in quantity, timing and locations.
- 7. The name, address, and phone number of the contact person who will be responsible for the operation and accounting of this plan must be provided on the accounting forms submitted to the division engineer and the water commissioner.
- 8. Conveyance loss for delivery of augmentation water is subject to assessment and modification as determined by the water commissioner or division engineer.
- Adequate accounting of depletions and replacements must be provided to the division engineer in Greeley (<u>DNR_Div1Accounting@state.co.us</u>) and the water commissioner (Mark Simpson at <u>Mark.Simpson@state.co.us</u>) on a monthly basis, unless otherwise approved in writing by the water commissioner.

In addition, the Applicant shall verify that the entities providing replacement water for this plan have included and shown this use in their monthly accounting submitted to this office. For this plan those entities are the City of Greeley (WDID 0303330), the East Larimer County Water District (WDID 0302563), and the Fort Collins-Loveland Water District (WDID 0302566).

- 10. The State Engineer may revoke this SWSP or add additional restrictions to its operation if at any time the State Engineer determines that injury to other vested water rights has occurred or will occur as a result of the operation of this SWSP. Should this SWSP expire without renewal or be revoked prior to adjudication of a permanent plan for augmentation, all use of water under this SWSP must cease immediately.
- 11. The approval of this SWSP does not relieve the Applicant and/or the landowner of the requirement to obtain a water court decree approving a permanent plan for augmentation or mitigation to ensure the permanent replacement of all depletions, including long-term evaporation losses and lagged depletions after gravel mining has ceased. If a lined pond results after reclamation, replacement of lagged depletions shall continue until there is no longer an effect on stream flow. Granting of this SWSP does not imply approval by this office of any such court application(s).
- 12. In accordance with amendments to section 25-8-202(7), C.R.S., and "Senate Bill 89-181 Rules and Regulations" adopted on February 4, 1992, the State Engineer shall determine

whether the substitute supply is of a quality to meet requirements of use to senior appropriators. As such, water quality data or analysis may be requested at any time to determine if the water quality is appropriate for downstream water users.

13. The decision of the state engineer shall have no precedential or evidentiary force, shall not create any presumptions, shift the burden of proof, or serve as a defense in any pending water court case or any other legal action that may be initiated concerning this SWSP. This decision shall not bind the state engineer to act in a similar manner in any other applications involving other SWSPs, or in any proposed renewal of this SWSP, and shall not imply concurrence with any findings of fact or conclusions of law contained herein, or with the engineering methodologies used by the Applicant.

If you have any questions concerning this approval, please contact Javier Vargas-Johnson in Denver at (303) 866-3581 or Michael Hein in Greeley at (970) 352-8712.

Sincerely,

and Runke

for Jeff Deatherage, P.E. Chief of Water Supply


Attachments: Figure 1 - Home Office Pit Figure 1 - Overland Trail Reservoir Project Tables 1 - 4

Cc: Michael Hein, Lead Assistant Division Engineer; <u>Michael.Hein@state.co.us</u> 1809 56th Avenue, Greeley, CO 80634, (970) 352-8712

Mark Simpson, Water Commissioner, Water District 3; <u>Mark.Simpson@state.co.us</u>


Louis Flink, Tabulation/Diversion Records Coordinator, Louis.Flink@state.co.us

Amy Eschberger, Division of Reclamation Mining and Safety, <u>Amy.Eschberger@state.co.us</u>



N105105Lafarge Water Planning\ Drawings\G LS\ Pre-1981\ Home_Office_Pre81_AeriaLmsd

Printed: April 13, 2011 by JMD










Miles

0.6



By: Greeley GIS, jmt Date: 7/14/2011 File: OverlandPonds2011 2009 NAIP Aerial Imagery





Poudre River Trail

Proposed Overland Trail Reservoirs / Gravel Pits

Fill Sequence

Approximate Location of Structures of Interest in Case No. 00CW251 Table 1 Tri-Districts and City of Greeley Lamb Lakes, M-2018-039 (WDID 0302556, Plan ID 6135)

Calculated Evaporative Losses at Lamb A, B, and C

Total Exposed Water Surface =	83.9	acres
Pre-1981 Exposed Surface Area =	22.1	acres
Augmented Water Surface =	61.8	acres
Annual Precipitation =	15.12	inches - Taken from Fort Collins Weather Station
Gross Annual Evaporation =	38	inches - Taken from NOAA Technical Report NWS 33

	(1)	(2)	(3)	(4)	(5)	(6)
Month	Percent of Annual Evaporation	Gross Lake Evaporation	Annual Precipitation	Effective Precipitation	Net Lake Evaporation	Total Lake Evaporation
	LVaporation	(ft)	(in)	(ft)	(ft)	(AF)
Nov	4.0%	0.13	0.59	0.03	0.09	5.70
Dec	3.0%	0.10	0.49	0.03	0.07	4.10
Jan	3.0%	0.10	0.36	0.02	0.07	4.57
Feb	3.5%	0.11	0.48	0.03	0.08	5.12
Mar	5.5%	0.17	1.20	0.07	0.10	6.44
Apr	9.0%	0.29	1.98	0.12	0.17	10.48
May	12.0%	0.38	2.72	0.16	0.22	13.68
Jun	14.5%	0.46	1.83	0.11	0.35	21.78
Jul	15.0%	0.48	1.60	0.09	0.38	23.59
Aug	13.5%	0.43	1.44	0.08	0.34	21.23
Sep	10.0%	0.32	1.30	0.08	0.24	14.88
Oct	7.0%	0.22	1.13	0.07	0.16	9.63
Totals	100.0%	3.17	15.12	0.88	2.28	141.19

Notes:

(1) Based on SEO SB120 guidelines for evaporation rates at elevations below 6500 feet.

(2) Based on NOAA Technical Report NWS 33 and distributed according to SEO SB120 guidelines, Column 1 *(Gross evaporation/12)

(3) Based on Climate data from the Fort Collins Weather Station from CDSS

(4) Assumes 70% effective precipitation, (Column 3 * 0.70)/12

(5) Net lake evaporation from water surface areas, Column 2 - Column 4

(6) Total lake evaporation = Column 5 net lake evap.* total exposed water surface

Table 2 Tri-Districts and City of Greeley Lamb Lakes, M-2018-039 (WDID 0302556, Plan ID 6135)

Depletion Summary from AWAS Model (ac-ft)

Evaporative Depletions

Liapora	Jan	Feb	Mar	Apr	Мау	Jun	Jul	Aug	Sep	Oct	Nov	Dec
2002				-	-			39.48				
	5.69	8.19	10.47	16.32	22.26	34.23	40.43		31.68	23.17	16.11	12.15
2003	11.52	11.87	13.40	18.73	24.25	35.87	41.79	40.60	32.60	23.94	16.75	12.67
2004	11.96	12.23	13.70	18.97	24.45	36.04	41.93	40.71	32.70	24.02	16.81	12.73
2005	12.00	12.27	13.73	19.00	24.47	36.06	41.94	40.73	32.71	24.02	16.82	12.73
2006	12.01	12.27	13.73	19.00	24.47	36.06	41.94	40.73	32.71	24.03	16.82	12.73
2007	12.01	12.27	13.73	19.00	24.47	36.06	41.94	40.73	32.71	24.03	16.82	12.73
2008	12.01	12.27	13.73	19.00	24.47	36.06	41.94	40.73	32.71	24.03	16.82	12.73
2009	12.01	12.27	13.73	19.00	24.47	36.06	41.94	40.73	32.71	24.03	16.82	12.73
2010	12.01	12.27	13.73	19.00	24.47	36.06	41.94	40.73	32.71	24.03	16.82	12.73
2011	12.01	12.27	13.73	19.00	24.47	36.06	41.94	40.73	32.71	24.03	16.82	12.73
2012	11.99	12.24	13.7	18.95	24.4	35.95	41.81	40.61	32.61	22.16	14.95	11.48
2013	9.97	9.75	10.59	14.2	17.99	29.23	37.39	33.07	24.36	17.55	12.33	9.36
2014	8.77	8.89	9.84	13.47	17.24	25.29	29.36	28.49	22.89	16.82	11.78	8.92
2015	8.41	8.59	9.6	13.26	17.07	25.15	29.25	28.4	22.81	16.75	11.73	8.88
2016	8.37	8.56	9.57	13.24	17.05	19.6	21.48	20.67	16.6	12.24	8.62	6.54
2017	6.14	6.23	6.92	9.49	12.16	17.86	20.74	20.13	16.17	11.88	8.32	6.30
2018	5.92	5.76	6.89	9.3	12.16	17.65	20.84	20.13	15.95	11.96	8.19	6.34
2019	5.94	5.78	6.9	9.31	12.17	17.66	20.85	20.13	15.95	11.96	8.19	6.34
2020	5.92	5.86	6.85	9.28	12.15	17.64	20.84	20.12	15.94	11.96	8.18	6.34
2021	5.94	5.78	6.90	9.31	12.17	17.65	20.85	20.13	15.95	11.96	8.19	6.34
2022	5.91	6.05	6.77	9.37	12.06	17.77	20.67	20.07	16.12	11.84	8.29	6.27
2023	5.91	6.05	6.77	9.37	12.06	17.77	20.67	20.07	16.12	11.84	8.29	6.27

Table 3 Tri-Districts and City of Greeley Lamb Lakes, M-2018-039 (WDID 0302556, Plan ID 6135)

Total Calculated and Lagged Depletions

	(1)	(2)
Month	Calculated Evaporative Depletions at Lamb Lakes	Updated Lagged Evaporative Depletions
	AF	AF
Jan-22	4.57	5.9
Feb-22	5.12	6.1
Mar-22	6.44	6.8
Apr-22	10.48	9.4
May-22	13.68	12.1
Jun-22	21.78	17.8
Jul-22	23.59	20.7
Aug-22	21.23	20.1
Sep-22	14.88	16.1
Oct-22	9.63	11.8
Nov-22	5.70	8.3
Dec-22	4.10	6.3
Total	141.19	141.19
Jan-23	4.57	5.9
Feb-23	5.12	6.1
Mar-23	6.44	6.8
Apr-23	10.48	9.4
May-23	13.68	12.1
Jun-23	21.78	17.8
Jul-23	23.59	20.7
Aug-23	21.23	20.1
Sep-23	14.88	16.1
Oct-23	9.63	11.8
Nov-23	5.70	8.3
Dec-23	4.10	6.3
Total	141.19	141.19

NOTES:

1 Calculated evaporative depletions from Table 1

2 Lagged evaporative depletions from AWAS Model

Table 4 **Tri-Districts and City of Greeley** Lamb Lakes, M-2018-039 (WDID 0302556, Plan ID 6135)

Water Balance and Replacements

	(1)	(2)	(3)	(4)	(5)	(6)
Month	Updated Total Lagged Depletions	ELCO Municipal Return Flows	FCLWD Municipal Return Flows	Remaining Depletions	Transit Losses from Reservoir Releases to Lamb Lakes	Replacements from the City of Greeley and Tri-Districts
	AF	AF	AF	AF	AF	AF
Jan-22	5.91			5.91	0.46	6.37
Feb-22	6.05			6.05	0.47	6.52
Mar-22	6.77			6.77	0.53	7.30
Apr-22	9.37			9.37	0.73	10.10
May-22	12.06			12.06	0.94	13.00
Jun-22	17.77			17.77	1.39	19.16
Jul-22	20.67			20.67	1.61	22.28
Aug-22	20.07			20.07	1.57	21.64
Sep-22	16.12			16.12	1.26	17.38
Oct-22	11.84			11.84	0.92	12.76
Nov-22	8.29			8.29	0.65	8.94
Dec-22	6.27			6.27	0.49	6.76
Total	141.19	0.00		141.19	11.01	152.20
Jan-23	5.91			5.91	0.46	6.37
Feb-23	6.05			6.05	0.47	6.52
Mar-23	6.77			6.77	0.53	7.30
Apr-23	9.37			9.37	0.73	10.10
May-23	12.06			12.06	0.94	13.00
Jun-23	17.77			17.77	1.39	19.16
Jul-23	20.67			20.67	1.61	22.28
Aug-23	20.07			20.07	1.57	21.64
Sep-23	16.12			16.12	1.26	17.38
Oct-23	11.84			11.84	0.92	12.76
Nov-23	8.29			8.29	0.65	8.94
Dec-23	6.27			6.27	0.49	6.76
Total	141.19	0.00		141.19	11.01	152.20

NOTES:

1 Lagged depletions from Table 4

2 ELCO reusable municipal return flows from 09CW282
 3 FCLWD reusable municipal return flows from 19CW3019

4 Remaining depletions, Column 1 - 2 - 3
5 Transit losses of 7.8 percent for releases from mountain reservoirs
6 Total replacements from mountain reservoirs to augment depletions