

Table 4.8-2 Haul Road Culvert Sizing.

Culvert No.	Peak Flow (cfs)	Diameter (in)	Quantity	Footnote
<u>Existing</u>				
A-1	24	48	1	1)
A-2	133	60	1	1)
A-3	72	48	1	1)
A-4	77	48	1	1)
A-5	138	48	2	1)
A-7	47	36	1	3)
A-9	51	48	1	1)
A-10	99	48	1	3)
A-11	21	18	1	3)
A-12	29	36	1	1)
A-13	2.4	24	1	3)
A-14	35	36	1	1)
A-15	2.4	48	1	3)
AE-4	14	24	1	3)
AE-7	12	24	1	3)
AE-8	37	42	1	3)
AE-10	99	48	1	3)
AE-11	47	48	1	3)
AE-12	0.5	36	1	3)
AE-13A	7.1	24	1	3)
AE-13B	7.1	36	1	3)
ASH-1	18	24	1	3)
BC-1	37	24	3	1)
BC-2	57	60	1	1)
BC-5	2	24	1	1)
D-9	14	24	1	1)
D-10	8	18	1	1)
D-12	2	18	1	1)
D-15	33	36	1	1)
D-16	2	24	1	1)
D-17	2	24	1	1)
EMF-1	51	36	2	2)
GRS-1	9	24	1	1)
GRS-2	45	48	1	1)
SA-1	156	48	2	3)
SA-7	28	36	1	3)
SAH-1	13	24	1	3)

cont.

Table 4.8.2 - page 2

Culvert No.	Peak Flow (cfs)	Diameter (in)	Quantity	Footnote
<u>Future</u>				
BC-6	34	36	1	3)
BC-7	30	36	1	3)
OH-6	7	18	1	2)

Footnote column indicates Haulroad type

Footnotes:

- 1) Certified Haulroads
- 2) Light use road
- 3) Non-Certified Haulroads in disturbed areas

Note: See map M51, Drainage and Sediment Control, for all culvert locations. [TR-50, TR-54, TR-61, TR-79, MR-172, PR-5, PR-6, PR-7, PR-11]