

Johnson Stockpile East Diversion

Designed using a 10-year, 24-hour rainfall event

Jim Mattern

JMattern Mining, LLC

Email: jim.mattern@jmatternmining.com

Revision: PR-11 Submitted: 10-14-2022
--

General Information

Storm Information:

Storm Type:	NRCS Type II
Design Storm:	10 yr - 24 hr
Rainfall Depth:	1.400 inches

Structure Networking:

Type	Stru #	(flows into)	Stru #	Musk. K (hrs)	Musk. X	Description
Channel	#1	==>	End	0.000	0.000	Johnson Stockpile East Diversion

#1 Chan'l

Structure Summary:

	Immediate Contributing Area (ac)	Total Contributing Area (ac)	Peak Discharge (cfs)	Total Runoff Volume (ac-ft)
#1	8.500	8.500	3.25	0.31

Structure Detail:

Structure #1 (Erodible Channel)

Johnson Stockpile East Diversion

Triangular Erodible Channel Inputs:

Material: Graded silts to cobbles when colloidal

Left Sideslope Ratio	Right Sideslope Ratio	Slope (%)	Manning's n	Freeboard Depth (ft)	Freeboard % of Depth	Freeboard Mult. x (VxD)	Limiting Velocity (fps)
3.0:1	3.0:1	1.4	0.0300	1.00			5.5

Erodible Channel Results:

	w/o Freeboard	w/ Freeboard
Design Discharge:	3.25 cfs	
Depth:	0.64 ft	1.64 ft
Top Width:	3.83 ft	9.83 ft
Velocity:	2.65 fps	
X-Section Area:	1.23 sq ft	
Hydraulic Radius:	0.303 ft	
Froude Number:	0.83	

Subwatershed Hydrology Detail:

Stru #	SWS #	SWS Area (ac)	Time of Conc (hrs)	Musk K (hrs)	Musk X	Curve Number	UHS	Peak Discharge (cfs)	Runoff Volume (ac-ft)
#1	1	8.500	0.263	0.000	0.000	87.000	F	3.25	0.314
Σ		8.500						3.25	0.314

Subwatershed Time of Concentration Details:

Stru #	SWS #	Land Flow Condition	Slope (%)	Vert. Dist. (ft)	Horiz. Dist. (ft)	Velocity (fps)	Time (hrs)
#1	1	5. Nearly bare and untilled, and alluvial valley fans	3.02	25.00	827.02	1.730	0.132
		7. Paved area and small upland gullies	1.35	15.00	1,109.05	2.340	0.131
#1	1	Time of Concentration:					0.263