

Some methane gas from the sealed mine sections is used to heat mine ventilation air at the Ventilation Shafts No. 1 & 2, in a system completed in 2003 and amended a few years later. A 10" diameter methane supply hole was drilled to the B seam to the south of Shaft 3. About 100' of buried 12" HDPE pipeline ties the borehole into the existing mine air heater line.

Fire Breaks

Fire Breaks are constructed West the Main Mine Site. The neighboring mine, Bear Mine, has historically had issues with underground fire that, more recently, has spread to surface fire. In order to protect the Main Mine Site location and land from fire danger MCC installed a fire break that consists of approximately 1.8 miles of road that is roughly 20-30 feet wide. The land disturbance for the Fire Breaks is not a mine facility and will not be used in the future for any activity associated with mining or reclamation. See Exhibit 83 for Fire Break location.

Figure 17: Fire Breaks- located in Exhibit 83

Access Road to Bear Mine Site

An access road to the inactive Bear Mine site is located East of MB-5E ponds and extends to the vent holes that have created a fire hazard to the immediate and surrounding areas. MCC is not liable to reclaim this road and the disturbance is not a mine facility and will not be used for any mining activity. See Exhibit 83 for construction, location and use details.

Figure 17a: Bear Mine Access Road- located in Exhibit 83

Deer Creek Shaft Facilities

In 2009 MCC constructed Deer Creek shaft. Location and layout design of the Deer Creek Shaft can be found on Map 53D. The shaft is used as a secondary escapeway from the mine as well as assisting in mine ventilation. See Exhibit 77 for further details.

Monument Dam Survey Station

The Monument Dam Survey Station is located on the hillside Northwest of the Dam on property owned by MCC. The station houses continuous survey equipment. The equipment is owned and operated by MCC. A 9ft security fence surrounds the pad where the station is located.

Box Canyon Water Storage pumphouse

A pad, pump and pump house are located just North of subsoil pile #1 access road. The subsoil pile is located at the base of Sylvester Gulch Road and the main mine access road. This facility retrieves the stored water in the Box Canyon North water storage area. This water will be recycled to the million-gallon mine water tank located above the main mine site. The drill hole specs are approximately 365 feet deep. From 0-40 feet the hole will be 24 inches in diameter with a 20 inch casing. From 40-320 feet the hole will be 18 inches in diameter with a 14 inch casing. From 320-365 feet the hole will be 12.25 inches in diameter with no casing.