



COLORADO

Division of Reclamation,
Mining and Safety

Department of Natural Resources
1313 Sherman Street, Room 215
Denver, CO 80203

REQUEST FOR TECHNICAL REVISION (TR) Importation of Inert Fill

File No.: M-_____ Site Name: _____

County: _____ TR# _____ (DRMS Use only)

Permittee: _____

Operator (If Other than Permittee): _____

Permittee Representative: _____

The request for a TR is not considered “filed for review” until the appropriate fee is received by the Division (as listed below by permit type). Please submit the appropriate fee with your request to expedite the review process. After the TR is submitted with the appropriate fee, the Division will determine if it is approvable within 30 days. If the Division requires additional information to approve a TR, you will be notified of specific deficiencies that will need to be addressed. If at the end of the 30 day review period there are still outstanding deficiencies, the Division must deny the TR unless the permittee requests additional time, in writing, to provide the required information.

There is no pre-defined format for the submittal of a TR. Page 2 is designed to address the requirements of Rule 3.1.5(9). It is up to the permittee to provide sufficient information to the Division to approve the TR request, including updated mining and reclamation plan maps that accurately depict the changes proposed in the requested TR.

Required Fees for Technical Revision by Permit Type - Please mark the correct fee and submit it with your request for a Technical Revision.

<u>Permit Type</u>	<u>Required TR Fee</u>	<u>Submitted (mark only one)</u>
110c, 111, 112 construction materials, and 112 quarries	\$216	
112 hard rock (not DMO)	\$175	
110d, 112d(1, 2 or 3)	\$1006	
2018-2019 Wildfire Material Debris Removal	Waived	



COLORADO

Division of Reclamation,
Mining and Safety

Department of Natural Resources
1313 Sherman Street, Room 215
Denver, CO 80203

Rule 1.1(24)/1.1(20) "Inert Material" means non-water-soluble and non-putrescible solids together with such minor amounts and types of other materials, unless such materials are acid or toxic producing, as will not significantly affect the inert nature of such solids. The term includes, but is not limited to, earth, sand, gravel, rock, concrete which has been in a hardened state for at least sixty days, masonry, asphalt paving fragments, and other inert solids.

**Rebar or other protruding reinforcements must be removed prior to placement. All material must be buried to a minimum of 3 feet below final surface grade.

-
1. General Description of material to be imported: _____

 2. Approximate volume of inert material to be backfilled: _____
 3. Estimated dates of commencement: _____ and completion: _____
 4. Use/purpose of imported material: _____

 5. A general engineering plan stating how the material will be placed and stabilized in a manner to avoid unacceptable settling and voids. _____

Enclosed is a map showing the proposed location of the inert material.

3.1.5(9)(c) - Affidavit

I _____ of _____ hereby
certify that only clean and inert material will be imported at _____.
All material will adhere to the Division's definition of Inert Material as defined in Rule
1.1(24)/1.1(20).

Signature: _____ Date: _____

MIDWAY PIT – M-1988-018 INERT BACKFILL LOCATION MAP

PREPARED FOR:
Midway Aggregates,
RLLP

