


SITE MAP



| | | |
|----------------|---------------|-------------|
| DRAWING NUMBER | INVESTIGATION | TB |
| 1 | DRAFTER | TB |
| OF 1 | DATE | April, 2006 |
| | JOB NO. | 06-023-020 |

Lone Eagle Land Brokerage
MONTROSE 552-ACRE RANCH
 MONTROSE COUNTY, COLORADO

BUCKHORN GEOTECH


Civil, Structural, and Geotechnical Engineers, Inc.
 222 South Park Avenue
 Montrose, Colorado 81401
 Phone (970) 249-6828 Fax (970) 249-0945

Year 2006 Groundwater Study Summary

Montrose 552-acre Ranch
06-023-GEO

| Standpipe # | 1 | 2 | 3 | 4 | 5 |
|------------------|--------------|------|------|------|------|
| Location | TP#1 | TP#2 | TP#3 | TP#4 | TP#5 |
| Depth (ft.) | 8.4 | 8.1 | 8.3 | 7.8 | 4.6 |
| Observation Date | Apr 10, 2006 | dry | dry | dry | dry |
| Jun 1, 2006 | dry | -0.5 | 2.5 | 2.3 | 0 |
| Jun 8, 2006 | dry | -0.4 | 3 | 0.2 | 0 |
| Jun 15, 2006 | dry | -1.1 | 3.3 | 0.2 | 0 |
| Jun 22, 2006 | dry | -0.8 | 0.7 | 0.2 | 0 |
| Jun 29, 2006 | dry | -0.5 | 1.6 | 0.1 | 0 |
| Jul 6, 2006 | dry | -0.3 | 3.3 | 1.5 | 0 |
| Jul 13, 2006 | dry | -0.8 | 2.2 | 0.8 | 0 |
| Jul 20, 2006 | dry | -0.5 | 0 | 0.2 | 0 |
| Jul 27, 2006 | dry | -0.7 | 2.5 | 0.9 | 0 |

Groundwater Levels from the Ground Surface




—◇— SP#1 —■— SP#2 —△— SP#3 —×— SP#4 —*— SP#5

Year 2006 Groundwater Study Summary

Montrose 552-acre Ranch
06-023-GEO

| Standpipe # | Location | TP#6 | TP#7 | TP#8 | TP#9 | TP#10 |
|--------------|----------|------|------|------|------|-------|
| Depth (ft.) | | 8.2 | 8.2 | 8 | 7.8 | 8.1 |
| Apr 10, 2006 | | dry | dry | dry | dry | dry |
| Jun 1, 2006 | | dry | dry | dry | 6.7 | dry |
| Jun 8, 2006 | | dry | 5.9 | dry | 6.6 | dry |
| Jun 15, 2006 | | dry | 5.7 | dry | 7.3 | dry |
| Jun 22, 2006 | | dry | dry | dry | dry | dry |
| Jun 29, 2006 | | 6.1 | 5.7 | dry | dry | dry |
| Jul 6, 2006 | | dry | 4.4 | dry | dry | dry |
| Jul 13, 2006 | | dry | 5.4 | dry | dry | dry |
| Jul 20, 2006 | | dry | 5.4 | dry | dry | dry |
| Jul 27, 2006 | | dry | 5.4 | dry | dry | dry |

Groundwater Levels from the Ground Surface




◆ SP#6 ■ SP#7 ▲ SP#8 × SP#9 * SP#10

Year 2006 Groundwater Study Summary

Montrose 552-acre Ranch
06-023-GEO

| Standpipe # | 11 | 12 | 13 | 14 | 15 |
|------------------|-------|-------|-------|-------|-------|
| Location | TP#11 | TP#12 | TP#13 | TP#14 | TP#15 |
| Depth (ft.) | 7.9 | 6.3 | 8.2 | 8 | 8.2 |
| Observation Date | dry | dry | dry | dry | dry |
| Apr 10, 2006 | dry | dry | dry | dry | dry |
| Jun 1, 2006 | dry | dry | 8 | dry | dry |
| Jun 8, 2006 | dry | dry | dry | dry | dry |
| Jun 15, 2006 | dry | dry | dry | dry | dry |
| Jun 22, 2006 | dry | dry | dry | dry | dry |
| Jun 29, 2006 | dry | 3.4 | dry | dry | dry |
| Jul 6, 2006 | dry | 0.8 | dry | dry | dry |
| Jul 13, 2006 | dry | 0.9 | dry | dry | dry |
| Jul 20, 2006 | dry | 2 | dry | dry | dry |
| Jul 27, 2006 | dry | 0.8 | dry | dry | dry |

Groundwater Levels from the Ground Surface




Year 2006 Groundwater Study Summary

Montrose 552-acre Ranch
06-023-GEO

| Standpipe # | 16 | 17 | 18 | 19 | 20 |
|------------------|-------|-------|-------|-------|-------|
| Location | TP#16 | TP#17 | TP#18 | TP#19 | TP#20 |
| Depth (ft.) | 8.2 | 7.8 | 11.7 | 8.7 | 8.1 |
| Observation Date | dry | dry | dry | dry | dry |
| 10-Apr-06 | dry | dry | dry | dry | dry |
| 1-Jun-06 | dry | dry | dry | dry | dry |
| 8-Jun-06 | dry | dry | dry | dry | dry |
| 15-Jun-06 | dry | dry | dry | dry | dry |
| 22-Jun-06 | dry | dry | dry | dry | dry |
| 29-Jun-06 | dry | dry | dry | dry | dry |
| 6-Jul-06 | dry | dry | dry | dry | dry |
| 13-Jul-06 | dry | dry | dry | dry | dry |
| 20-Jul-06 | dry | dry | dry | dry | dry |
| 27-Jul-06 | dry | dry | dry | dry | dry |

Groundwater Levels from the Ground Surface



**GEOLOGIC REPORT
LOAN EAGLE LAND BROKERAGE
MONTROSE 552-ACRE RANCH
T ROAD
MONTROSE COUNTY, COLORADO**


Buckhorn Geotech, Inc. conducted a series of investigations of site and subsurface conditions in January, February, and March of 2006 at the Montrose 552-Acre Ranch in Montrose County, Colorado. This work was performed at the request of the property co-owner, Mr. Joseph Burns, on behalf of Lone Eagle Land Brokerage, Inc. The purpose for the analysis was to assess the general suitability of the property for development of a major subdivision. The investigation consisted of a site inspection, excavation and logging of twenty test pits, drilling and logging of four borings, percolation and radon testing, installation and monitoring of twenty groundwater standpipes, testing of soil materials encountered, and analysis of available data. Our geologic report includes an analysis of the geologic hazards and constraints relating to groundwater, soil and/or geologic conditions within the 552-acre ranch. The following report presents the findings of our investigation and our conclusions and general engineering considerations for planning, development, and construction within the ranch.

Site Conditions and Proposed Development


The Montrose 552-Acre Ranch is located between Government Springs Road to the south, T Road to the north, west of the Uncompahgre River, east of U. S. Highway 550 and extending west to Sims Mesa, approximately 7 miles south of downtown Montrose (see Vicinity Map). The property is situated in Sections 26, 27, 34, and 35, Township 47 North, Range 9 West, N.M.P.M. The ranch contains a segment of Horsefly Creek to the east, the West Canal, and a portion of the eastern flank of Sims Mesa, locally known as "Moonlight Mesa." Agricultural fields occupy the lower eastern portion of the property between U. S. Highway 550 to the West Canal. The West Canal flows from the southeast corner of the property to the northwest, aligning with the toe of the eastern escarpment of Moonlight Mesa. The top of Moonlight Mesa is relatively level with a subtle general dip to the north and east. A network of small irrigation ditches intersect through the lower fields, while seasonal drainages crease the escarpment and

mesa top. The approximate elevation of the property ranges from 6,140 near the highway to 6,500 feet on top of the mesa (*USGS 7.5 Montrose East Topographic Quadrangle*). Topography across the ranch consists of gentle slopes (2 to 5%) on top of the mesa, an escarpment comprised of undulating slopes (30 to 60%) to the east approximately 200 to 250 feet down, and lower nearly level agricultural fields. Vegetation on the non-irrigated mesa top and escarpment consists of sage, yucca, cacti, some juniper and pinon trees, native grasses, and riparian growth such as Russian olives, willows, cottonwoods, and cattails within the drainages leading off the top of the mesa. The lower fields generally consist of hay meadows and some riparian growth along the banks of Horsefly Creek, the West Canal and other surrounding irrigation ditches. An existing homestead, located on the escarpment toe, is surrounded by some landscaped trees and lawn.


The attached Site Map shows the basic features of the property, including property boundaries, and the approximate locations of our test pits. The following photographs taken from various locations across the property, shows the vegetative cover, local topography, and general characteristics of the ranch.



Looking south from on top of the escarpment, majority of the lower agricultural fields is pictured. T Road is to the left of the photograph, while the West canal is running through the center of the photo.



Looking west, the escarpment and the eastern most agricultural field can be seen. The frontage road for Highway 550 is pictured in the immediate foreground.



Looking north, the mesa top is pictured. BLM land borders the south and west. The escarpment is to the right of the photographer.

Geology

The Montrose 552-Acre Ranch is located within and along the western margin of the Uncompahgre River Valley, which is a northwesterly trending depression lying between the Uncompahgre Plateau uplift to the west and the Gunnison uplift, consisting of pre-Cambrian Black Canyon schist and gneiss, to the east (*Geologic Map of the Montrose 30' x 60' Quadrangle*, USGS Map I-1939: Steven and Hail, 1989). A prominent formation exposed along the west and east margins of the valley is the Dakota Sandstone Formation (*Kd*), a resistant sandstone unit that forms a cap layer on the Uncompahgre Plateau and the western flank of the Black Canyon. The Dakota Sandstone consists of massive, light brown sandstone layers interbedded with weaker, thin strata of gray to black shale, mudstone and some coal. The Mancos Shale Formation (*Km*) overlies the Dakota formation and is the main rock unit immediately underlying the Uncompahgre Valley. The Mancos Shale, a dark-gray to dark-brown, marine clay shale that is locally calcareous or sandy, forms a bedrock wedge that is thickest on the eastern portion of the valley, where it outcrops as "adobe badlands", and thins to the west at the edge of the Uncompahgre Plateau. Under the ranch property, the Mancos Shale is approximately 200 to 300 feet thick and is composed of variably silty, calcareous clay shale with minor inclusions of sandstone, siltstone and limestone.

The valley floor is a broad outwash plain with low mesas formed by melting glaciers. As the glaciers in the surrounding mountains melted, the mud, sand, and gravel contained within the mass of ice was swept downstream, eventually filling in the incised river valley to a depth of 30 to 80 feet. Sims Mesa is an outwash glacial plain that has been isolated by post-glacial down-cutting of the Uncompahgre River. In some places, the escarpment profile shows the cap of glacial outwash as well as the underlying shale bedrock. Erosion of the adjacent adobe hills and terraces has brought fine-grained silts and clays into the valley floor that has spread over the glacial and fluvial alluvium. Subsequent erosion by the river and its tributaries has re-excavated the valley to the shape seen today. This re-excavation has not been a uniform process but has been punctuated by climatic cycles that accelerated the rate of erosion during extended periods which were often followed by periods of quiescence.

According to the *Geologic Map of the Montrose 30' x 60' Quadrangle* (USGS Map I-1939), the lower agricultural fields and portions of the mesa are mapped as undivided stream alluvium, alluvial-fan deposits, and terrace gravel (*Qa*), consisting of "alluvial deposits in floodplains flanking modern streams, alluvial fans at the mouths of tributaries, and older gravels covering stream terraces graded to former stream levels," while the escarpment is mapped as Mancos Shale (*Km*). Much of the Mancos Shale along the margins of the Uncompahgre River valley is covered by surficial outwash deposits, as observed during our investigation. The conditions encountered during our field investigation are consistent with this mapping.

Soil Classification

According to the *Delta-Montrose Area Soil Survey* (Soil Conservation Service: Cline et al., 1967), the soils in the lower agricultural fields are classified as Vernal clay loam (*VeA*, 0 to 2% slopes), Colona clay, gravel substratum (*CsA*, 0 to 2% and *CoC*, 2 to 8% slopes), Genola clay loam (*GeA*, 0 to 2% slopes), Billings silty clay (*BdB*, 2 to 5% and *BdC*, 5 to 10% slopes), Billings silty clay loam (*BgC*, 5 to 10% slopes), and Chipeta-Persayo-Mesa association (*CkC*, 2 to 10% slopes) surrounding the existing homestead. The majority of the escarpment is classified as Rough Broken Land, Shale and Till Materials (*Rv*), while the soils on top of the mesa are classified as Mesa clay loam to Mesa gravelly clay loam (*MLA*, 0 to 2%, *MLB*, 2 to 5%, *MoB*, 2 to 5%, and *MoA*, 5 to 10% slopes).

Vernal soils are deep, well-drained, and moderately fine-textured soils formed on stream terraces, which are not highly susceptible to erosion, have a moderate organic content, and have a stable structure. Colona soils are deep, moderately well drained, and mainly fine textured. They form on floodplains and at the low end of alluvial fans in uniform, fine-textured, calcareous alluvium derived mainly from sedimentary rocks, and are very similar to Genola soils. Billings soils are deep, well-drained, moderately to fine-textured, and calcareous soils that are formed on the lower portion of gently sloping alluvial fans in sediments washed from adjacent exposures of shale and siltstone. Billings soils are noted for their weak and unstable structure. Rough Broken Land, Shale and Till Materials occur on the steeply sloping sides of erosional valleys and isolated mesas. Mesa soils are deep, well drained, and moderately fine textured grassland soils formed on mesas and high terraces in gravelly, calcareous alluvium of mixed mineralogy. These soil types are consistent with the findings of our field investigation.

Geologic Hazards

A variety of geological hazards can exist in western Colorado as a result of elevation, extreme, topography, soil/geologic conditions, surface and groundwater, and climatic effects. The hazards that potentially affect the Montrose 552-Acre Ranch are discussed below. Some buildings, roadways, and septic systems throughout the region have experienced negative impacts due to slope movement, expansive and compressible soils, and groundwater problems. Appropriate engineering techniques for design and construction relating to troublesome climate and soil conditions should be used to reduce the potential for such problems. However, because of the overall dynamic characteristics of the area, almost every site is subject to at least some degree of potential risk. These risks are explained below.

Unstable Slopes

Slopes on the property range from approximately 2 to 5% on top of the mesa, 30 to 60% as uneven slopes on the escarpment, and nearly level agricultural fields on the valley floor. The slopes of the escarpment appear to be well-vegetated and stable. Although some steep slopes in the region that are composed of these materials are susceptible to potential slope movement, we did not observe any features that may indicate recent movement such as leaning or splayed trees,

scarps, soil tension cracks, seeps, disrupted vegetation, or hummocky topography. Although the slopes of the escarpment appear currently stable, they can be destabilized through design and construction practices that ignore the potential for earth movement. If development through the escarpment is proposed, we recommend a slope stability analysis.

Slope stability can be impaired by cutting into steep slopes (especially near the toe of the slope), applying loads at the crest of a slope, careless removal of vegetation, and introducing soil moisture or disrupting the existing pattern of surface or subsurface water flow. Providing logical landscape topography, developing an integrated grading and drainage plan, and retaining cut slopes over 3 feet high will be important in preserving site stability. Due to the multiple possible home sites, slope stability will be a site specific issue. Slope stability should be examined for each building site (as needed) as development is planned. Other recommendations for enhancing slope stability are presented in the *Conclusions and Recommendations* Section of this report.

Erosion

Erosion can be a hazard due to sparse vegetation, low organic content of the soil, sloping terrain, weak soil structure, and/or a thin layer of soil over bedrock. During medium- to high-intensity precipitation events, large volumes of runoff can drain from the surrounding areas, causing a concentration of high flows in the seasonal drainages. High velocity runoff can erode surface sediments and scour channel walls, causing widening and/or down-cutting of drainages. Careful soil and water management is recommended along drainages and for construction on or near the escarpment to maintain and enhance the existing stability. Careful and conscientious construction practices should be used when developing to minimize the potential for erosion.

Shallow Groundwater

Shallow groundwater can be problematic as it weakens foundation soils, creates hydraulic pressure, can seep into the interior of buildings if foundation components are not properly waterproofed, and can interfere with the operation of an improperly designed septic system. On moderate to steep slopes, saturated soil conditions can also contribute to unstable slope conditions. Management of surface and subsurface water at this site is important for the long-term performance of foundation components and slope stability. A comprehensive site drainage plan, designed in tandem with the grading and landscape plans, should be designed to intercept surface and subsurface water and remove it from development areas. Care should also be taken so that outfall from drains is not concentrating the runoff, which could cause erosion or slope stability problems. General recommendations for grading and foundation preparation are given below in the *Conclusions and Recommendations* Section of this report.

Although we did not find groundwater during our subsurface investigations and did not observe any indications of seeps or springs, we did observe iron-oxide staining, mottling, and in some of the lower test pits, an abrupt cessation of roots, suggesting that groundwater may seasonally rise. Since we performed our investigation during a time of the year when irrigation is not occurring and groundwater levels are cyclically low (winter), it is expected that groundwater levels will be higher during the irrigation season. Groundwater monitoring standpipes (piezometers) were installed in the excavations prior to backfilling. These piezometers were positioned to

demonstrate the limits of high groundwater that may occur on the property. Groundwater levels will be monitored as per the County requirements. When our measurements are complete, and we are comfortable determining the level of shallowest groundwater, we will tabulate the results to be summarized in a letter that will be an addendum to this report.

Wetlands

Field observations of various areas within the ranch, particularly the southern portion, indicate that potential jurisdictional wetland(s) may exist along principal drainages. Jurisdictional wetlands are defined by the U.S. Army Corps of Engineers as areas that are inundated by surface and/or groundwater in durations sufficient to support a prevalence of vegetation suited to saturated ground conditions. Section 404 of the 1977 Clean Water Act requires a permit to be obtained before a wetland or water of the U.S. can be impacted. Wetlands adjacent to waters of the U.S. such as lakes, rivers, and streams are considered waters of the U.S. In addition, specific County regulations, permits, and setbacks may apply. It is recommended that a wetlands delineation survey be conducted to identify wetland areas that may be impacted by proposed development.

Flooding

According to the Federal Emergency Management Agency (FEMA) Flood Insurance Rate Map Panel 402B, the majority of the 552-acre ranch is located in *Zone C*, areas of minimal flooding, where no special precautions are required to mitigate potential flood hazards. Areas within the Horsefly Creek channel are mapped as *Zone A*, areas affected by the 100-year flood. No observable signs of recent flooding were seen on the property. However, due to the mapping designation along Horsefly Creek, the close proximity of the West Canal and surrounding ditches, we recommend that the property owners avoid all potential floodplains and consider elevating the first floor level of any home built downgrade of these water features, a minimum of 1-foot above surrounding grade to minimize the hazard resulting from an unlikely breach.

Expansive and Compressive Soil and Rock

Soil materials containing some types of clay, especially bentonite (montmorillonite), can expand in volume as they absorb water and then shrink as they become dry. In some areas of Colorado, these expansive soils are very hazardous and can cause serious damage to foundations, roadways, pavements, and embankments. The geology of swelling soils, the effects of moisture on these soils, and dealing with construction and landscaping on swelling soils are discussed in the Colorado Geological Survey publication, *A Guide to Swelling Soils for Colorado Homebuyers and Homeowners* (Special Publication #43: Noe et al., 1997). In the Montrose area, these clays are principally derived from Mancos Shale.

Compressive soils are those that have generally been laid down rapidly, have a weak matrix containing voids, and/or are not naturally in a dense or compacted state. Compressive soils typically have a large proportion of fine-grained materials, especially silt, but this is not always the case. For example, alluvial and debris fan deposits contain soil, rock and organic debris that is laid down during flood events in an unsorted and uncontrolled manner. Consequently, the

debris contains voids and, although it contains rocks up to boulder-size, the interstitial material is often not dense or in a well-consolidated state. Clayey soils can also be compressive if saturated when loads are applied.

Mancos Shale and its residual soil can be very sensitive to variations in moisture, being quite strong when dry but either expansive or losing strength rapidly when wetted. Additionally, wetting and drying cycles can weaken the shale so that it becomes highly erodible. When in a dry and dense state, the shale and its residual soil can exert expansive pressures when moisture is absorbed. Conversely, when in a loose, highly fractured state, the material can consolidate when wetted under moderate loads. The expansive and compressive characteristics of the shale and soil are discussed in detail in the *Subsurface Conditions* Section of this report.

The potential hazard from expansive and compressive soil is the differential movement of foundation soils under loads applied through the foundation. This hazard can be partly mitigated by control of on-site drainage so that no water is allowed to accumulate, stand, or penetrate into the soil in the vicinity of foundations and slab/pavement areas. Further mitigation can be attained through design of foundation systems that extend to firmer material or which have sufficient strength to resist differential movements. Another option is the removal of the problematic soil and replacement with structural fill. These methods are discussed in further detail below in the *Conclusions and Recommendations* Section. Special Publication #43 gives general explanations and illustrations of design and drainage options on swelling soils.

Seismicity

There are no geologically recent (Quaternary-aged) or potentially active faults identified in the immediate vicinity of the Montrose 552-Acre Ranch in either of the Colorado Geological Survey (CGS) reports relating to earthquake potential [*Earthquake Potential in Colorado—A Preliminary Evaluation* (Bulletin #43: Kirkham and Rogers, 1981) and *Preliminary Quaternary Fault and Fold Map and Database of Colorado* (Open-file Report 98-8: Widmann et al., 1998)]. The closest mapped potentially active faults to the ranch are the Cimarron Fault group, a segmented fault zone located 8 miles northeast of Montrose and continuing for roughly 35 miles to the southeast, and the Roubideau Creek Fault, located roughly 12 miles southwest of Montrose. Both are northwest-trending faults that are interpreted to be Quaternary-aged, but the Cimarron Fault group consists of five distinct sections with apparently different ages and amounts of movement associated with the Laramide Gunnison Uplift that was later reactivated, while the Roubideau Creek Fault appears to be associated with movement on the eastern flank of the Uncompahgre Plateau. The maximum credible earthquake inferred for the Cimarron Fault group is M6.75. A maximum credible earthquake has not been assigned to the Roubideau Creek Fault, but it is believed to be one of the youngest faults in the region, having displaced late Pleistocene to Holocene age landslide deposits, making it less than 15,000 years old.

Montrose County is located in the Colorado Plateau Seismotectonic Province in Colorado, where maximum credible earthquakes are estimated to be on the order of magnitude 5.5 to 6.5, which is equivalent to Modified Mercalli (MM) V to VIII (CGS Bulletin #43). The largest recorded earthquake in the region was the 1960 M5.5 (MM VI) Montrose/Cimarron event [according to the CGS Bulletin #52 entitled *Colorado Earthquake Information, 1867-1996* (Kirkham and

Rogers, 2000) and the CGS website database of earthquake events: <http://geosurvey.state.co.us>]. There were several other similar magnitude earthquakes in the Montrose region: Ridgway in 1897 (MM V), Lake City in 1913 (MM VI) and 1955 (MM VI), Somerset in 1944 (MM VI), and Cimarron Ridge/Montrose in 1962 (MM V). Many other earthquake events less than MM V have been identified for the region.

The Colorado Geological Survey indicates that, based on limited historical records, Colorado is considered to be a region of minor earthquake activity, where moderate to large events are relatively infrequent. However, there is a growing body of evidence that suggests that Colorado is at greater risk than previously thought. According to the Uniform Building Code, western Colorado is in Seismic Risk Zone 1 where distant earthquakes would be expected to cause only minor damage to structures with fundamental periods of vibration greater than one second. Excepting transmission towers, we are unaware of such tall, slender structures in western Colorado. However, the CGS recommends in their Bulletin #43 that a Seismic Risk Zone 2 designation may be more appropriate for all of Colorado except the extreme northeast corner. It also suggests that for areas that are far from known active faults, a minimum of 0.1g horizontal acceleration should be used in design and safety analyses.

Radon Gas

Radon gas is produced by decay of radioactive minerals contained in subsurface rock and soil. The U.S. Environmental Protection Agency (EPA) has determined that radon is the 2nd leading cause of lung cancer and that radon can accumulate in homes if the gas is not properly removed through passive or active methods. The EPA map of Radon Zones indicates that virtually all of western Colorado, including Montrose County, is in Zone 1 (www.epa.gov/iaq/radon/zonemap/colorado.htm). Although there is no known safe level of radon, Zone 1 is the zone of highest risk for exposure to radon gas [i.e., greater than 4 picoCuries per Liter (pCi/L)]. The Colorado Geological Survey (CGS) participated in an EPA study in 1987 and 1988 to record indoor radon levels throughout Colorado homes and compiled its results in a report that relates geologic setting and house construction with radon levels (CGS 1991 Open-File Report 91-4). Generally, homes with basements had higher levels of radon than homes with slabs on the same geologic material. In our region of Colorado, Precambrian igneous rocks had the highest readings, followed by older Mesozoic sedimentary rocks, and Tertiary volcanic and volcaniclastic rocks. Radon values in alluvial and glacial valley fill was highly variable. The CGS is careful to state that radon potential can vary considerably within the same geologic unit. This has to do with the non-uniform distribution of uranium, secondary leaching, and the accumulation of uranium and other radioactive elements into other strata.

The EPA recommends testing radon levels in existing homes, but it has not developed a sampling test that will determine levels of radon gas in the native soils prior to construction. This is due to the fact that there are too many factors that affect the movement of radon through soils, such as soil moisture, soil types, weather patterns, and wind, and these factors cannot be completely accounted for or controlled during testing. However, based on levels of radon recorded in existing homes in the region and the presence of rock types that are known to produce radon, it is reasonable to assume that radon is present in the Montrose area. The EPA, the Colorado Department of Public Health and Environment (CDPHE) Radiation Management

Division, and the National Association of Home Builders (NAHB) recommend that all new homes constructed in Zone 1 should include radon-resistant features. They also recommend that after the house is constructed, radon should be measured in the home and if the results are greater than 4 pCi/L, the system should be upgraded from passive to active (usually by installing a fan). In the EPA publication entitled, *Building Radon Out: A Step-by-Step Guide on How to Build Radon-Resistant Homes* (USEPA Office of Air and Radiation EPA/402-K-01-002, April 2001), they present three practical and inexpensive alternatives for a passive, sub-slab depressurization system: gravel with vents, perforated pipes, or soil gas collection mats. As stated in that EPA publication, radon-reduction techniques not only reduce radon in the home but also are “consistent with state-of-the-art energy-efficient construction...which will result in energy savings and lower utility bills for the homeowner” and they have the added benefits of “decreasing moisture and other soil gases in the home, reducing molds, mildews, methane, pesticide gases, volatile organic compounds, and other indoor air quality problems.” It is estimated that retrofitting a house after construction with radon resistant features is 2 to 10 times more expensive than if it had been included in the original construction.

As required by Montrose County Land Use Regulations, radon tests were performed in the soil at each test pit location and sent to a laboratory for evaluation. The test results showed radon levels ranging from lower than the method detection limit (0.5 pCi/L) to 38.1 pCi/L (see Radon test results, respectively). A positive reading is common throughout the Uncompahgre Valley.

The *Building Radon Out* EPA publication can be obtained from the CDPHE in Denver by calling (303) 692-3420. Other recommendations for passive and active design and construction techniques for reducing radon gas can be found on the EPA radon website www.epa.gov/radon/ or the CDPHE radon website www.cdphe.state.co.us/hm/rad/radon.

No other geologic hazards are known to be present in the vicinity of the Montrose 552-Acre Ranch.

Subsurface Conditions

Twenty test pits (TP#1 through TP#20) and four boreholes (BH06-1 through BH06-4) were excavated/drilled at selected locations shown on the attached Site Map. The locations of the test pits were chosen based upon the anticipated variation in subsurface conditions, access, consideration of existing development, and are thought to be representative of the surficial geologic conditions across the property based on available information. The soil and groundwater conditions were visually examined and logged, and representative samples of soils encountered were brought back to our laboratory for detailed examination and testing. The stratigraphy encountered in the test pits and boreholes and laboratory results are shown on the attached Soil Logs and Logs of Exploratory Drilling. Laboratory test results are shown on the attached laboratory test sheets, and summarized on the attached *Summary of Laboratory Test Results*.

The test pits were excavated using a backhoe/front-end loader. The borings were advanced using a truck-mounted Simco 2800 HS auger rig. The holes were drilled using a 4.25-inch outside diameter (O.D.) continuous-flight solid-stem auger. Soil samples were obtained at discrete intervals while performing in-situ Standard Penetration Tests (SPT) in general accordance with ASTM Standard D-1586, using a 2-inch I.D. "California" split-spoon sampler with liners. The number of blows required to drive the sampler one foot were recorded (SPT "N" penetration resistance values) and, when properly evaluated, indicate the relative density or consistency of the soils. Samples collected from the split spoon sampler were used to classify the soil material and determine its engineering characteristics.

Generally, the 552-acre ranch consists of three different geologic settings; old lower floodplain (agricultural fields), escarpment, and mesa top. The lower agricultural fields are generally comprised of clayey soil with varying amounts of sand and gravel underlain by deep gravel and cobbles. The escarpment is composed of shale, shale outcrops, and overlying sand and gravel deposits eroded from the above mesa top. The mesa top generally consists of an undulating layer of sand, gravel, and cobbles above shale. Test pits #1 through #16 were excavated within the escarpment and throughout the lower agricultural fields, while test pits #17 through #20 and the four drilled boreholes were advanced on top of the mesa. The laboratory test results are summarized in the following paragraphs in accordance with their geologic setting.

TP#2, TP#3, TP#4, TP#5, TP#6, TP#7, TP#9, TP#12, and TP#13 were excavated in the agricultural fields. These pits generally consisted of approximately 1-foot of damp, organic, silt and clay topsoil underlain by stiff silt and clay with varying amounts of sand and gravel. TP#6 and TP#7, which were located furthest east, revealed deep gravel and cobbles underlying the silt and clay at depths of 2 and 7.5 feet. Atterberg Limits tests performed on the clayey soils revealed Plasticity Indices (PI) ranging from 19 to 32, indicating that the soil typically has a moderate to high shrink/swell potential with moisture changes. Gradation Analyses performed on the clayey samples indicate that these subsoils are typically composed of 61.6 to 95.3% fines (silt and clay), 2 to 37.7% sand, and 0.0 to 20.1% gravel. A sample of the underlying gravel and cobbles in TP#6 revealed to be Non-Plastic (NP) and composed of 3.2% fines, 27.7% sand, and 69.1% gravel. Drive samples were taken in these soils and subjected to swell/consolidation tests. Under a confining pressure of 2000 pounds per square foot (psf) and left at their in-situ moisture contents ranging from 14.7 to 24.3%, the samples generated estimated swelling pressures ranging from 190 to 950 psf, considered low to moderate (see Summary of Laboratory Test Results, respectively). These excavations were terminated at an approximate depth of 8 feet, with no groundwater being encountered. Samples tested revealed moderately high levels of sulfates.



Soils at TP#3 and TP#4. The photograph on the left shows the typical soil profile revealed in out test pits throughout the lower agricultural fields, while the photo on the right shows a test hole during excavation.


TP#1, TP#8, TP#10, TP#11, TP#14, TP#15, and TP#16 were located within the escarpment. The soil and rock ranged from shale to sand and gravel. Atterberg Limits tests performed on the variety of material found revealed PI's ranging from 22 to 26, indicating that the soils typically have a moderate shrink/swell potential. Gradation analysis were performed on the various samples indicate that these subsoils (not including shale) are typically composed of 50 to 83.7% fines, 16.3 to 31.2% sand and 0 to 29.3% gravel. Drive samples were taken in these soils and subjected to swell/consolidation tests. Under confining pressures ranging from 2000 to 8000 psf and left in their in-situ moisture contents ranging from 11.6 to 12.5% the samples generated swelling pressures ranging from 650 to 2570 psf, considered low to high (see Summary of Laboratory Test Results). These excavations were terminated at an approximate depth of 8 feet, with no groundwater being encountered. A sample of soil from the escarpment area was found to contain a high level of sulfate.



Soils at TP#16. The photograph shows the typical soil profile revealed in out test pits within the escarpment. Note the upper granular material overlying the fractured shale.

TP#17 through TP#20, as well as BH04-1 through BH04-4, were excavated/drilled on top of the mesa. These test pits and borings generally revealed clayey sand and gravel overlying sandy gravel and cobbles, which is underlain by shale at depths ranging from 15 to 35 feet. Atterberg Limits tests performed on the gravelly soils revealed Plasticity Indices (PI) ranging from Non-Plastic (NP) to 19, indicating that the soil typically has a low to moderate shrink/swell potential with moisture changes. Gradation Analyses performed on the sand and gravelly samples indicate

that these subsoils are typically composed of 1.2 to 40.7% fines (silt and clay), 6.2 to 54.6% sand, and 16.1 to 92.8% gravel. Drive samples were taken in these soils and subjected to swell/consolidation tests. Under confining pressures ranging from 2000 to 4000 psf and left in their in-situ moisture contents ranging from 6.7 to 9.8% the samples generated swelling pressures ranging from 360 to 1610 psf, considered low to moderate (see Summary of Laboratory Test Results).



Soils at TP#18. The picture shows the typical test pit on top of the mesa.

In summary, the property consists of three separate geologic settings, the lower agricultural fields, escarpment, and upper mesa top, each having distinct soil profiles. Generally the lower fields consist of a mantle of stiff, moderate to highly plastic clay with moderate to high swell potential, which thins out to the east where underlying gravels and cobbles are found at shallow depths. The escarpment is composed of shale outcrops, shale residuum, and small-scale colluvial fans. The top of the mesa generally consists of calcareous sand and gravel with silt and low to moderately plastic clay underlain by sandy gravel and cobbles extending to various depths before reaching shale. Due to the fine-grained nature of the soils and the existing arid conditions in various areas of the property, management of surface and subsurface water will be essential to the long-term performance of the foundation soils.

Percolation Testing

Percolation tests were performed at each of the test pit locations to evaluate the potential for On-site Wastewater Systems (OWS). The soil profiles of these test pits can be seen on the attached *Soil Logs*. The soils found in each percolation hole and the resulting percolation rates are presented in the attached *Summary Table of Percolation Results*. The rates are measured in minutes per inch (mpi), per county requirements.

Generally, the percolation rates at the sites tested on the mesa top were mostly acceptable but, as expected, the escarpment sites tested were variable but mostly on the slow side. The valley floor sites were also variable but some tests provided very slow percolation rates.

The Colorado Health Department requires percolation rates to be between 5 and 60 mpi for the use of a "standard" absorption system, as well as no bedrock, groundwater, or confining layer

within four feet of the bottom of treatment zone. Based on our test results, it appears that specially designed systems will be needed in some locations on the escarpment and valley floor. Additional site-specific percolation tests will be necessary for OWS design for each lot, unless the leachfield is located exactly where the tests for this report were conducted.

CONCLUSIONS AND RECOMMENDATIONS

Our evaluation indicates that the Montrose 552-Acre Ranch appears suitable for development that pays careful attention to foundation design, drainage control, site preparation, septic system design, and groundwater management. The following recommendations are offered as measures to enhance the stability of the site and the long-term performance of the foundation soils. These measures cannot and will not arrest or prevent large-scale geologic processes that may be ongoing elsewhere on the property and within the Montrose area. Also, as mentioned earlier in this report, some degree of risk is inherent in all construction in mountainous areas of Colorado. The recommended measures are intended to be reasonable and prudent but cannot be considered as absolute protection against the vagaries of nature.

Based on our site investigation and laboratory soil testing, the following **general recommendations** are offered for foundation evaluation and for mitigation of potential site hazards. Aside from pavement design sections, these recommendations are conceptual and are offered as general guidelines, not job specifications. *Site-specific investigation and testing should be done to verify applicability prior to design and construction.*

Foundation Systems

- Shallow foundations should perform adequately, but may require some subgrade treatment to reduce the potential for post-construction differential movement due to either heave or settlement. This typically involves some overexcavation below foundation level, followed by replacement with structural fill, but can also involve other forms of treatment of the subgrade. Additional alternatives that may provide less risk of foundation movement include post-tensioned raft slabs or deep foundations (drilled caissons, micropiles, or helical piers). Details of these alternatives can be determined through site-specific testing.
- Site-specific soil investigation and testing should be conducted at each proposed building site to determine the specific design parameters required to match the subsurface conditions to the proposed patterns and intensities of loading incurred by each structure. These investigations should address potential for soil expansion, hydrocompaction, and settlement, all of which are known to occur within the highly variable terrain conditions found in the area.
- Shallow foundation systems should be extended into the subsurface a minimum depth below finished grade as prescribed by the local building official for frost heave protection.

- Basements may be considered but the potential for shallow groundwater should be carefully evaluated at each proposed building site prior to development of construction plans.

Floor Systems

- Floor system selection will depend of the results of site-specific soil investigation and testing. Generally, it can be expected that framed floors over crawl spaces will be acceptable when properly ventilated and supported on appropriately designed footings and stem walls. Basements slabs may require special design and/or waterproofing pending the results of groundwater monitoring and further site investigations.
- Where the foundation conditions allow, floating slabs on-grade may be used at the site for garage and interior floor slabs, so long as such slabs will not be subjected to groundwater seepage and/or hydraulic forces. Long-term differential movement between the foundations and slabs on-grade may occur. For this reason, any floating slabs on-grade should be structurally isolated from the foundation, bearing walls, and interior partitions so that the slabs can float freely in response to soil volume changes without distressing the structure. Construction methods exist to provide slip joints with interior finishes so that slab movement does not compromise the finished product.
- We recommend under-slab plumbing be avoided where possible to minimize the potential for leakage under the slabs. Where necessary, under-slab plumbing should be provided with flexible couplings and should be leak-tested prior to being placed in service.
- Suspended floor systems have historically performed well, but are subject to moisture accumulation in the crawlspaces that can not only cause environmental concerns but also compromise the structural integrity of the flooring system over the long-term. To ensure the long-term performance of these systems, site grading, drainage and ventilation of the crawlspace are important considerations.

Exterior Concrete Flatwork

- Exterior concrete flatwork should be designed and constructed so that it drains freely away from structures. Concrete flatwork adjacent to foundations should slope away at a rate of at least 1/4-inch per foot.
- Flatwork may be placed on native soil with the topsoil and organic material removed. If fill is needed under exterior flatwork, it should consist of washed rock or structural fill, placed and compacted in accordance with project specifications.
- Flatwork adjacent to exterior doorways should be dowelled into the foundation to prevent long-term differential movement between the flatwork and structure.

- All concrete used at this site in contact with native soil should comply with the recommendations in the *Concrete* Section of these Recommendations.

Retaining Structures

- Lateral loads developed against retaining walls are a function of the height of the retained soil, the backslope angle, soil placed against the walls, the drainage conditions, and the compactive effort applied to the backfill. Walls designed to retain lateral loads should be designed based upon site-specific investigation and testing, and should account for any expansive pressures that may develop within the soil and backfill.
- The retaining walls should have provisions for drainage so that hydrostatic pressures are not allowed to build up. This is usually accomplished by providing free-draining granular backfill between the walls and retained soil, with a collection drain provided at the bottom of this granular zone, and/or the use of weep holes through the face of the walls. The drain systems should be continuous and have positive outfalls which release the collected water well away from the walls in a manner that minimizes the erosive energy of concentrated flow. The design engineer should ensure that drainage design is compatible with design assumptions.
- Fill material placed behind the walls should be specified and compacted as per the design engineer's specifications. Compaction of 85 to 90% of Standard Proctor maximum dry density is typically used to minimize post-construction settlement of the backfill. Over-compaction of the backfill should be avoided so that excessive pressures are not placed against the retaining wall. Unless expressly approved by the design engineer, only hand-operated light-duty compaction equipment should be used within three feet of the wall. The upper one foot of backfill should consist of clayey soil to create a barrier against infiltration of surface runoff.

Concrete

Long-term performance of concrete in contact with soils and rock can be impaired by sulfates present within the soil and bedrock by a phenomenon called "sulfate attack". When sufficient amounts of sulfate are present, the sulfates can react with chemicals in the cement paste, destroying the paste, causing cracks in the concrete, and ultimately reducing or eliminating the concrete strength. Where high quantities of sulfates are known to be present, non-standard cements that can resist the sulfate attacks are used. These cements resist sulfate attacks due to lesser amounts of the sulfate-reactive chemicals used in the manufacturing process. The American Concrete Institute (ACI), as well as other organizations, has provided guidance levels for the types of cements to be used. Water-soluble sulfates tests conducted on samples of the soils encountered in our excavations showed sulfate concentrations ranging from 0.189 to 0.539%, considered by the American Concrete Institute (ACI) to be "moderate to severe" sulfate exposure. Based on this information, Type V sulfate-resistant cement should be used in areas with elevated sulfate concentrations. If securing Type V cement proves difficult at this project

location, alternatives may be considered provided the contractor can demonstrate equivalent performance. Typically a Type I/II cement with a specified type and amount of fly ash has been found acceptable. In any case, air entrainment, a maximum water/cement ratio of 0.45, and a minimum unconfined compressive concrete strength of 4,500 psi is recommended by the ACI.

Foundation Drainage and Ventilation

- It is important to prevent moisture from penetrating into the soil beneath or adjacent to foundations. Moisture can accumulate as a result of poor surface drainage, over-irrigation of landscaped areas, subsurface seepage, or condensation from vapor transport.
- Provisions should be made to evacuate subsurface moisture accumulation from around foundations and under floors. This may be accomplished using conventional footing drains in tandem with a positively-vented moisture and radon control system. Alternatively, consideration may be given to using concrete forms that facilitate both dewatering and the removal of radon gases and vapors.
- Floor systems and confined areas above concrete floor slabs should be properly ventilated to allow for the release of moisture and/or radon gas. (See the *Radon Gas* Section of this report for EPA references for design and construction techniques.)
- Aggressive dewatering or other forms of groundwater management may be required if basements are constructed in areas having seasonally high groundwater.
- Roof drainage should be captured by eave gutters. Downspouts should be fitted with extensions to discharge a minimum of 10 feet away from structures or piped into a closed underground drain system and evacuated off-site. In no case should the downspouts be directed into foundation drain systems. These points of discharge should be identified in the site drainage plan so that water is readily removed from the site.

Site Preparation and Grading

- The site drainage plan, in tandem with the landscape and grading plans, should ensure that each lot is adequately drained and that captured runoff is discharged from the development in a manner that is compatible with the natural drainage patterns and pertinent local regulations.
- Surface water should be removed and not allowed to accumulate or stand anywhere near building sites either during or after completion of construction. This includes water from landscaped areas, patios, decks, and roofs. Drainage plans should ensure that precipitation, snowmelt, and runoff are conveyed around and away from buildings as well as driveways. This is typically accomplished by raising the final grade of each building site above the roadways to direct the surface drainage onto the streets.

- An integrated drainage plan should be developed for the property that provides a network of easements and structures to completely control surface runoff. This should include provisions for retention and detention as temporary and/or permanent features of a stormwater management plan.
- Final grading around the perimeter of foundations should slope downward with at least one foot of drop within the first 10 feet of horizontal distance. Concrete flatwork adjacent to the foundations should slope away at a rate of at least ¼-inch per foot.
- As a precaution against an unlikely breach or flooding of Horsefly Creek, the West Canal, or other nearby irrigation canals and ditches, we recommend elevating the first floor level of homes built down grade of these water features, a minimum of 1-foot above surrounding grade to minimize the hazard resulting from an unlikely breach.
- Development should utilize "best practices" for design and construction so that on-site erosion is minimized. This may include selective thinning of vegetation, construction of temporary diversion ditches, silt fencing, and/or dust suppression. If the cumulative area of disturbance equals or exceeds one acre, on-site erosion control should be planned and executed in conformance with Colorado Department of Public Health and Environment (Water Quality Control Division) stormwater discharge regulations. The local building official will be able to provide specific details regarding these requirements
- Grading of all permanent cut and fill slopes should not exceed 2H:1V. All slopes greater than 2H:1V and over 3 feet in vertical height should be restrained by an engineered retaining structure/system.
- Irrigation of lawn and landscaped areas should be kept at a distance of at least 5 feet from the perimeter of the building and sprinkler heads should be set to spray away from and not towards the foundation.
- Backfill placed in utility trenches should be compacted in accordance with project specifications. This will inhibit surface water infiltration and migration towards foundations, as well as to minimize post-construction settlement of the trench backfill.
- Disturbed areas should be revegetated as soon as practical to reduce soil erosion.
- If fill is used during construction, it should meet the gradational and compaction requirements specified by the design engineer and it should be placed and compacted in **maximum 6-inch lifts**, unless otherwise directed by that engineer. Structural fill should not be placed on topsoil, organic debris, or frozen or wet native soil.

Excavation and Shoring

- Temporary excavations should be made consistent with Occupational Safety and Health Administration (OSHA) regulations and with worker safety in mind.

- If the excavations for foundations, floor slabs, or other settlement-sensitive structures will be made or remain open during wet weather or if they will be left open for extended periods, it is recommended that polyethylene sheeting be secured over the excavation faces to minimize sediment runoff and deterioration of the foundation soils. Trafficking should be kept to a minimum, but where these areas will be subject to traffic, it is recommended that these areas be protected by 6 inches of sand and gravel or a 2-inch layer of lean concrete as a working mat. Large rocks exposed in the excavation face should be scaled for worker safety.
- Excavation dewatering may be required if excavations are made during peak groundwater season (spring through summer). The excavations should be designed to accommodate clarification and discharge of this intercepted water. The Montrose County Building Department should be contacted for specific regulations regarding the clarification and discharge of groundwater off-site. Surface runoff above the cuts should be directed away from excavations using berms or diversion ditches.
- We anticipate that excavation of the site soils can be accomplished by conventional excavating equipment.

Pavement Section Design

Pavement section designs for the proposed development are presented below. The section designs are based upon an estimate of 180 residences (assuming density of 1 home per 3-acres), estimated traffic loadings, and results of field and laboratory testing. Two soils types were checked for bearing strength, with areas of native clay resulting in a low bearing strength (CBR-value of 2) and the areas with native gravels and sand resulting in a higher bearing value (CBR-value of 5). Two pavement section designs were developed for the different subgrade conditions.

- Daily traffic volumes were estimated based on the estimated density of development of approximately 180 residential units for the development. The traffic estimations were based upon the Institute of Transportation Engineer's trip generations for residential development with added trips for school buses, trucks, and construction traffic. Vehicle loadings are correlated to an 18-kip Equivalent Single Axle Load (ESAL) for design purposes. The traffic estimation was projected for a 20-year pavement life resulting in 205,000 18-kip ESALs which is lower than the minimum design traffic of 300,000 18-kip ESALs required by Montrose County for residential streets. The required 300,000 18-kip ESALs value was used for the 20-year pavement design.
- The following parameters were used in the analyses, and stem from the *Colorado Department of Transportation's Pavement Design Manual* and the Colorado Asphalt Pavement Association's *Guidelines for the Design and Use of Asphalt Pavements for Colorado Roadways*.

| Parameter | clay subgrade | gravel subgrade |
|---------------------------|---------------|-----------------|
| Resilient Modulus (ksi) | 3.0 | 7.5 |
| Drainage coefficient | 1.0* | 1.0* |
| Reliability (%) | 75 | 75 |
| Serviceability Loss (psi) | 2.5 | 2.5 |
| Strength coefficients: | | |
| HMA | 0.44 | 0.44 |
| ABC | 0.12 | 0.12 |
| SUBBASE | 0.10 | 0.10 |

*based upon unknown drainage details per CDOT

- Based upon the parameters provided above, the Montrose County minimum pavement section is not adequate for the clay subgrade and the following pavement sections are provided for the given 18-kip design ESAL₂₀. For the gravel subgrade the minimum County section of 3-inches of asphalt over 4-inches of Class 6 aggregate and 12-inches of Class 2 subbase is adequate for the design section. Options for alternative sections are given below to allow some flexibility in the section design.

Pavement section for 300,000 18-kip ESAL₂₀ (residential streets) CLAY SUBGRADE

| Asphalt Thickness (in.) | Base Course Thickness (in.) | Subbase Course Thickness (in.) |
|-------------------------|-----------------------------|--------------------------------|
| 3.0 | 8 | 14 |
| 3.0 | 6 | 16 |
| 3.0 | 4 | 18 |

Pavement section for 300,000 18-kip ESAL₂₀ (residential streets) GRAVEL SUBGRADE

| Asphalt Thickness (in.) | Base Course Thickness (in.) | Subbase Course Thickness (in.) | Notes |
|-------------------------|-----------------------------|--------------------------------|--|
| 3.0 | 4 | 12 | Minimum County section |
| 3.0 | 4 | 8 | Need County approval (less than minimum section) |
| 3.0 | 12 | 0 | Need County approval (less than minimum section) |

- To provide a stable base for construction of the pavement sections, we recommend that the subgrade be scarified to a minimum depth of 12 inches below the subbase level, moisture conditioned to -2% to +4% of optimum moisture content, and recompacted to a minimum of 95% of Standard Proctor maximum dry density (ASTM D-698). If soft areas are encountered that can not achieve compaction requirements the engineer should determine if a woven geotextile (Mirafi 500X or equivalent) or a biaxial geogrid (such as Tensar BX1200) is required to provide longevity of the roadway.
- Roadbase and subbase sections should have sufficient width to fully extend beneath road shoulders. Construction of the roadway prism should promote drainage away from the prism and subgrade. Adequate borrow ditches and culverts should be provided and, where needed, lateral and/or crossdrains should be installed to keep water away from the roadways.

- Subgrade preparation, backfill gradation and placement, and asphalt and cement concrete mix designs should follow the specifications given in the Montrose County Standards and *Specifications for Roads and Bridges*. Topsoil should be removed and organic material grubbed prior to commencing construction of the road sections.

On-Site Wastewater System Design and Construction

- We measured percolation rates of 3 to greater than 320 minutes per inch (mpi) in the soil at the sites tested. "Special" systems are recommended that accommodate areas demonstrating rates that do not meet or exceed the Colorado Health Department requirements (5 to 60 mpi). It is expected that additional site-specific percolation tests will be necessary for the planned development.
- Water conservation devices should be used in the home to reduce the volume of water that will be passing through the septic system. This will help to extend its working life.
- Care must be taken in locating the disposal areas to ensure proper system operation, compliance with state and local setback criteria, and not to disrupt existing slope stability.
- The percolation tests were conducted in accordance with Colorado State regulations and for engineering of on-site wastewater systems. However, Buckhorn Geotech takes no responsibility for OWS designs carried out by others using this information.

Closing Considerations

This report has been prepared in a manner consistent with local standards of professional geotechnical engineering practice. Investigation of the site for environmental contaminants was not part of our scope of services performed at this site. The classification of soils and interpretation of subsurface stratigraphy is based on our training and years of experience, but is necessarily based on limited subsurface observation and testing. As such, inferred ground conditions cannot be guaranteed to be exact. No other warranty, Express or Implied, is made.

If the proposed arrangement of lots changes from what we have described in this report, we should be notified to reevaluate our recommendations. Also, if during excavation, soil and groundwater conditions are discovered that vary from these discussed herein, construction should be stopped until the situation has been assessed by a representative of Buckhorn Geotech. Construction should be resumed only when remedies or design adjustments, as necessary, have been prescribed.

Additional Services


Thank you for the opportunity to perform this geologic investigation for you. Buckhorn Geotech is a full-service engineering firm providing foundation, roadway, on-site wastewater system, site drainage and grading, structural, and retaining structure design services, as well as surveying, construction materials testing, and inspections. For a full description of our services please talk with us or visit our website at www.buckhorngeo.com. If you require any of these services, please do not hesitate to contact us.

To provide continuity and consistency from project start to finish, we should be retained to make observations and carry out materials testing as a service to the owner. As noted above, we recommend the owner contact us to discuss required services and scheduling in advance of the construction phase.

Thank you again for the opportunity to perform this work for you. If you have any questions regarding this report or our services, please do not hesitate to contact us.

Respectfully Submitted,
May 5, 2006

Reviewed by:




Timothy P. Brethauer
Geologist

Thomas E. Griepentrog, P.E., CPG.

Enclosures: Vicinity Map, Site Map, Radon test results, Soil Logs, Summary Table of Laboratory Results, Atterberg Limits and Sieve Analysis results, Summary Table of Percolation Results, Swell/Consolidation graphs

VICINITY MAP




| | | |
|--|---------------|-------------|
| DRAWING NUMBER 1 OF 1 | INVESTIGATION | TE |
| | DRAFTER | TB |
| | DATE | April, 2006 |
| | JOB NO. | 06-023-GEO |

Loan Eagle Land Brokerage
MONTROSE 552-ACRE RANCH
 MONTROSE COUNTY, COLORADO

BUCKHORN GEOTECH


Civil, Structural, and Geotechnical Engineers, Inc.
 222 South Park Avenue
 Montrose, Colorado 81401
 Phone (970) 249-6828 Fax (970) 249-0945

SITE MAP



| | | | | |
|-------------------------------------|---------------|-------------|--|---|
| DRAWING NUMBER 1 OF 1 | INVESTIGATION | TB | Loan Eagle Land Brokerage MONTROSE 552-ACRE RANCH MONTROSE COUNTY, COLORADO | <div style="border: 1px solid black; padding: 2px; font-weight: bold;">BUCKHORN GEOTECH</div> Civil, Structural, and Geotechnical Engineers, Inc. 222 South Park Avenue Montrose, Colorado 81401 Phone (970) 249-8628 Fax (970) 249-0945 |
| | DRAFTER | ib | | |
| | DATE | April, 2006 | | |
| | JOB NO. | 06-023-GEO | | |

SOIL LOG KEY



DRAWING NUMBER

1

INVESTIGATION

DRAWING

DATE

SOIL LOG KEY


BUCKHORN GEOTECH

Civil, Structural, and Geotechnical Engineers, Inc.
 222 South Park Avenue
 Montrose, Colorado 81401
 Phone (970) 249-6828 Fax (970) 249-0945

CF :

OB NC

SOIL LOG TEST PIT #1 (TP#1) South finger



| | |
|---|--------------------|
| DRAWING NUMBER 1 OF 20 | INVESTIGATION TB |
| | DRAFTING JG |
| | DATE 1/31/06 |
| | JOB NO. 06-023-GEO |


JOEY BURNS
552 ACRE RANCH
MONTROSE, COLORADO

BUCKHORN GEOTECH

Civil, Structural, and Geotechnical Engineers, Inc.
222 South Park Avenue
Montrose, Colorado 81401
Phone (970) 249-6828 Fax (970) 249-0945

SOIL LOG TEST PIT #2 (TP#2)

Below escarpment pasture (upper)



| | | |
|---|---------------|------------|
| DRAWING NUMBER 2 OF 20 | INVESTIGATION | TB |
| | DRAFTING | JG |
| | DATE | 1/31/06 |
| | JOB NO. | 06-023-GEO |


JOEY BURNS
552 ACRE RANCH
MONTROSE, COLORADO

BUCKHORN GEOTECH

Civil, Structural, and Geotechnical Engineers, Inc.
222 South Park Avenue
Montrose, Colorado 81401
Phone (970) 249-6828 Fax (970) 249-0945

SOIL LOG TEST PIT #3 (TP#3)

Pasture stream terrace



| | |
|---|--------------------|
| DRAWING NUMBER 3 OF 20 | INVESTIGATION TB |
| | DRAFTING JG |
| | DATE 1/31/06 |
| | JOB NO. 06-C23-GEO |


JOEY BURNS
 552 ACRE RANCH
 MONTROSE, COLORADO

BUCKHORN GEOTECH

Civil, Structural, and Geotechnical Engineers, Inc.
 222 South Park Avenue
 Montrose, Colorado 81401
 Phone (970) 249-6828 Fax (970) 249-0945

SOIL LOG TEST PIT #4 (TP#4)

N. of corral




| | |
|---|--------------------|
| DRAWING NUMBER 4 OF 20 | INVESTIGATION TB |
| | DRAFTING JG |
| | DATE 1/31/06 |
| | JOB NO. 06-023-GEO |

JOEY BURNS
552 ACRE RANCH
MONTROSE, COLORADO

BUCKHORN GEOTECH

Civil, Structural, and Geotechnical Engineers, Inc.
222 South Park Avenue
Montrose, Colorado 81401
Phone (970) 249-8828 Fax (970) 249-0945

SOIL LOG TEST PIT #5 (TP#5)
Pasture (north by V Rd.) stream terrace



DRAWING NUMBER

5

OF 20

INVESTIGATION TB

DRAFTING JG

DATE 1/31/06


JOB NO. 06-023-GEO

JOEY BURNS
 552 ACRE RANCH
 MONTROSE, COLORADO

BUCKHORN GEOTECH

Civil, Structural, and Geotechnical Engineers, Inc.
 222 South Park Avenue
 Montrose, Colorado 81401
 Phone (970) 249-6828 Fax (970) 249-0845

*SOIL LOG TEST PIT #6 (TP#6)
Eastern most pasture, stream terrace*



GS8
NON-PLASTIC
GF=69.1%
SF=27.7%
F200=3.2%
MC=5.3%

DRAWING NUMBER

6

OF 20

INVESTIGATION TB

DRAFTING JG

DATE 1/31/06


JOB NO. 06-023-GEO

JOEY BURNS
552 ACRE RANCH
MONTROSE, COLORADO

BUCKHORN GEOTECH

Civil, Structural, and Geotechnical Engineers, Inc.
222 South Park Avenue
Montrose, Colorado 81401
Phone (970) 249-6828 Fax (970) 249-0945

SOIL LOG TEST PIT #7 (TP#7)
 Pasture (mideast), stream terrace




| | |
|---|--------------------|
| DRAWING NUMBER 7 OF 20 | INVESTIGATION TB |
| | DRAFTING JG |
| | DATE 1/31/06 |
| | JOB NO. 06-023-GEO |

JOEY BURNS
 552 ACRE RANCH
 MONTROSE, COLORADO

BUCKHORN GEOTECH

Civil, Structural, and Geotechnical Engineers, Inc.
 222 South Park Avenue
 Montrose, Colorado 81401
 Phone (970) 249-6828 Fax (970) 249-0945

SOIL LOG TEST PIT #8 (TP#8)
 approx. 150' west uphill of corral




| | |
|--------------------------------------|--------------------|
| DRAWING NUMBER 8 OF 20 | INVESTIGATION TB |
| | DRAFTING JG |
| | DATE 2/1/06 |
| | JOB NO. 06-G23-GEO |

JOEY BURNS
 552 ACRE RANCH
 MONTROSE, COLORADO

BUCKHORN GEOTECH
 Civil, Structural, and Geotechnical Engineers, Inc.
 222 South Park Avenue
 Montrose, Colorado 81401
 Phone (970) 249-6828 Fax (970) 249-0945

*SOIL LOG TEST PIT #9 (TP#9)
pasture below main drainage*



DRAWING NUMBER

9

OF 20

INVESTIGATION TB

DRAFTING JG

DATE 2/1/06


JOB NO. 06-023-GEO

JOEY BURNS
552 ACRE RANCH
MONTROSE, COLORADO

BUCKHORN GEOTECH

Civil, Structural, and Geotechnical Engineers, Inc.
222 South Park Avenue
Montrose, Colorado 81401
Phone (970) 249-8928 Fax (970) 249-0945

SOIL LOG TEST PIT #10 (TP#10)
 Southern part of drainage, East side




| | |
|--|--------------------|
| DRAWING NUMBER 10 OF 20 | INVESTIGATION TB |
| | DRAFTING JC |
| | DATE 2/1/06 |
| | JOB NO. 06-023-GEO |

JOEY BURNS
 552 ACRE RANCH
 MONTROSE, COLORADO

BUCKHORN GEOTECH
 Civil, Structural, and Geotechnical Engineers, Inc.
 222 South Park Avenue
 Montrose, Colorado 81401
 Phone (970) 249-6828 Fax (970) 249-0945

SOIL LOG TEST PIT #11 (TP#11)
 northern part of drainage, west side



DRAWING NUMBER

11

OF 20

INVESTIGATION TB

DRAFTING JG

DATE 2/1/06


JOB NO. 06-023-GEO

JOEY BURNS
 552 ACRE RANCH
 MONTROSE, COLORADO

BUCKHORN GEOTECH

Civil, Structural, and Geotechnical Engineers, Inc.
 222 South Park Avenue
 Montrose, Colorado 81401
 Phone (970) 249-6828 Fax (970) 249-0945

SOIL LOG TEST PIT #12 (TP#12)
pinned pasture, east of corral




| | |
|---------------------------------------|--------------------|
| DRAWING NUMBER 12 OF 20 | INVESTIGATION TB |
| | DRAFTING JG |
| | DATE 2/1/06 |
| | JOB NO. 06-023-GEO |

JOEY BURNS
 552 ACRE RANCH
 MONTROSE, COLORADO

BUCKHORN GEOTECH
 Civil, Structural, and Geotechnical Engineers, Inc.
 222 South Park Avenue
 Montrose, Colorado 81401
 Phone (970) 249-6828 Fax (970) 249-0945

SOIL LOG TEST PIT #13 (TP#13)
11 acers east of corral




| | |
|---------------------------------------|--------------------|
| DRAWING NUMBER 13 OF 20 | INVESTIGATION TB |
| | DRAFTING JG |
| | DATE 2/1/06 |
| | JOB NO. 06-023-GEO |

JOEY BURNS
552 ACRE RANCH
MONTROSE, COLORADO

BUCKHORN GEOTECH
Civil, Structural, and Geotechnical Engineers, Inc.
222 South Park Avenue
Montrose, Colorado 81401
Phone (970) 249-6828 Fax (970) 249-0945

SOIL LOG TEST PIT #14 (TP#14)
 West of canal, just W. of "11 acres"




| | |
|--|--------------------|
| DRAWING NUMBER 14 OF 20 | INVESTIGATION TB |
| | DRAFTING JG |
| | DATE 2/1/06 |
| | JOB NO. 06-023-GEO |

JOEY BURNS
 552 ACRE RANCH
 MONTROSE, COLORADO

BUCKHORN GEOTECH

Civil, Structural, and Geotechnical Engineers, Inc.
 222 South Park Avenue
 Montrose, Colorado 81401
 Phone (970) 249-6826 Fax (970) 249-0945

*SOIL LOG TEST PIT #15 (TP#15)
Northern most pit, below tunnel*



DRAWING NUMBER

15

OF 20


| | |
|---------------|------------|
| INVESTIGATION | TB |
| DRAFTING | JG |
| DATE | 2/2/06 |
| JOB NO. | 06-023-GEO |

JOEY BURNS
552 ACRE RANCH
MONTROSE, COLORADO

BUCKHORN GEOTECH

Civil, Structural, and Geotechnical Engineers, Inc.
222 South Park Avenue
Montrose, Colorado 81401
Phone (970) 249-6828 Fax (970) 249-0945

SOIL LOG TEST PIT #16 (TP#16)
 Within escarpment, above (west) of blue house



DRAWING
NUMBER

16

OF 20

INVESTIGATION TB

DRAFTING JC

DATE 2/2/06


JOB NO. 06-023-GEO

JOEY BURNS
552 ACRE RANCH
MONTROSE, COLORADO

BUCKHORN GEOTECH

Civil, Structural, and Geotechnical Engineers, Inc.
222 South Park Avenue
Montrose, Colorado 81401
Phone (970) 249-6828 Fax (970) 249-0945

SOIL LOG TEST PIT #17 (TP#17)
 SW on mesa top (next to BH06-1)



DRAWING
NUMBER

17

OF 20

INVESTIGATION TB

DRAFTING TB

DATE 3/24/06


JOB NO. 06-023-GEO

JOEY BURNS
 552 ACRE RANCH
 MONTROSE, COLORADO

BUCKHORN GEOTECH

Civil, Structural, and Geotechnical Engineers, Inc.
 222 South Park Avenue
 Montrose, Colorado 81401
 Phone (970) 249-6628 Fax (970) 249-0845

SOIL LOG TEST PIT #18 (TP#18)
 SE on mesa top (nest to BH06-2)



*Standpipe installed


| | |
|---------------------------------------|--------------------|
| DRAWING NUMBER 18 OF 20 | INVESTIGATION TB |
| | DRAFTING TB |
| | DATE 3/24/06 |
| | JOB NO. 06-023-GEO |

JOEY BURNS
 552 ACRE RANCH
 MONTROSE, COLORADO

BUCKHORN GEOTECH

Civil, Structural, and Geotechnical Engineers, Inc.
 222 South Park Avenue
 Montrose, Colorado 81401
 Phone (970) 249-8828 Fax (970) 249-0845

SOIL LOG TEST PIT #19 (TP#19)
 NE on mesa top (next to BH06-3)




| | |
|---------------------------------------|--------------------|
| DRAWING NUMBER 19 OF 20 | INVESTIGATION TB |
| | DRAFTING TB |
| | DATE 3/24/06 |
| | JOB NO. 06-023-GEO |

JOEY BURNS
 552 ACRE RANCH
 MONTROSE, COLORADO

BUCKHORN GEOTECH

Civil, Structural, and Geotechnical Engineers, Inc.
 222 South Park Avenue
 Montrose, Colorado 81401
 Phone (970) 249-6628 Fax (970) 249-0945

SOIL LOG TEST PIT #20 (TP#20)
 NW on mesa top (next to BS06-4)



| | |
|--|--------------------|
| DRAWING NUMBER 20 OF 20 | INVESTIGATION TB |
| | DRAFTING TB |
| | DATE 3/24/06 |
| | JOB NO. 06-023-GEO |

JOEY BURNS
 552 ACRE RANCH
 MONTROSE, COLORADO

BUCKHORN GEOTECH


Civil, Structural, and Geotechnical Engineers, Inc.
 222 South Park Avenue
 Montrose, Colorado 81401
 Phone (970) 249-6828 Fax (970) 249-0945

LOG OF EXPLORATORY DRILLING - AUGER HOLE #X

SURFACE ELEVATION:
 DRILLER:
 DRILL RIG:

DRILL STEM:
 SAMPLER:
 CASING:

NOTES: SPT N-values not corrected for energy or depth; stratigraphic transitions are approximate and are inferred from cuttings and driller's comments



Unified Classification System (ASTM D-2487)

CL = lean clay to sandy/gravelly lean clay
 ML = silt to sandy/gravelly silt
 CH = high plasticity clay to sandy/gravelly high plasticity clay
 MH = high elasticity silt to sandy/gravelly high elasticity silt
 SW = well-graded sand or well-graded sand with gravel
 SP = poorly graded sand or poorly graded sand with gravel
 SM = silty sand to silty sand with gravel
 SC = clayey sand to clayey sand with gravel
 GW = well-graded gravel or well-graded gravel with sand
 GP = poorly graded gravel or poorly graded gravel with sand
 GM = silty gravel or silty gravel with sand
 GC = clayey gravel or clayey gravel with sand

Sheet 1
 of 1

| |
|---------------|
| Field Testing |
| Lab/Drafting |
| DATE |
| PROJECT # |

KEY
 Test Boring
 and Lab Test Results



Civil, Structural & Geotechnical Engineers
 222 South Park Ave. Montrose, Colorado 81401
 970-249-6828 Fax. No. 970-249-0949

LOG OF EXPLORATORY DRILLING – BORE HOLE #1 (BH06-1)

SURFACE ELEVATION:

DRILLER: McCracken

DRILL RIG: Simco 2800

NOTES: SPT N-values not corrected for energy or depth; stratigraphic transitions are approximate and are inferred from cuttings and drillers comments

DRILL STEM: 4" Solid-stem continuous flight auger

SAMPLER: 1.375" I.D. Standard and 2" I.D. California split spoon

CASING: None used

| DEPTH (ft.) | GRAPHIC | WATER LEVEL | SAMPLE TYPE | SAMPLE NUMBER | SPT BLOW COUNTS | SPT 'N' VALUE (bls) | RECOVERY (in.) | SOIL DESCRIPTION | FIELD & LABORATORY TEST RESULTS |
|-------------|---------|-------------|-------------|---------------|-----------------|---------------------|----------------|--|--|
| 0 | | | | | | | | | |
| 0-5 | | | | GS19 | | | | light brown, dry-damp, compact, silty SAND and GRAVEL with clay (0-5') | |
| 5-6.5 | | | | GS20 BD | 12 13 10 | 23 | 12/ 18 | occasional cobbles driller added water @6.5' | GS20 LL=39 PL=23 PI=16 GF=22.8% SF=39.5% F200=37.7% MC=7.9% |
| 10-11 | | | | GS21 | 21 41 | 62 | 12/ 12 | increase in density to very dense same as above (tan), almost no rock from 11-19' | |
| 14 | | | | | | | | one rock @14' | GS21 LL=37 PL=18 PI=19 GF=16.1% SF=43.3% F200=40.7% MC=5.4% |
| 11-19 | | | | | | | | increase in clay content | |
| 20-21 | | | | GS22 | 50 | 50/3 | 3/3 | brown, damp, very dense, clayey, sandy GRAVEL and COBBLES | |
| 32 | | | | | | | | end of bore hole @32' no groundwater or bedrock encountered | |
| 35 | | | | | | | | | |
| 40 | | | | | | | | | |
| 45 | | | | | | | | | |
| 50 | | | | | | | | | |
| 55 | | | | | | | | | |
| 60 | | | | | | | | | |

| | | |
|--|---------------|------------|
| DRAWING NUMBER 1 OF 4 | INVESTIGATION | TB |
| | DRAFTING | JG |
| | DATE | 2/23/06 |
| | JOB NO. | 06-023-GEO |

JOEY BURNS
552 ACRE RANCH
MONTROSE, COLORADO

BUCKHORN GEOTECH

Civil, Structural, and Geotechnical Engineers, Inc.
222 South Park Avenue
Montrose, Colorado 81401
Phone (970) 249-8828 Fax (970) 249-0945

LOG OF EXPLORATORY DRILLING - BORE HOLE #2 (BH06-2)

SURFACE ELEVATION:

DRILLER: McCracken

DRILL RIG: Simco 2800

NOTES: SPT N-values not corrected for energy or depth; stratigraphic transitions are approximate and are inferred from cuttings and drillers comments

DRILL STEM: 4" Solid-stem continuous flight auger

SAMPLER: 1.375" I.D. Standard and 2" I.D. California split spoon

CASING: None used

| DEPTH (ft.) | GRAPHIC | WATER LEVEL | SAMPLE TYPE | SAMPLE NUMBER | SPT BLOW COUNTS | SPT 'N' VALUE (pcf) | RECOVERY (in.) | SOIL DESCRIPTION | FIELD & LABORATORY TEST RESULTS |
|-------------|---------|-------------|-------------|---------------|-----------------|---------------------|----------------|--|---|
| 0 | | | | | | | | tan, dry, silty SAND and GRAVEL with clay; very dense (0-5') | |
| 5 | | | | GS23 | 15 | 52 | 12/18 | driller hit water @5' same as above | GS24 LL=26 PL=18 PI=8 GF=37.0% SF=54.6% F200=8.4% MC=2.4% |
| | | | | GS24 | 25 | | | | |
| | | | | | 27 | | | dark gray, thinly bedded, jumbled SHALE; highly fractured/highly weathered @11' R1-R2/W3-W4 | |
| 10 | | | | | | | | end of bore hole @17' in dark gray, thinly bedded, formational SHALE R3/W4 no groundwater | |
| 15 | | | | | | | | *Standpipe installed to 12' | |
| 20 | | | | | | | | | |
| 25 | | | | | | | | | |
| 30 | | | | | | | | | |
| 35 | | | | | | | | | |
| 40 | | | | | | | | | |
| 45 | | | | | | | | | |
| 50 | | | | | | | | | |
| 55 | | | | | | | | | |
| 60 | | | | | | | | | |

| | | |
|--|---------------|------------|
| DRAWING NUMBER 2 OF 4 | INVESTIGATION | TB |
| | DRAFTING | JG |
| | DATE | 2/23/06 |
| | JOB NO. | 06-023-GEO |

JOEY BURNS
 552 ACRE RANCH
 MONTROSE, COLORADO

BUCKHORN GEOTECH

Civil, Structural, and Geotechnical Engineers, Inc.
 222 South Park Avenue
 Montrose, Colorado 81401
 Phone (970) 249-6828 Fax (970) 249-0945

LOG OF EXPLORATORY DRILLING - BORE HOLE #3 (BH06-3)

SURFACE ELEVATION:

DRILLER: McCracken

DRILL RIG: Simco 2800

NOTES: SPT N-values not corrected for energy or depth; stratigraphic transitions are approximate and are inferred from cuttings and drillers comments

DRILL STEM: 4" Solid-stem continuous flight auger

SAMPLER: 1.375" I.D. Standard and 2" I.D. California split spoon

CASING: None used

| DEPTH (ft.) | GRAPHIC | WATER LEVEL | SAMPLE TYPE | SAMPLE NUMBER | SPT BLOW COUNTS | SPT 'N' VALUE (bpf) | RECOVERY (in.) | SOIL DESCRIPTION | FIELD & LABORATORY TEST RESULTS |
|-------------|---------|-------------|-------------|---------------|-----------------|---------------------|----------------|--|---------------------------------|
| 0 | | | | | | | | tan, dry, silty GRAVEL with clay to gravelly SILT with clay and trace fine sand (0-5') | |
| 5 | | | | GS25 | 18 | 57 | 12/18 | increased gravel content @4' | |
| | | | | GS26 | 23 | | | tan, dry, very dense, silty SAND and GRAVEL with little clay | |
| | | | | | 34 | | | | |
| 10 | | | | | | | | | |
| 15 | | | | | | | | increase in gravel and cobbles | |
| 20 | | | | | | | | refusal @21' in gravels and cobbles | |
| | | | | | | | | no groundwater or bedrock encountered | |
| 25 | | | | | | | | | |
| 30 | | | | | | | | | |
| 35 | | | | | | | | | |
| 40 | | | | | | | | | |
| 45 | | | | | | | | | |
| 50 | | | | | | | | | |
| 55 | | | | | | | | | |
| 60 | | | | | | | | | |

| | | |
|--|---------------|------------|
| DRAWING NUMBER 3 OF 4 | INVESTIGATION | TB |
| | DRAFTING | JG |
| | DATE | 2/23/06 |
| | JOB NO. | 06-023-GEO |

JOEY BURNS
552 ACRE RANCH
MONTROSE, COLORADO

BUCKHORN GEOTECH

Civil, Structural, and Geotechnical Engineers, Inc.
222 South Park Avenue
Montrose, Colorado 81401
Phone (970) 249-6828 Fax (970) 249-0945

LOG OF EXPLORATORY DRILLING – BORE HOLE #4 (BH06-4)

SURFACE ELEVATION:

DRILLER: McCracken

DRILL RIG: Simco 2800

NOTES: SPT N-values not corrected for energy or depth; stratigraphic transitions are approximate and are inferred from cuttings and drillers comments

DRILL STEM: 4" Solid-stem continuous flight auger

SAMPLER: 1.375" I.D. Standard and 2" I.D. California split spoon

CASING: None used

| DEPTH (ft.) | GRAPHIC | WATER LEVEL | SAMPLE TYPE | SAMPLE NUMBER | SPT BLOW COUNTS | SPT N' VALUE (ppf) | RECOVERY (in.) | SOIL DESCRIPTION | FIELD & LABORATORY TEST RESULTS |
|-------------|---------|-------------|-------------|---------------|-----------------|--------------------|----------------|--|---------------------------------|
| 0 | | | | | | | | light brown, dry, silty SAND and GRAVEL with clay (0-5') | |
| 5 | | | | GS27 | 10 | 41 | 15/18 | driller added water @5' same as above | |
| | | | | GS28 | 17 | | | | |
| | | | | | 24 | | | | |
| 10 | | | | | | | | | |
| 15 | | | | | | | | | |
| 20 | | | | | | | | | |
| 25 | | | | | | | | brown, dry-damp, sandy SILT and CLAY with little gravel @23' driller commented that it became stiff after 23' | |
| 30 | | | | | | | | | |
| 35 | | | | | | | | very little rock from 33-35.5', possible shale contact end of bore hole @35.5' no groundwater encountered | |
| 40 | | | | | | | | | |
| 45 | | | | | | | | | |
| 50 | | | | | | | | | |
| 55 | | | | | | | | | |
| 60 | | | | | | | | | |

GS28
 LL=29 PL=21 PI=8
 GF=40.7%
 SF=43.4%
 F200=15.9%
 MC=3.8%

DRAWING NUMBER

4

OF 4

INVESTIGATION TB

DRAFTING JG

DATE 2/23/06

JOB NO. 06-023-GEO

JOEY BURNS
 552 ACRE RANCH
 MONTROSE, COLORADO

BUCKHORN GEOTECH

Civil, Structural, and Geotechnical Engineers, Inc.
 222 South Park Avenue
 Montrose, Colorado 81401
 Phone (970) 249-6828 Fax (970) 249-0945

Summary of Laboratory Test Results

| Soil Identification | | | | Index | | | Gradation | | | Atterberg Limits | | | Heave Potential | | | Consolidation (%) | |
|---------------------|--------------------------------------|------------------------------|----------------------|--------------------------|-------------------|----------------------------|--------------|--------------|---------------------------|------------------|----------------------|----------------------|--------------------------|---------------------|----------------------|-------------------|----------------------|
| Location | Depth (ft.) | Sample | USCS | Moisture Content (%) | Dry Density (pcf) | Water-soluble Sulfates (%) | Gravel (%) | Sand (%) | Fines (silt and clay) (%) | Liquid Limit (%) | Plasticity Index (%) | Swell Pressure (psf) | Confining Pressure (psf) | Swell Potential (%) | Initial Collapse (%) | Consolidation (%) | Final Pressure (psf) |
| TP#1 | 3-5' 4' | GS1 "S" | CH | 13.7 | 101.5 | | | | | 53 | 26 | 2570 | 8000 | 16.5 | | | |
| | | | CH | 12.1 | | | | | | | | | | | | | |
| TP#2 | 2-3' 5-6' 5.5' | GS2 GS3 "AQ" | CH CL CL | 28.6 24 14.7 | | 0.168 | 0 | 6.2 37.7 | 91.8 82.3 | 52 43 | 32 20 | | | | | | |
| TP#3 | 3-4' 3.5' | GS4 "H" | CL CL | 25.1 23.3 | 93.5 | | 0 | 23.6 | 76.4 | 39 | 19 | 180 | 2000 | 0.4 | 1.4 | 2.3 | 2000 |
| TP#4 | 4-5' 5' | GS5 "G" | CH CH | 24.4 24.3 | 97.8 | | 0 | 2 | 98 | 54 | 32 | 920 | 2000 | 2.8 | | | |
| TP#5 | 3.5-4.5' | GS6 | CH | 23.2 | | 0.189 | 0 | 4.7 | 95.3 | 50 | 29 | | | | | | |
| TP#6 | 5-5.5' | GS8 | GW | 5.3 | | | 69.1 | 27.7 | 3.2 | NP | NP | | | | | | |
| TP#8 | 4-5' | GS10 | CL | 6.8 | | | 29.3 | 19.3 | 51.5 | 42 | 23 | | | | | | |
| TP#9 | 3.5-4.5' 2-3' | GS11 BS2 | CL CL | 15.2 15.2 | | | 16.4 16.4 | 18.2 18.2 | 65.4 65.4 | 40 40 | 20 20 | | | | | | |
| TP#10 | 5' 2-3' | "GU" BS3 | CL CL | 11.6 | 110.8 | | 14.3 | 33.2 | 52 | 44 | 19 | 650 | 2000 | 4.8 | | | |
| TP#11 | 2-3' | BS4 | GC | | | | 49.2 | 15.5 | 35.3 | 44 | 23 | | | | | | |
| TP#13 | 4-5' 4.5' | GS15 "H46" | CL CL | 17.5 18.3 | 105.4 | | 20.1 | 18.3 | 51.8 | 47 | 26 | 950 | 2000 | 2.3 | | | |
| TP#14 | 3.5-4.5' | GS16 | CL | 13.3 | | 0.539 | 26.6 | 23.4 | 50 | 49 | 26 | | | | | | |
| TP#15 | 3-4' | GS17 | CL | 10.4 | | | 8.3 | 31.2 | 60.5 | 43 | 22 | | | | | | |
| TP#16 | 3-4' 4' | GS18 "HMT" | CL CL | 12.8 12.5 | 102.9 | | 0 | 18.3 | 83.7 | 45 | 23 | 1280 | 4000 | 5.3 | | | |
| TP#18 | 6-10' | GS31 | GW | 3.2 | | | 61.5 | 34.1 | 4.4 | 29 | 11 | | | | | | |
| TP#19 | 4-5' | GS32 | GW | 4.2 | | | 92.6 | 6.2 | 1.2 | NP | NP | | | | | | |
| TP#20 | 3.5' | "NY" | GW | 9.8 | 77.7 | | | | | | | | | | | | |
| BP-06-1 | 5-6.5' 10-11' 5-6.5' 10-11' | GS20 GS21 "BD" "DD" | SC SC SC SC | 7.9 5.4 8.6 6.7 | | | 22.8 16.1 | 39.5 43.3 | 37.7 40.7 | 39 37 | 16 19 | | | | | | |
| BP-06-2 | 5-6.5' | GS24 | SW-SC | 2.4 | | | 37 | 54.8 | 8.4 | 26 | 8 | 1610 | 4000 | 7.4 | 0.6 | 8 | 2000 |
| BP-06-4 | 5-5.5' | GS28 | SC | 3.8 | | | 40.7 | 43.4 | 15.9 | 29 | 8 | | | | | | |

Project Name Montrose 552-Acre Ranch
 Project Location Government Springs Rd
 Client Joey Burns
 Test Location TP#1 @3-5'
 Sample # GS1

Date 2/2/2006
 Project # 06-023-GEO
 Sample by TB
 Tested by SM

Sieve Analysis
 ASTM C136 / C117


| Sieve | Opening (mm) | % Passing |
|-------|--------------|-----------|
| 3" | 76.2 | 100.0 |
| 3/4" | 19.0 | 97.1 |
| 3/8" | 9.5 | 91.3 |
| #4 | 4.75 | 54.2 |
| #10 | 2.0 | 22.6 |
| #40 | 0.425 | 5.0 |
| #200 | 0.075 | 0.5 |

Atterberg Limits
 ASTM D4318

| | |
|-----------------------|-----------|
| Liquid Limit (LL) | <u>53</u> |
| Plastic Limit (PL) | <u>27</u> |
| Plasticity Index (PI) | <u>26</u> |

Natural Moisture Content (%) = 13.7%

Soil Description dk. gray-brown fat clayey SHALE *all clay shale*
 USCS Classification SW



| | | | | | |
|--------------|-------------|--------|--------|---------------|--------|
| Clay/Silt | Fine | Medium | Coarse | Fine | Coarse |
| FINES | SAND | | | GRAVEL | |

% Fines = 0.4 % Sand = 53.7 % Gravel = 45.8

BUCKHORN GEOTECH

Civil, Structural & Geotechnical Engineers

222 South Park Ave. • Montrose, CO 81401
 Ph (970) 249-6828 • FAX: (970) 249-0945

Project Name Montrose 552-Acre Ranch
 Project Location Government Springs Rd
 Client Joey Burns
 Test Location TP#2 @2-3'
 Sample # GS2

Date 2/2/2006
 Project # 06-023-GEO
 Sample by TB
 Tested by SM

Sieve Analysis ASTM C136 / C117


| Sieve | Opening (mm) | % Passing |
|-------|--------------|-----------|
| 3" | 76.2 | 100.0 |
| 3/4" | 19.0 | 100.0 |
| 3/8" | 9.5 | 100.0 |
| #4 | 4.75 | 100.0 |
| #10 | 2.0 | 99.0 |
| #40 | 0.425 | 96.6 |
| #200 | 0.075 | 91.8 |

Atterberg Limits ASTM D4318

| | |
|-----------------------|-----------|
| Liquid Limit (LL) | <u>52</u> |
| Plastic Limit (PL) | <u>20</u> |
| Plasticity Index (PI) | <u>32</u> |

Natural Moisture Content (%) = 29.6%

Soil Description gray-brown fat CLAY
 USCS Classification CH



| Clay/Silt | Fine | Medium | Coarse | Fine | Coarse |
|--------------|-------------|--------|--------|---------------|--------|
| FINES | SAND | | | GRAVEL | |

% Fines = 91.8

% Sand = 8.2

% Gravel = 0.0

BUCKHORN GEOTECH

Civil, Structural & Geotechnical Engineers

222 South Park Ave. • Montrose, CO 81401
 Ph: (970) 249-6628 • FAX: (970) 249-0945

Project Name Montrose 552-Acre Ranch
 Project Location Government Springs Rd
 Client Joey Burns
 Test Location TP#2 @5-6'
 Sample # GS3

Date 2/2/2006
 Project # 06-023-GEO
 Sample by TB
 Tested by VB

Sieve Analysis ASTM C136 / C117


| Sieve | Opening (mm) | % Passing |
|-------|--------------|-----------|
| 3" | 76.2 | 100.0 |
| 3/4" | 19.0 | 100.0 |
| 3/8" | 9.5 | 100.0 |
| #4 | 4.75 | 100.0 |
| #10 | 2.0 | 96.9 |
| #40 | 0.425 | 79.3 |
| #200 | 0.075 | 62.3 |

Atterberg Limits ASTM D4318

| | |
|-----------------------|-----------|
| Liquid Limit (LL) | <u>43</u> |
| Plastic Limit (PL) | <u>23</u> |
| Plasticity Index (PI) | <u>20</u> |

Natural Moisture Content (%) = 24.0%

Soil Description gray-brown sandy lean CLAY
 USCS Classification CL



| Clay/Silt | Fine | Medium | Coarse | Fine | Coarse | |
|--------------|------|-------------|--------|------|---------------|--|
| FINES | | SAND | | | GRAVEL | |

% Fines = 62.3 % Sand = 37.7 % Gravel = 0.0

BUCKHORN GEOTECH

Civil, Structural & Geotechnical Engineers

222 South Park Ave • Montrose, CO 81401
 Ph: (970) 249-6828 • FAX: (970) 249-0945

Project Name Montrose 552-Acre Ranch
 Project Location Government Springs Rd
 Client Joey Burns
 Test Location TP#3 @3-4'
 Sample # GS4

Date 2/2/2006
 Project # 06-023-GEO
 Sample by TB
 Tested by SM

Sieve Analysis ASTM C136 / C117


| Sieve | Opening (mm) | % Passing |
|-------|--------------|-----------|
| 3" | 76.2 | 100.0 |
| 3/4" | 19.0 | 100.0 |
| 3/8" | 9.5 | 100.0 |
| #4 | 4.75 | 100.0 |
| #10 | 2.0 | 99.0 |
| #40 | 0.425 | 95.1 |
| #200 | 0.075 | 76.4 |

Atterberg Limits ASTM D4318

| | |
|-----------------------|-----------|
| Liquid Limit (LL) | <u>39</u> |
| Plastic Limit (PL) | <u>20</u> |
| Plasticity Index (PI) | <u>19</u> |

Natural Moisture Content (%) = 25.1%

Soil Description brown lean CLAY with sand
 USCS Classification CL



| | | | | | |
|--------------|-------------|--------|--------|---------------|--------|
| Clay/Silt | Fine | Medium | Coarse | Fine | Coarse |
| FINES | SAND | | | GRAVEL | |

% Fines = 76.4 % Sand = 23.6 % Gravel = 0.0

Project Name Montrose 552-Acre Ranch
 Project Location Government Springs Rd
 Client Joey Burns
 Test Location TP#4 @4-5'
 Sample # GS5

Date 2/6/2006
 Project # 06-023-GEO
 Sample by TB
 Tested by SM

Sieve Analysis
 ASTM C136 / C117


| Sieve | Opening (mm) | % Passing |
|-------|--------------|-----------|
| 3" | 76.2 | 100.0 |
| 3/4" | 19.0 | 100.0 |
| 3/8" | 9.5 | 100.0 |
| #4 | 4.75 | 100.0 |
| #10 | 2.0 | 100.0 |
| #40 | 0.425 | 99.8 |
| #200 | 0.075 | 98.0 |

Atterberg Limits
 ASTM D4318

| | |
|-----------------------|-----------|
| Liquid Limit (LL) | <u>54</u> |
| Plastic Limit (PL) | <u>22</u> |
| Plasticity Index (PI) | <u>32</u> |

Natural Moisture Content (%) = 24.4%

Soil Description gray-brown fat CLAY
 USCS Classification CH



| Clay/Silt | Fine | Medium | Coarse | Fine | Coarse |
|--------------|-------------|--------|--------|---------------|--------|
| FINES | SAND | | | GRAVEL | |

% Fines = 98.0 % Sand = 2.0 % Gravel = 0.0

Project Name Montrose 552-Acre Ranch
 Project Location Government Springs Rd
 Client Joey Burns
 Test Location TP#5 @3.5-4.5'
 Sample # GS6

Date 2/6/2006
 Project # 06-023-GEO
 Sample by TB
 Tested by LS/SM

Sieve Analysis
ASTM C136 / C117


| Sieve | Opening (mm) | % Passing |
|-------|--------------|-----------|
| 3" | 76.2 | 100.0 |
| 3/4" | 19.0 | 100.0 |
| 3/8" | 9.5 | 100.0 |
| #4 | 4.75 | 100.0 |
| #10 | 2.0 | 99.7 |
| #40 | 0.425 | 99.1 |
| #200 | 0.075 | 95.3 |

Atterberg Limits
ASTM D4318

| | |
|-----------------------|-----------|
| Liquid Limit (LL) | <u>50</u> |
| Plastic Limit (PL) | <u>21</u> |
| Plasticity Index (PI) | <u>29</u> |

Natural Moisture Content (%) = 23.2%

Soil Description gray-brown fat CLAY
 USCS Classification CH



| Clay/Silt | Fine | Medium | Coarse | Fine | Coarse | |
|--------------|------|-------------|--------|------|---------------|--|
| FINES | | SAND | | | GRAVEL | |

% Fines = 95.3 % Sand = 4.7 % Gravel = 0.0

Project Name Montrose 552-Acre Ranch
 Project Location Government Springs Rd
 Client Joey Burns
 Test Location TP#6 @5-5.5'
 Sample # GS8

Date 2/2/2006
 Project # 06-023-GEO
 Sample by TB
 Tested by SM/LS

Sieve Analysis

ASTM C136 / C117

| Sieve | Opening (mm) | % Passing |
|-------|--------------|-----------|
| 3" | 76.2 | 100.0 |
| 3/4" | 19.0 | 52.8 |
| 3/8" | 9.5 | 38.6 |
| #4 | 4.75 | 30.9 |
| #10 | 2.0 | 25.5 |
| #40 | 0.425 | 10.7 |
| #200 | 0.075 | 3.2 |

Atterberg Limits


ASTM D4318

| | |
|-----------------------|-----------|
| Liquid Limit (LL) | <u>NP</u> |
| Plastic Limit (PL) | <u>NP</u> |
| Plasticity Index (PI) | <u>NP</u> |

NP = Non-Plastic

Natural Moisture Content (%) = 5.3%

Soil Description reddish-brown well-graded GRAVEL with sand
 USCS Classification GW



| Clay/Silt | Fine | Medium | Coarse | Fine | Coarse | |
|--------------|------|-------------|--------|------|---------------|--|
| FINES | | SAND | | | GRAVEL | |

% Fines = 3.2 % Sand = 27.7 % Gravel = 69.1

Project Name Montrose 552-Acre Ranch
 Project Location Government Springs Rd
 Client Joey Burns
 Test Location TP#8 @4-5'
 Sample # GS10

Date 2/7/2006
 Project # 06-023-GEO
 Sample by TB
 Tested by BAU

Sieve Analysis

ASTM C136 / C117

| Sieve | Opening (mm) | % Passing |
|-------|--------------|-----------|
| 3" | 76.2 | 100.0 |
| 3/4" | 19.0 | 87.9 |
| 3/8" | 9.5 | 78.6 |
| #4 | 4.75 | 70.7 |
| #10 | 2.0 | 63.9 |
| #40 | 0.425 | 58.1 |
| #200 | 0.075 | 51.5 |


Atterberg Limits

ASTM D4318

| | |
|-----------------------|-----------|
| Liquid Limit (LL) | <u>42</u> |
| Plastic Limit (PL) | <u>19</u> |
| Plasticity Index (PI) | <u>23</u> |

Natural Moisture Content (%) = 6.8%

Soil Description brown gravelly lean CLAY with sand
 USCS Classification CL



| | | | | | |
|--------------|-------------|--------|--------|---------------|--------|
| Clay/Silt | Fine | Medium | Coarse | Fine | Coarse |
| FINES | SAND | | | GRAVEL | |

% Fines = 51.5 % Sand = 19.3 % Gravel = 29.3

Project Name Montrose 552-Acre Ranch
 Project Location Government Springs Rd
 Client Joey Burns
 Test Location TP#9 @3.5-4.5'
 Sample # GS11

Date 2/9/2006
 Project # 06-023-GEO
 Sample by TB
 Tested by SM

Sieve Analysis
 ASTM C136 / C117


| Sieve | Opening (mm) | % Passing |
|-------|--------------|-----------|
| 3" | 76.2 | 100.0 |
| 3/4" | 19.0 | 90.1 |
| 3/8" | 9.5 | 88.0 |
| #4 | 4.750 | 83.6 |
| #10 | 2.000 | 80.6 |
| #40 | 0.425 | 76.8 |
| #200 | 0.075 | 65.4 |

Atterberg Limits
 ASTM D4318

| | |
|-----------------------|-----------|
| Liquid Limit (LL) | <u>40</u> |
| Plastic Limit (PL) | <u>20</u> |
| Plasticity Index (PI) | <u>20</u> |

Natural Moisture Content (%) = 15.2%

Soil Description gray-brown sandy lean CLAY with gravel
 USCS Classification CL



| Clay/Silt | Fine | Medium | Coarse | Fine | Coarse |
|--------------|-------------|--------|--------|---------------|--------|
| FINES | SAND | | | GRAVEL | |

% Fines = 65.4 % Sand = 18.2 % Gravel = 16.4

Project Name Montrose 552-Acre Ranch
 Project Location Government Springs Rd
 Client Joey Burns
 Test Location TP#13 @4-5'
 Sample # GS15

Date 2/9/2006
 Project # 06-023-GEO
 Sample by TB
 Tested by SM

Sieve Analysis
ASTM C136 / C117


| Sieve | Opening (mm) | % Passing |
|-------|--------------|-----------|
| 3" | 76.2 | 100.0 |
| 3/4" | 19.0 | 91.0 |
| 3/8" | 9.5 | 85.1 |
| #4 | 4.750 | 79.9 |
| #10 | 2.000 | 73.9 |
| #40 | 0.425 | 68.5 |
| #200 | 0.075 | 61.6 |

Atterberg Limits
ASTM D4318

| | |
|-----------------------|-----------|
| Liquid Limit (LL) | <u>47</u> |
| Plastic Limit (PL) | <u>21</u> |
| Plasticity Index (PI) | <u>26</u> |

Natural Moisture Content (%) = 17.5%

Soil Description gray brown gravelly lean CLAY with sand
 USCS Classification CL



| Clay/Silt | Fine | Medium | Coarse | Fine | Coarse |
|--------------|-------------|--------|--------|---------------|--------|
| FINES | SAND | | | GRAVEL | |

% Fines = 61.6 % Sand = 18.3 % Gravel = 20.1

Project Name Montrose 552-Acre Ranch
 Project Location Government Springs Rd
 Client Joey Burns
 Test Location TP#14 @3.5-4.5'
 Sample # GS16

Date 2/9/2006
 Project # 06-023-GEO
 Sample by TB
 Tested by SM

Sieve Analysis
ASTM C136 / C117


| Sieve | Opening (mm) | % Passing |
|-------|--------------|-----------|
| 3" | 76.2 | 100.0 |
| 3/4" | 19.0 | 82.9 |
| 3/8" | 9.5 | 79.2 |
| #4 | 4.750 | 73.4 |
| #10 | 2.000 | 69.1 |
| #40 | 0.425 | 63.8 |
| #200 | 0.075 | 50.0 |

Atterberg Limits
ASTM D4318

| | |
|-----------------------|-----------|
| Liquid Limit (LL) | <u>49</u> |
| Plastic Limit (PL) | <u>23</u> |
| Plasticity Index (PI) | <u>26</u> |

Natural Moisture Content (%) = 13.3%

Soil Description light brown-gray gravelly lean CLAY with sand
 USCS Classification CL



| Clay/Silt | Fine | Medium | Coarse | Fine | Coarse |
|--------------|-------------|--------|--------|---------------|--------|
| FINES | SAND | | | GRAVEL | |

% Fines = 50.0 % Sand = 23.3 % Gravel = 26.6

Project Name Montrose 552-Acre Ranch
 Project Location Government Springs Rd
 Client Joey Burns
 Test Location TP#15 @3-4'
 Sample # GS17

Date 2/8/2006
 Project # 06-023-GEO
 Sample by TB
 Tested by SM/BAU

Sieve Analysis
ASTM C136


| Sieve | Opening (mm) | % Passing |
|-------|--------------|-----------|
| 3" | 76.2 | 100.0 |
| 3/4" | 19.0 | 100.0 |
| 3/8" | 9.5 | 96.7 |
| #4 | 4.750 | 91.7 |
| #10 | 2.000 | 85.7 |
| #40 | 0.425 | 72.9 |
| #200 | 0.075 | 0.0 |

Atterberg Limits
ASTM D4318

| | |
|-----------------------|-----------|
| Liquid Limit (LL) | <u>43</u> |
| Plastic Limit (PL) | <u>21</u> |
| Plasticity Index (PI) | <u>22</u> |

Natural Moisture Content (%) = 10.4%

Soil Description gray-brown sandy lean CLAY
 USCS Classification CL



| Clay/Silt | Fine | Medium | Coarse | Fine | Coarse | |
|--------------|------|-------------|--------|------|---------------|--|
| FINES | | SAND | | | GRAVEL | |

% Fines = 60.5 % Sand = 31.2 % Gravel = 8.3

Project Name Montrose 552-Acre Ranch
 Project Location Government Springs Rd
 Client Joey Burns
 Test Location TP#16 @3-4'
 Sample # GS18

Date 2/8/2006
 Project # 06-023-GEO
 Sample by TB
 Tested by SM

Sieve Analysis
ASTM C136 / C117


| Sieve | Opening (mm) | % Passing |
|-------|--------------|-----------|
| 3" | 76.2 | 100.0 |
| 3/4" | 19.0 | 100.0 |
| 3/8" | 9.5 | 100.0 |
| #4 | 4.75 | 100.0 |
| #10 | 2.0 | 99.3 |
| #40 | 0.425 | 95.8 |
| #200 | 0.075 | 83.7 |

Atterberg Limits
ASTM D4318

| | |
|-----------------------|-----------|
| Liquid Limit (LL) | <u>45</u> |
| Plastic Limit (PL) | <u>22</u> |
| Plasticity Index (PI) | <u>23</u> |

Natural Moisture Content (%) = 12.8%

Soil Description light brown-gray lean CLAY with sand
 USCS Classification CL



| Clay/Silt | Fine | Medium | Coarse | Fine | Coarse |
|--------------|-------------|--------|--------|---------------|--------|
| FINES | SAND | | | GRAVEL | |

% Fines = 83.7 % Sand = 16.3 % Gravel = 0.0

Project Name Montrose 552 Acre Ranch
 Project Location Government Springs Rd
 Client Joey Burns
 Test Location BH06-1 @5-6.5'
 Sample # GS20

Date 2/27/2006
 Project # 06-023-GEO
 Sample by TB
 Tested by VB/SM

Sieve Analysis
 ASTM C136 / C117


| Sieve | Opening (mm) | % Passing |
|-------|--------------|-----------|
| 3" | 76.2 | 100.0 |
| 3/4" | 19.0 | 96.5 |
| 3/8" | 9.5 | 86.4 |
| #4 | 4.750 | 77.2 |
| #10 | 2.000 | 70.2 |
| #40 | 0.425 | 57.8 |
| #200 | 0.075 | 37.7 |

Atterberg Limits
 ASTM D4318

| | |
|-----------------------|-----------|
| Liquid Limit (LL) | <u>39</u> |
| Plastic Limit (PL) | <u>23</u> |
| Plasticity Index (PI) | <u>16</u> |

Natural Moisture Content (%) = 7.9%

Soil Description brown clayey SAND with gravel
 USCS Classification SC



| Clay/Silt | Fine | Medium | Coarse | Fine | Coarse |
|--------------|-------------|--------|--------|---------------|--------|
| FINES | SAND | | | GRAVEL | |

% Fines = 37.7 % Sand = 39.5 % Gravel = 22.8

Project Name Montrose 552 Acre Ranch
 Project Location Government Springs Rd
 Client Joey Burns
 Test Location BH06-1 @10-11'
 Sample # GS21

Date 2/28/2006
 Project # 06-023-GEO
 Sample by TB
 Tested by SM

Sieve Analysis

ASTM C136 / C117

| Sieve | Opening (mm) | % Passing |
|-------|--------------|-----------|
| 3" | 76.2 | 100.0 |
| 3/4" | 19.0 | 95.2 |
| 3/8" | 9.5 | 91.0 |
| #4 | 4.750 | 83.9 |
| #10 | 2.000 | 75.0 |
| #40 | 0.425 | 60.1 |
| #200 | 0.075 | 40.7 |


Atterberg Limits

ASTM D4318

| | |
|-----------------------|-----------|
| Liquid Limit (LL) | <u>37</u> |
| Plastic Limit (PL) | <u>18</u> |
| Plasticity Index (PI) | <u>19</u> |

Natural Moisture Content (%) = 5.4%

Soil Description brown clayey SAND with gravel
 USCS Classification SC



| Clay/Silt | Fine | Medium | Coarse | Fine | Coarse |
|--------------|-------------|--------|--------|---------------|--------|
| FINES | SAND | | | GRAVEL | |

% Fines = 40.7 % Sand = 43.3 % Gravel = 16.1

Project Name Montrose 552 Acre Ranch
 Project Location Government Springs Rd
 Client Joey Burns
 Test Location BH06-2 @5-6.5'
 Sample # GS24

Date 2/28/2006
 Project # 06-023-GEO
 Sample by TB
 Tested by SM

Sieve Analysis

ASTM C136 / C117

| Sieve | Opening (mm) | % Passing |
|-------|--------------|-----------|
| 3" | 76.2 | 100.0 |
| 3/4" | 19.0 | 83.4 |
| 3/8" | 9.5 | 74.0 |
| #4 | 4.750 | 63.0 |
| #10 | 2.000 | 48.2 |
| #40 | 0.425 | 21.3 |
| #200 | 0.075 | 8.4 |


Atterberg Limits

ASTM D4318

| | |
|-----------------------|-----------|
| Liquid Limit (LL) | <u>26</u> |
| Plastic Limit (PL) | <u>18</u> |
| Plasticity Index (PI) | <u>8</u> |

Natural Moisture Content (%) = 2.4%

Soil Description light brown well-graded SAND with clay and gravel
 USCS Classification SW-SC



| Clay/Silt | Fine | Medium | Coarse | Fine | Coarse |
|--------------|-------------|--------|--------|---------------|--------|
| FINES | SAND | | | GRAVEL | |

% Fines = 8.4 % Sand = 54.6 % Gravel = 37.0

BUCKHORN GEOTECH

Civil, Structural & Geotechnical Engineers

222 South Park Ave • Montrose, CO 81401
 Ph (970) 249-6828 • FAX (970) 249-0945

Project Name Montrose 552 Acre Ranch
 Project Location Government Springs Rd
 Client Joey Burns
 Test Location BH06-4 @5-6.5'
 Sample # GS28

Date 2/28/2006
 Project # 06-023-GEO
 Sample by TB
 Tested by VB/BAU

Sieve Analysis

ASTM C136 / C117

| Sieve | Opening (mm) | % Passing |
|-------|--------------|-----------|
| 3" | 76.2 | 100.0 |
| 3/4" | 19.0 | 84.2 |
| 3/8" | 9.5 | 71.7 |
| #4 | 4.750 | 59.3 |
| #10 | 2.000 | 46.2 |
| #40 | 0.425 | 27.3 |
| #200 | 0.075 | 15.9 |


Atterberg Limits

ASTM D4318

| | |
|-----------------------|-----------|
| Liquid Limit (LL) | <u>29</u> |
| Plastic Limit (PL) | <u>21</u> |
| Plasticity Index (PI) | <u>8</u> |

Natural Moisture Content (%) = 3.8%

Soil Description light brown clayey SAND with gravel
 USCS Classification SC



| Clay/Silt | Fine | Medium | Coarse | Fine | Coarse |
|--------------|-------------|--------|--------|---------------|--------|
| FINES | SAND | | | GRAVEL | |

% Fines = 15.9 % Sand = 43.4 % Gravel = 40.7

Sieve Analysis and Atterberg Limits

| | | | |
|------------------|--------------------------------|-----------|-------------------|
| Project Name | <u>Montrose 552 Acre Ranch</u> | Date | <u>3/29/2006</u> |
| Project Location | <u>Government Springs Rd</u> | Project # | <u>06-023-GEO</u> |
| Client | <u>Joey Burns</u> | Sample by | <u>TB</u> |
| Test Location | <u>TP#18 @6-10'</u> | Tested by | <u>VB</u> |
| Sample # | <u>GS31</u> | | |

Sieve Analysis

ASTM C136 / C117

| Sieve | Opening (mm) | % Passing |
|-------|--------------|-----------|
| 3" | 76.2 | 100.0 |
| 3/4" | 19.0 | 72.2 |
| 3/8" | 9.5 | 53.0 |
| #4 | 4.750 | 38.5 |
| #10 | 2.000 | 24.3 |
| #40 | 0.425 | 10.3 |
| #200 | 0.075 | 4.4 |

Atterberg Limits


ASTM D4318

| | |
|-----------------------|-----------|
| Liquid Limit (LL) | <u>29</u> |
| Plastic Limit (PL) | <u>18</u> |
| Plasticity Index (PI) | <u>11</u> |

Natural Moisture Content (%) = 3.2%

Soil Description gray-brown well-graded GRAVEL with sand

USCS Classification GW



| Clay/Silt | Fine | Medium | Coarse | Fine | Coarse |
|--------------|-------------|--------|--------|---------------|--------|
| FINES | SAND | | | GRAVEL | |

% Fines = 4.4 % Sand = 34.1 % Gravel = 61.5

Sieve Analysis and Atterberg Limits

Project Name Montrose 552 Acre Ranch
 Project Location Government Springs Rd
 Client Joey Burns
 Test Location TP#19 @4.0-5.0'
 Sample # GS32

Date 4/3/2006
 Project # 06-023-GEO
 Sample by TB
 Tested by VB

Sieve Analysis
ASTM C136 / C117

| Sieve | Opening (mm) | % Passing |
|-------|--------------|-----------|
| 3" | 76.2 | 100.0 |
| 3/4" | 19.0 | 23.8 |
| 3/8" | 9.5 | 11.6 |
| #4 | 4.75 | 7.4 |
| #10 | 2.0 | 5.5 |
| #40 | 0.425 | 3.0 |
| #200 | 0.075 | 1.2 |


Atterberg Limits
ASTM D4318

| | |
|-----------------------|-----------|
| Liquid Limit (LL) | <u>NP</u> |
| Plastic Limit (PL) | <u>NP</u> |
| Plasticity Index (PI) | <u>NP</u> |

NP = Non-Plastic

Natural Moisture Content (%) = 4.2%

Soil Description gray well-graded GRAVEL
 USCS Classification GW



| | | | | | |
|--------------|-------------|--------|--------|---------------|--------|
| Clay/Silt | Fine | Medium | Coarse | Fine | Coarse |
| FINES | SAND | | | GRAVEL | |

% Fines = 1.2 % Sand = 6.2 % Gravel = 92.6

Sieve Analysis and Atterberg Limits

| | | | |
|------------------|--------------------------------|-----------|-------------------|
| Project Name | <u>Montrose 552 Acre Ranch</u> | Date | <u>4/11/2006</u> |
| Project Location | <u>Government Springs Rd</u> | Project # | <u>06-023-GEO</u> |
| Client | <u>Joey Burns</u> | Sample by | <u>TB</u> |
| Test Location | <u>TP#10 @2-5'</u> | Tested by | <u>VB/BAU</u> |
| Sample # | <u>BS3</u> | | |


Sieve Analysis
ASTM C136 / C117

| Sieve | Opening (mm) | % Passing |
|-------|--------------|-----------|
| 3" | 76.2 | 100.0 |
| 3/4" | 19.0 | 99.6 |
| 3/8" | 9.5 | 98.2 |
| #4 | 4.750 | 85.7 |
| #10 | 2.000 | 79.9 |
| #40 | 0.425 | 68.5 |
| #200 | 0.075 | 52.6 |

Atterberg Limits
ASTM D4318

| | |
|-----------------------|-----------|
| Liquid Limit (LL) | <u>44</u> |
| Plastic Limit (PL) | <u>25</u> |
| Plasticity Index (PI) | <u>19</u> |

Soil Description dark gray sandy lean CLAY (shale)
USCS Classification CL



| Clay/Silt | Fine | Medium | Coarse | Fine | Coarse |
|--------------|-------------|--------|--------|---------------|--------|
| FINES | SAND | | | GRAVEL | |

% Fines = 52.6 % Sand = 33.2 % Gravel = 14.3

Sieve Analysis and Atterberg Limits

Project Name Montrose 552 Acre Ranch
 Project Location Government Springs Rd
 Client Joey Burns
 Test Location TP#11 @2-5'
 Sample # BS4

Date 4/11/2006
 Project # 06-023-GEO
 Sample by TB
 Tested by BAU


Sieve Analysis
ASTM C136 / C117

| Sieve | Opening (mm) | % Passing |
|-------|--------------|-----------|
| 3" | 76.2 | 100.0 |
| 3/4" | 19.0 | 62.8 |
| 3/8" | 9.5 | 56.0 |
| #4 | 4.750 | 50.8 |
| #10 | 2.000 | 45.1 |
| #40 | 0.425 | 39.6 |
| #200 | 0.075 | 35.3 |

Atterberg Limits
ASTM D4318

| | |
|-----------------------|-----------|
| Liquid Limit (LL) | <u>44</u> |
| Plastic Limit (PL) | <u>21</u> |
| Plasticity Index (PI) | <u>23</u> |

Soil Description light brown clayey GRAVEL with sand
 USCS Classification GC



| | | | | | |
|--------------|------|-------------|--------|---------------|--------|
| Clay/Silt | Fine | Medium | Coarse | Fine | Coarse |
| FINES | | SAND | | GRAVEL | |


% Fines = 35.3 % Sand = 15.5 % Gravel = 49.2

Swell/Consolidation Test
ASTM D4546

Project Name Montrose 552 Acre Ranch
 Location TP#1 @4'
 Sample # S
 Soil Description dark gray clayey SHALE
 Comments _____

Date 02/01/06
 Project # 06-023-GEO
 Sample by TB
 Test by BAU
 Test for TB
 Drafting by BAU

| | | | |
|--|-----------|-------------------------|-----------|
| Initial compression (Due to 100 psf pressure) =4.49% | | | |
| Initial swell (Due to water & 100 psf pressure) =15.50% | | | |
| Total consolidation (Due to water & 8000 psf pressure) =19.80% | | | |
| Estimated swelling pressure =2570 psf | | | |
| Initial Moisture Content | 12.1 % | Final Moisture Content | 28.3 % |
| Initial Dry Density | 101.5 pcf | Final Dry Density | 98.0 pcf |
| Initial Wet Density | 113.9 pcf | Final Saturated Density | 125.8 pcf |




Swell/Consolidation Test
 ASTM D4546

Project Name Montrose 552 Acre Ranch
 Location TP#2 @5.5'
 Sample # AQ
 Soil Description gray-brown sandy lean CLAY (CL)
 Comments _____

Date 02/02/06
 Project # 06-023-GEO
 Sample by TB
 Test by SM
 Test for TB
 Drafting by BAU

Initial compression (Due to 100 psf pressure) = 1.44%
 Initial consolidation (Due to water & 100 psf pressure) = 0.07%
 Total consolidation (Due to water & 2000 psf pressure) = 2.29%

| | | | |
|--------------------------|-----------|-------------------------|-----------|
| Initial Moisture Content | 14.7 % | Final Moisture Content | 15.0 % |
| Initial Dry Density | 114.3 pcf | Final Dry Density | 120.1 pcf |
| Initial Wet Density | 131.0 pcf | Final Saturated Density | 138.1 pcf |




Swell/Consolidation Test
ASTM D4546

Project Name Montrose 552 Acre Ranch
 Location TP#3 @3.5'
 Sample # H
 Soil Description brown lean CLAY with sand (CL)
 Comments _____

Date 02/02/06
 Project # 06-023-GEO
 Sample by TB
 Test by SM
 Test for TB
 Drafting by BAU

| | | | |
|--|-----------|-------------------------|-----------|
| Initial compression (Due to 100 psf pressure) <u>-3.10%</u> | | | |
| Initial swell (Due to water & 100 psf pressure) <u>0.41%</u> | | | |
| Total consolidation (Due to water & 2000 psf pressure) <u>-5.12%</u> | | | |
| Estimated swelling pressure <u>190 psf</u> | | | |
| Initial Moisture Content | 23.3 % | Final Moisture Content | 26.6 % |
| Initial Dry Density | 93.5 pcf | Final Dry Density | 97.4 pcf |
| Initial Wet Density | 115.3 pcf | Final Saturated Density | 123.3 pcf |




Swell/Consolidation Test

ASTM D4546

Project Name Montrose 552 Acre Ranch
 Location TP#4 @5'
 Sample # G
 Soil Description gray-brown fat CLAY (CH)
 Comments _____

Date 02/02/06
 Project # 06-023-GEO
 Sample by TB
 Test by SM
 Test for TB
 Drafting by BAU

| | | | |
|--|-----------|-------------------------|-----------|
| Initial compression (Due to 100 psf pressure) <u>-3.73%</u> | | | |
| Initial swell (Due to water & 100 psf pressure) <u>-2.76%</u> | | | |
| Total consolidation (Due to water & 2000 psf pressure) <u>-3.24%</u> | | | |
| Estimated swelling pressure <u>=920 psf</u> | | | |
| Initial Moisture Content | 24.3 % | Final Moisture Content | 25.6 % |
| Initial Dry Density | 97.6 pcf | Final Dry Density | 100.6 pcf |
| Initial Wet Density | 121.4 pcf | Final Saturated Density | 126.3 pcf |




Swell/Consolidation Test ASTM D4546

Project Name Montrose 552 Acre Ranch
 Location TP#10 @5'
 Sample # GU
 Soil Description dark gray-brown CLAY
 Comments clay shale

Date 02/06/06
 Project # 06-023-GEO
 Sample by TB
 Test by SM
 Test for TB
 Drafting by BAU

| | | | |
|--|-----------|-------------------------|-----------|
| Initial compression (Due to 100 psf pressure) <u>-2.60%</u> | | | |
| Initial swell (Due to water & 100 psf pressure) <u>-4.75%</u> | | | |
| Total consolidation (Due to water & 2000 psf pressure) <u>-7.26%</u> | | | |
| Estimated swelling pressure <u>=650 psf</u> | | | |
| Initial Moisture Content | 11.6 % | Final Moisture Content | 23.8 % |
| Initial Dry Density | 110.8 pcf | Final Dry Density | 102.6 pcf |
| Initial Wet Density | 123.7 pcf | Final Saturated Density | 127.0 pcf |




Swell/Consolidation Test
 ASTM D4546

Project Name Montrose 552 Acre Ranch
 Location TP#13 @4.5'
 Sample # H46
 Soil Description gray brown gravelly lean CLAY with sand (CL)
 Comments _____

Date 02/06/06
 Project # 06-023-GEO
 Sample by TB
 Test by SM
 Test for TB
 Drafting by BAU

| | | | |
|--|-----------|-------------------------|-----------|
| Initial compression (Due to 100 psf pressure) <u>-1.03%</u> | | | |
| Initial swell (Due to water & 100 psf pressure) <u>-2.27%</u> | | | |
| Total consolidation (Due to water & 2000 psf pressure) <u>-2.77%</u> | | | |
| Estimated swelling pressure <u>=950 psf</u> | | | |
| Initial Moisture Content | 18.3 % | Final Moisture Content | 22.4 % |
| Initial Dry Density | 105.4 pcf | Final Dry Density | 104.1 pcf |
| Initial Wet Density | 124.7 pcf | Final Saturated Density | 127.5 pcf |




Swell/Consolidation Test

ASTM D4546

Project Name Montrose 552 Acre Ranch
 Location TP#16 @4'
 Sample # HM
 Soil Description light brown-gray lean CLAY with sand (CL)
 Comments _____

Date 02/06/08
 Project # 06-023-GEO
 Sample by TB
 Test by SM
 Test for TB
 Drafting by BAU

| | | | |
|---|-----------|-------------------------|-----------|
| Initial compression (Due to 100 psf pressure) = <u>0.99%</u> | | | |
| Initial swell (Due to water & 100 psf pressure) = <u>5.30%</u> | | | |
| Total consolidation (Due to water & 4000 psf pressure) = <u>8.41%</u> | | | |
| Estimated swelling pressure = <u>1280 psf</u> | | | |
| Initial Moisture Content | 12.5 % | Final Moisture Content | 23.5 % |
| Initial Dry Density | 102.9 pcf | Final Dry Density | 101.8 pcf |
| Initial Wet Density | 115.8 pcf | Final Saturated Density | 125.7 pcf |




Swell/Consolidation Test
 ASTM D4546

Project Name Montrose 552 Acre Ranch
 Location BH06-1 @5-6.5'
 Sample # BD
 Soil Description reddish yellow clayey SAND with gravel (SC)
 Comments _____

Date 02/27/06
 Project # 06-023-GEO
 Sample by TB
 Test by SM
 Test for TB
 Drafting by BAU

Initial compression (Due to 100 psf pressure) -0.59%
 Initial consolidation (Due to water & 100 psf pressure) -0.29%
 Total consolidation (Due to water & 2000 psf pressure) -7.97%

| | | | |
|--------------------------|----------|-------------------------|-----------|
| Initial Moisture Content | 9.6 % | Final Moisture Content | 28.8 % |
| Initial Dry Density | 87.6 pcf | Final Dry Density | 94.3 pcf |
| Initial Wet Density | 96.0 pcf | Final Saturated Density | 121.5 pcf |



Swell/Consolidation Test


ASTM D4546

Project Name Montrose 552 Acre Ranch
 Location BH06-1 @10-11'
 Sample # DO
 Soil Description brown clayey SAND with gravel (SC)
 Comments _____

Date 02/27/06
 Project # 06-023-GEO
 Sample by TB
 Test by SM
 Test for TB
 Drafting by BAJ

Initial compression (Due to 100 psf pressure) -0.39%
 Initial swell (Due to water & 100 psf pressure) -7.40%
 Total consolidation (Due to water & 4000 psf pressure) -8.89%
 Estimated swelling pressure = 1610 psf

| | | | |
|--------------------------|-----------|-------------------------|-----------|
| Initial Moisture Content | 6.7 % | Final Moisture Content | 23.7 % |
| Initial Dry Density | 109.9 pcf | Final Dry Density | 103.1 pcf |
| Initial Wet Density | 117.2 pcf | Final Saturated Density | 127.6 pcf |




Swell/Consolidation Test

ASTM D4546

Project Name Montrose 552-Acre Ranch
 Project Location Government Springs Rd.
 Client Burns
 Test Location TP#17 @4.0'
 Sample # PX
 Soil Description yellow brown CLAY with sand

Date 04/03/06
 Project # 06-023-GEO
 Sample by TB
 Test by BAU

| | | | |
|--|-----------|-------------------------|-----------|
| Initial compression (Due to 100 psf pressure) <u>-1.28%</u> | | | |
| Initial swell (Due to water & 100 psf pressure) <u>+2.09%</u> | | | |
| Total consolidation (Due to water & 2000 psf pressure) <u>-5.12%</u> | | | |
| Estimated swelling pressure <u>=530 psf</u> | | | |
| Initial Moisture Content | 10.8 % | Final Moisture Content | 25.8 % |
| Initial Dry Density | 97.0 pcf | Final Dry Density | 99.2 pcf |
| Initial Wet Density | 107.5 pcf | Final Saturated Density | 124.8 pcf |




Swell/Consolidation Test
 ASTM D4546

Project Name Montrose 552-Acre Ranch
 Project Location Government Springs Rd.
 Client Burns
 Test Location TP#20 @3.5'
 Sample # NX
 Soil Description light yellow brown CLAY

Date 04/03/06
 Project # 06-023-GEO
 Sample by TB
 Test by BAU

| | | | |
|--|----------|-------------------------|-----------|
| Initial compression (Due to 100 psf pressure) <u>-0.50%</u> | | | |
| Initial swell (Due to water & 100 psf pressure) <u>-1.61%</u> | | | |
| Total consolidation (Due to water & 2000 psf pressure) <u>-8.56%</u> | | | |
| Estimated swelling pressure <u>380 psf</u> | | | |
| Initial Moisture Content | 9.8 % | Final Moisture Content | 36.6 % |
| Initial Dry Density | 77.7 pcf | Final Dry Density | 80.8 pcf |
| Initial Wet Density | 85.3 pcf | Final Saturated Density | 110.4 pcf |



BUCKHORN GEOTECH

Montrose 552-Acre Ranch Summary of Percolation Tests

| TEST PIT | Depth (inches) | Percolation Rate (mpi) | Soil Description | Setting |
|----------|----------------|------------------------|--|---------------------|
| TP#1 | 14 | 240 | brown gray SILT and CLAY | escarpment |
| | 25 | 160 | dk. gray brown SHALE | |
| | 33 | 320 | dk. gray brown SHALE | |
| | 47 | 160 | dk. gray brown SHALE | |
| TP#2 | 13 | 80 | dk. brown SILT and CLAY | agricultural fields |
| | 38 | >320 | gray-brown SILT and CLAY | |
| | 53 | 160 | gray-brown SHALE RESIDUUM | |
| TP#3 | 26 | 40 | brown SILT and CLAY | agricultural fields |
| | 41 | 40 | brown SILT and CLAY | |
| | 53 | 80 | brown SILT and CLAY | |
| TP#4 | 13 | 53 | dk. brown SILT and CLAY | agricultural fields |
| | 41 | >320 | brown SILT and CLAY | |
| | 54 | >320 | gray-brown SILT and CLAY | |
| | 61 | >320 | gray-brown SILT and CLAY | |
| TP#5 | 12 | 80 | dk. brown SILT and CLAY | agricultural fields |
| | 28 | >320 | gray-brown SILT and CLAY | |
| | 36 | >320 | gray-brown SILT and CLAY | |
| | 52 | >320 | gray-brown SILT and CLAY | |
| TP#6 | 26 | 80 | gray-brown SILT and CLAY | agricultural fields |
| | 37 | 15 | reddish-brown clayey GRAVEL | |
| | 61 | 8 | reddish-brown GRAVEL and COBBLES | |
| TP#7 | 13 | 16 | dk. brown SILT and CLAY | agricultural fields |
| | 37 | >320 | gray brown SILT and CLAY | |
| | 51 | 80 | gray brown SILT and CLAY w/ sand | |
| | 64 | 80 | gray brown SILT and CLAY w/ sand | |
| TP#8 | 36 | 16 | brown sandy GRAVEL w/ clay | escarpment |
| | 48 | 20 | brown sandy GRAVEL w/ clay | |
| | 57 | 16 | brown sandy GRAVEL w/ clay | |
| TP#9 | 36 | 160 | gray brown gravelly SILT and CLAY | agricultural fields |
| | 52 | 160 | gray brown gravelly SILT and CLAY | |
| | 66 | 160 | gray brown gravelly SILT and CLAY | |
| TP#10 | 14 | >320 | dk. gray-dk. brown SILT and CLAY | escarpment |
| | 39 | 80 | dk. brown SILT and CLAY | |
| | 47 | 160 | gray brown SILT and CLAY (residuuum) | |
| | 60 | 5 | gray brown SHALE | |
| TP#11 | 36 | 32 | brown sandy GRAVEL w/ clay | escarpment |
| | 50 | 20 | brown sandy GRAVEL w/ clay | |
| | 62 | 32 | brown sandy GRAVEL w/ clay | |
| TP#12 | 12 | 160 | dk. brown SILT and CLAY | agricultural fields |
| | 46 | >320 | gray brown SILT and CLAY | |
| | 53 | 160 | gray brown SILT and CLAY | |
| | 66 | >320 | gray brown SILT and CLAY | |
| TP#13 | 14 | 160 | dk gray-dk. brown SILT and CLAY | agricultural fields |
| | 36 | >320 | gray brown SILT and CLAY | |
| | 44 | 160 | gray brown SILT and CLAY w/ sand | |
| | 52 | 320 | gray brown SILT and CLAY w/ sand | |
| TP#14 | 48 | 160 | brown sandy GRAVEL w/ clay | agricultural fields |
| | 57 | 160 | brown sandy GRAVEL w/ clay | |
| | 70 | 23 | brown sandy GRAVEL w/ clay | |
| TP#15 | 15 | 53 | brown silty clayey SAND and GRAVEL | escarpment |
| | 38 | >320 | gray brown SILT and CLAY w/ gravel | |
| | 51 | 160 | gray brown SILT and CLAY | |
| | 61 | >320 | gray brown SILT and CLAY | |
| TP#16 | 14 | 53 | brown clayey GRAVEL w/ sand and silt | escarpment |
| | 42 | 160 | brown sandy CLAY and GRAVEL w/ silt | |
| | 59 | 5 | lt. brown gray SILT and CLAY w/ gravel | |
| | 77 | 53 | lt. brown gray SILT and CLAY w/ gravel | |
| TP#17 | 38 | 16 | lt. brown clayey SAND w/ gravel | mesa top |
| | 51 | 32 | lt. brown clayey SAND w/ gravel | |
| | 66 | 40 | lt. brown clayey SAND w/ gravel | |
| TP#18 | 37 | 53 | lt. brown clayey SAND and GRAVEL | mesa top |
| | 59 | 20 | gray brown sandy GRAVEL & COBBLES | |
| | 76 | 70 | gray brown sandy GRAVEL & COBBLES | |
| TP#19 | 44 | 23 | brown clayey SAND w/ gravel | mesa top |
| | 68 | 27 | gray brown sandy GRAVEL & COBBLES | |
| | 76 | 5 | gray brown sandy GRAVEL & COBBLES | |
| TP#20 | 44 | 11 | lt. brown clayey SAND w/ gravel | mesa top |
| | 60 | 4 | gray brown sandy GRAVEL & COBBLES | |
| | 71 | 10 | gray brown sandy GRAVEL & COBBLES | |

Glossary of Engineering & Soils Terms

| | |
|--|---|
| Active Earth Pressure | The pressure that a soil exerts against a vertical surface which is allowed a certain degree of flexure or rotational freedom. |
| Allowable soil bearing capacity | The recommended maximum contact stress developed at the interface of the foundation and the supporting soil. Given in psf (pounds per square foot). |
| Alluvial Fan | A cone-shaped deposit of water-transported material (alluvium). They typically form at the base of topographic features where there is a distinct decrease in gradient. Consequently, alluvial fans tend to be coarse-grained near their mouths and relatively fine-grained at their edges. |
| Alluvium | Rock and soil material deposited by moving water. Rocks are generally rounded and sorted by size as they are worked by water. Found in river channels or alluvial fans. |
| ASTM | American Society for Testing and Materials (a national non-profit organization which writes testing standards for materials, products, systems and services). |
| At-Rest Earth Pressure | The pressure that soil exerts upon a vertical surface which is restrained from any movement. |
| Atterberg Limits | Named for a Swedish scientist, Atterberg Limits are defined by the water content that produces a specified soil consistency. See <i>Liquid Limit</i> and <i>Plastic Limit</i> . |
| Backfill | A specified material placed and compacted in a confined area. |
| Backslope Zone | The area in which loads applied to the ground surface or increase in slope angle will increase the total lateral force against a retaining wall. |
| Base Course | A layer of specified material placed on a subgrade or subbase. |
| Bedrock | Sedimentary, igneous, or metamorphic rock that has not been weathered or broken down by the elements of water, ice, wind, or gravity. Also referred to as "formational" material, as bedrock is known as a particular formation for the region. |
| Bench | A horizontal or near-horizontal surface in a sloped deposit. |
| Calcareous | Containing calcium carbonate (lime). A distinct layer of calcium carbonate hardpan is called caliche. |
| Clay | A fine-grained soil (finer than 0.002 mm) composed of very small platy (flat) particles that are smaller than silt particles. It forms lumps or clods when dry and is plastic (Plasticity Index greater than 4) and sticky when wet. |
| Cohesionless Soil | Non-plastic granular soils (silt, sand, gravel) composed of bulky grains that are not attracted to each other with the addition of water. |
| Cohesive Soil | Soils (i.e., clays and some silts) in which adsorbed water and particle attraction work together to produce a mass which holds together and deforms plastically. |
| Colluvium | Rock and soil material deposited by gravity. Rocks are generally angular to subangular, loose and not sorted. Found below steep slopes and at the mouth of canyons; talus and cliff debris are included. |

| | |
|--------------------------------|---|
| Compaction | The decrease in volume of an unsaturated soil mass due to a decrease in the void spaces, usually by mechanical means. |
| Consolidation | The decrease in soil volume due to a release of water within a saturated soil volume. As a soil consolidates, its void ratio decreases. Loosely, the term is used to describe the result of collapse of a loose soil structure. |
| Crawlspace | The space beneath the house that has a raised stemwall foundation and is typically 18 to 36 inches in height. |
| Creep | A slow, nearly continuous movement of soil caused by changes in soil moisture and the downhill force of gravity. |
| Dead Load | Static loads transferred to the foundation, usually the weight of building materials, but can also be the loads imposed by retained soil or a constructed slope. |
| Debris Flow | Debris flows are rapid flood-like events consisting of mud, water, rock and organic debris and that have 20 to 80% particles coarser than sand sizes. Steep slopes, weak or weathered rock, a lack of vegetative cover, and abnormal precipitation contribute to debris flows. (See mud flow) |
| Differential Settlement | Unequal settlement between or within foundation elements of a structure. |
| Dispersive Soils | Fine-grained soils whose clays have been neutralized by an abundance of cations which are then susceptible to removal (dispersion) from the soil matrix. This weakens soil strength; piping and gullyng are common features in this soil. |
| Drilled Caisson | A deep foundation system that consists of reinforced concrete piers cast into a drilled hole that extends into bedrock or other suitable material. |
| Driven Pile | A deep foundation system that consists of steel, concrete, or timber that is driven into bedrock or other suitable material. |
| Existing Fill | Materials deposited through the action of man prior to geotechnical exploration of the site. |
| Existing Grade | The ground surface at the time of field exploration. |
| Expansive Soil | A soil containing clay which expands (increases in volume) when exposed to an increase in moisture. |
| Fine Grained Soil | Soils composed of silt and/or clay-sized particles. |
| Flowing Avalanche | The turbulent cascade of slabs and blocks of relatively high-density (>25 pcf) snow and air down a slope. |
| Fluvial | Deposited or transported by a stream or river. |
| Fluvioglacial | Alluvial deposits derived from the rivers originating from the melting of glaciers. Glacial outwash is the term used to describe fluviglacial deposits. |
| Formational Material | See bedrock. Also known as the "R" horizon. |
| Grade Beam | Typically, concrete beams that are constructed at or just below ground elevation that are used to transfer building loads to deep foundation elements. Walls and floor systems are then built upon the grade beams. |

| | |
|-------------------------------|---|
| Groundwater | Water that is resident beneath the ground surface in porous soil and rock material. This level can fluctuate due to seasonal changes and irrigation. |
| Heave | Upward movement of soil or foundation components. |
| Hinge Point | Toe of excavated wall without footing or outside edge of concrete if footing is used. |
| Hummocky | The bumpy or chaotic terrain on the slumped material typically resulting from a landslide or glacial deposit. The rock and soil materials are unsorted and unsystematic. |
| Hydrocompactive Soils | Soils that have considerable voids, thus making it susceptible to consolidation in the presence of water. |
| Jumping Jack | A construction machine, used to compact both cohesive and cohesionless soils, that consists of a curved shoe that tamps the soil in an up and down motion. |
| Landslide | The general term for the rapid downward and outward movement (flow, slide or fall) of slope-forming bedrock, rock debris and "earth" (fine-grained fragmental debris). See "slump," a type of landslide. |
| Lifts | Horizontal layers of fill, generally in 6 to 8-inch increments. |
| Liquid Limit (LL) | The water content above which a soil behaves as a liquid. |
| Live Load | Transient loads introduced onto a structure and its foundation due to occupancy, wind, snow and rain, earthquakes, changes in groundwater, and other environmental factors. |
| Loam | An mixture of sand, silt and clay. It is easily crumbled when dry and has a slightly gritty, yet fairly smooth feel, and is often slightly plastic. |
| Monolithic Slab | A shallow foundation system that consists of a single unit of reinforced concrete with downturned edges and may include thickened ribs on the underside of the slab. |
| Moraine | Deposits formed by direct glacial action. There are many forms of moraines, but they generally consist of unsorted, unstratified, subrounded to subangular materials deposited by glacial ice. Also generally known as "drift" or "till." |
| Mottling | The discoloration of a soil due to the reaction of water with clay minerals during prolonged periods of saturation. Red colors indicate the presence of iron oxides in an oxidized state and gray indicate the removal of free iron in reducing conditions. |
| Mud Flow | Mud flows are flood-like events that have 80% or more mud and sand. Over-saturation of fine-grained soils triggers mud flows, which are a rapid failure or slippage of mud and other debris entrained in the movement. (See debris flow) |
| Native Grade | The naturally occurring ground surface (before disturbance). |
| Native Soil | Naturally occurring on-site soil. |
| Parent Material | The formational material from which a soil is derived. |
| Passive Earth Pressure | The resistance of a soil against movement when a lateral force is exerted upon it. |

| | |
|--|--|
| Piping | A feature in fine-grained soils whereby water preferentially follows root zones, animal burrows and surface soil cracks, and carries soil particles downwards through voids, leaving behind weak vertical planes, voids, and/or tunnels in the soil structure. |
| Pistol Butting | When the base of tree trunk is widened and bent upwards due to soil creep or slope movement. The tree continues to grow vertically despite the ground moving downslope, thus creating a shape like a "pistol butt" in the expanded trunk. |
| Plastic Index (PI) | The difference between Liquid and Plastic Limits (LL - PL). This represents the moisture content range that the soil is in the plastic state. The larger the PI, the more plastic a soil is. |
| Plastic Limit (PL) | The water content at which a soil becomes brittle after being in the plastic state. The soil breaks apart or crumbles when its moisture content is equal to or less than its PL. |
| Plastic Soil | A predominately silt or clay soil that exhibits plastic (deformable) behavior. |
| Powder Avalanche | The relatively low-density (12.5 pcf), high velocity, turbulent force of snow, air and entrained debris that precedes and extends beyond a dry-snow avalanche. The powder and air blast can travel at speeds in excess of 100 mph. |
| Proctor Density (Standard & Modified) | A laboratory compaction procedure to determine the maximum dry density and optimum moisture content of soil. The Standard Proctor procedure uses a 5.5-lb hammer and 3 lifts, while the Modified Proctor procedure uses a 10-lb hammer and 5 lifts. |
| Refusal | When very dense native material is encountered which cannot be excavated or penetrated further by whatever equipment is being used. |
| Rock | A natural aggregate of mineral grains connected by strong cohesive forces, usually requiring heavy equipment, drilling, wedging, blasting or other methods of extraordinary force for excavation. |
| Scarify | To mechanically loosen or break down existing soil structure. |
| Settlement | Downward movement of foundation components due to compression of a soil mass. |
| Shale | A thinly-bedded rock formation composed of clay or silt muds that have been solidified into rock. The Mancos Shale Formation in Colorado is of marine origin. |
| Silt | Fine-grained soil particles measuring 0.002 to 0.075mm, which are larger than clay but smaller than sand. Silt can exhibit plastic characteristics. |
| Slab-on-Grade | A concrete layer cast directly upon a base, subbase or subgrade. |
| Slope | The angle of a hillside, usually expressed in degrees or percent (elevation drop per given distance). |
| Slump | The rotational slip along a concave-up surface of rupture. A "main scarp" is the crescent shaped failure plane formed at the source of the slump. A slump is a form of landslide most common in thick, homogeneous, cohesive materials such as clay. |
| Soil | Any unconsolidated, excavatable earth material composed of discrete solid particles, with air or liquids between, that is the result of the chemical and mechanical weathering of rock. |
| Soil Log | A graphic representation of a column of soil indicating textural changes and general properties of soil or rock types encountered in a test pit or boring. |

| | |
|-------------------------|---|
| Spread Footing | A shallow foundation system that consists of a wide (typically from 12 to 48 inches) "foot" of reinforced concrete upon which vertical wall components are built. |
| Stemwall | A vertical concrete foundation component, normally 6 to 12 inches wide, that rests on the spread footing and extends up to the floor level. |
| Subbase | A layer of specified material between the subgrade and base course. |
| Subbase Grade | Top of subbase elevation. |
| Subgrade | Prepared native soil surface. |
| Subsoil | The layer of soil below the topsoil and above the substratum, that has undergone pedogenesis (soil formation). The "B" horizons. |
| Substratum | The layer of soil below the subsoil that has not undergone soil genesis. It contains weathered parent material. The "C" horizons. |
| Swell Potential | The potential of a soil to expand (increase in volume) due to absorption of moisture. |
| Tension Cracks | Transverse cracks (linear openings) in the soil due to soil movement. |
| Topsoil | The surface layer of soil containing organic material and roots. The "A" horizons. |
| Transverse | A feature (like a crack or ridge) that is at right angles to the slope of a hillside or the general trend of a valley. |
| Vesicular Pores | Sponge-like openings in a fine-grained soil that are the result of the solution and dispersal of clay particles. The pores are discontinuous and vary in size. These pores are often found in soils that have been irrigated. |
| Vibratory Roller | A construction machine, used to compact soil and aggregate material, that consists of a heavy vibrating drum that is rolled across a surface. |
| Void Ratio | A ratio of the volume of voids (pore spaces) to the volume of mass of a soil. |
| Water Table | The relatively continuous and consistent level of groundwater below the ground surface. |
| Weathering | The breakdown of intact masses of rock into smaller pieces by mechanical, chemical or solution processes. |